

TECHNICAL DATA

TAMPER

BT 60, BT 65



Maximum reliability and longevity
All around engine protection




More transparency
Hour meter RPM-meter with service indicator



Simple operation
Engine and fuel supply with combined switch

Shipping dimensions in m3

BT 60	0,262
BT 65	0,262



Standard Equipment

- Engine Protection System
 - Protective engine covering
 - Two-stage double air filter system
 - Automatic oil level control
 - Dual fuel filter system
- Vibration insulated steering bow
- Self-cleaning air filter housing
- Protective covering
- Single point lifting device
- Recoil starter
- Plastic castor as loading aid
- Infinitely variable frequency
- Combination of engine stop/fuel switch
- h-/ rpm meter
- 3-2-1 Warranty

Dimensions in mm

	B	H	L	L1	W
BT 60	350	1030	728	335	230
BT 65	350	1030	728	335	280

Optional Equipment

- Transport device with puncture proof wheels
- Tamp foot widths (160-330mm)
- Tamp foot extensions
- Special painting
- Tool kit
- Service Kit
- Operator protection contact breaker switch
- TOUGH WARRANTY

Technical Data

Weights

Operating weight CECE	kg	58	68
Basic weight	kg	57	67

Dimensions

Working width (tamper plate)	mm	230	280
------------------------------------	----	-----	-----

Driving Characteristics

Working speed max.	m/min	20	20
Area coverage max.	m ² /h	276	336

Drive

		BOMAG BT 60	BOMAG BT 65
Engine manufacturer		Honda	Honda
Type		GXR 120	GXR 120
Emission stage		CARB Phase III	CARB Phase III
Cooling		air	air
Number of cylinders		1	1
Performance SAE J 1349	kW	2,8	2,8
Fuel		gasoline	gasoline
Drive system		mech.	mech.
Fuel comsump. aver. during operation	l/h	0,9	0,9

Exciter system

Frequency	Hz	10- 11,8	10- 11,8
Impact force	kN	15,0	17,0

Capacities

Fuel	l	3,0	3,0
------------	---	-----	-----

Technical modifications reserved. Machines may be shown with options.

