

Dynamometer

D2000A

- Accuracy higher than 0,2% FS
- Very clear red digit LED display / Visible at long distances and in bright daylight
- Compact size / high strenght steel
- Fully serviceable parts
- Built-in rechargeable batteries
- Very easy to use
- Available ex. stock (DK)



Specifications:

Application areas:	Under hook crane weighing. Crane and hoist calibration and proof load testing.
Capacity:	2T - 120T.
Accuracy:	> 0,2%.
Safe overload:	120 %
Materials:	High strenght steel. Silver chrome plated surface.
Charger:	NIMH, 4-10 cell.
IP class:	IP 64
Display:	Bright LED
Batteries:	AA 1,5V (rechargeable)
Operating time:	8-14 hours
Operating Temp:	-20°C to +40°C

Item No:	Capacity (T)	Dimensions (LxWxH)	Bolt dia. (mm)	Weight (kg)	Increment (kg)
D2000-ALU-2T	2	200 x 100 x 66	20	1,20	1
D2000A-6T	6,5	220 x 95 x 75,4	30	3,30	5
D2000A-12T	12,5	250 x 95 x 83	35,5	4,55	10
D2000A-25T	25	340 x 108 x 83	51,0	7,60	10
D2000A-55T	55	440 x 160 x 94,4	73,0	19,10	50
D2000A-120T	120	500 x 200 x 120,2	100,0	39,50	100

Accessory options:

- Handheld display (2000B-6V-RTX).



- PC datalog software (DYNALOG)

