


Plast-o-Seal®

Permanently plastic universal sealant
Solvent free with no unpleasant odour
enables immediate assembly




- For sealing the smooth treated flanges of machine, gearbox and motor casing flanges.
- To improve the performance of both old and new gaskets made from paper, cork, felt etc.
- Solvent free - odourless
- Remains permanently plastic, both before and after assembly.
- Easy joint dismantling.
- Economical in use.
- Very good resistance to most fuels, mineral oils, water, air, coolant mixtures based on methanol and glycol, antifreezes, kerosene, fluorocarbon refrigerants etc.
- Max. gap filling capability up to 0,1 mm (without a gasket).
- Non-sag can be applied to vertical surfaces.
- Temperature resistant from -50°C to +200°C briefly up to +250°C
- Compensates for manufacturing defects such as scoring and scratches enabling accurate assembly.
- Allows accurate assembly and construction with low tolerances.
- No need to overtighten fixings during assembly.
- Non corrosive
- Neither contains any substances that disturb lacquer wettings (e.g. silicone).
- Fluorescent blue colour.




Technical data:

Temperature resistant:
from -50°C up to +200°C, briefly up to +250°C




Chemical base:
polyester resin

Viscosity:
950.000 up to 1.650.000 mPa•s



Colour:
blue (fluorescent)

Gap filling:
max 0,10 mm without gasket



Working temperature:
from +5°C up to +35°C.

Specific weight:
1,12 g/cm³



Shelf life:
24 months at room temperature
(approx. +20°C)



Any product specifications and recommendations given herein must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do warrant the continuously high quality of our products being free from defects in accordance with and subject to our General Sales Conditions. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

Distributed by:

WEICON GmbH & Co. KG
Königsberger Str. 255 • DE-48157 Münster
P.O.B. 84 60 • DE-48045 Münster

Tel. +49 (0) 251 / 93 22-0
Fax +49 (0) 251 / 93 22-44
Fax +49 (0) 251 / 93 22-33 Export

www.weicon.de
eMail: info@weicon.de
Tel. 0700/weiconde