



Industrial Hoses



INDUSTRIAL HOSES





CODAN.COM


AIR & WATER HOSE

1220	Air/water hose BS5718/2	WP: 20 bar BP: 60 bar Work °C: -30° – +80 °C	Inside: NR/SBR ID: 13 – 102 mm	Outside: NR/SBR Colour: Yellow	
1232	Air/water hose ISO1403:1995	WP: 10 bar BP: 30 bar Work °C: -30° – +100 °C	Inside: EPDM ID: 12.7 – 127 mm	Outside: EPDM Colour: Red	
3304	Air/water hose Codan standard	WP: 25 bar BP: 80 bar Work °C: -40° – +100 °C	Inside: EPDM ID: 6.3 – 38.1 mm	Outside: EPDM Colour: Grey	
3310	Air/water hose Codan standard	WP: 10 bar BP: 40 bar Work °C: -40° – +100 °C	Inside: EPDM ID: 6.3 – 25.4 mm	Outside: EPDM Colour: Black	
3311	Air/water hose Codan standard	WP: 20 bar BP: 60 bar Work °C: -40° – +100 °C	Inside: EPDM ID: 6.3 – 25 mm	Outside: EPDM Colour: Black	
3320	Air/water hose EN ISO 8031: 1997 ANTISTATIC	WP: 20 bar BP: 80 bar Work °C: -40° – +95 °C	Inside: EPDM ID: 6.0 – 25 mm	Outside: EPDM Colour: Black	
3321	Air/water hose EN ISO 8031: 1997 ANTISTATIC	WP: 20 bar BP: 60 bar Work °C: -30° – +80 °C	Inside: EPDM ID: 6.3 – 25 mm	Outside: EPDM Colour: Black	
1228	Air/water hose	WP: 20 bar BP: 60 bar Work °C: -30° – +140 °C	Inside: EPDM ID: 6.3 – 25 mm	Outside: EPDM Colour: Blue	
1229	Air/water hose EN ISO 8031: 1997	WP: 20 bar BP: 60 bar Work °C: -30° – +140 °C	Inside: EPDM ID: 6.3 – 25 mm	Outside: EPDM Colour: Red	

COOLANT HOSE

4801	Coolant / Anti-freeze / Glycol SAE J20 R3	WP: 10 bar BP: 40 bar Work °C: -40° – +100 °C	Inside: EPDM ID: 9.5 – 25 mm	Outside: EPDM Colour: Black	
4804	Coolant / Anti-freeze / Glycol DIN73411:1979	WP: 5 bar BP: 15 bar Work °C: -30° – +90 °C	Inside: EPDM ID: 13 – 125 mm	Outside: EPDM Colour: Black	

FUEL HOSE

3111	Petrol / Diesel SAE J30 R6 / EN 590:2010	WP: 12 bar BP: 50 bar Work °C: -30° – +100 °C	Inside: NBR/PVC ID: 3.2 – 16 mm	Outside: Polyester Colour: Black	
3122	Petrol / Diesel SAE J30 R7 / EN 590:2010	WP: 20 bar BP: 60 bar Work °C: -40° – +135 °C	Inside: NR/SBR ID: 4 – 15.6 mm	Outside: NR/SBR Colour: Black	
3133	Petrol / Diesel / Bio-diesel SAE J30 R9	WP: 10 bar BP: 62 bar Work °C: -30° – +130 °C	Inside: FKM/NBR ID: 4.8 – 15.6 mm	Outside: CPE Colour: Black	

ADBLUE

3201 AdBlue - Def - Urea Hose DIN 73411/SAE J20
WP: 10 bar **BP:** 30 bar **Inside:** EPDM **Outside:** EPDM
Work °C: -40° – +135 °C **ID:** 3.5 – 10 mm **Colour:** Black



OIL HOSE


1900 Petrol Tanker Hose EN12115
WP: 10 bar **BP:** 30 bar **Inside:** NBR **Outside:** CR
Work °C: -35° – +70 °C **ID:** 32 – 203 mm **Colour:** Black



2901 Oil / Petrol S/D Codan standard
WP: 10 bar **BP:** 30 bar **Inside:** NBR **Outside:** CR
Work °C: -40° – +70 °C **ID:** 25 – 152 mm **Colour:** Black




3006 Oil / Grease / Universal Codan standard **ANTISTATIC**
WP: 20 bar **BP:** 80 bar **Inside:** NBR **Outside:** CR
Work °C: -40° – +100 °C **ID:** 6.3 – 51 mm **Colour:** Black



3009 Oil / Grease / Universal Codan standard
WP: 15 bar **BP:** 45 bar **Inside:** NBR **Outside:** NBR/PVC
Work °C: -30° – +100 °C **ID:** 5 – 25 mm **Colour:** Black



3012 Oil / Grease / Universal Codan standard
WP: 25 bar **BP:** 75 bar **Inside:** NBR **Outside:** NBR/PVC
Work °C: -25° – +100 °C **ID:** 6 – 25 mm **Colour:** Black



WELD HOSE / LPG

2601 LPG / Propane / Butane ISO3821:2019
WP: 20 bar **BP:** 60 bar **Inside:** NBR **Outside:** EPDM
Work °C: -30° – +80 °C **ID:** 5 – 11 mm **Colour:** Orange




2614 LPG / Propane / Butane EN 16436-1:2014 CLASS 2
WP: 10 bar **BP:** 30 bar **Inside:** NBR **Outside:** EPDM
Work °C: -30° – +80 °C **ID:** 5 – 11 mm **Colour:** Orange



2654 LPG / Propane / Butane EN 16436-1:2014 CLASS 3
WP: 30 bar **BP:** 90 bar **Inside:** NBR **Outside:** EPDM
Work °C: -30° – +80 °C **ID:** 4 – 11 mm **Colour:** Orange



2801 Acetylene ISO3821:2019
WP: 20 bar **BP:** 60 bar **Inside:** EPDM **Outside:** EPDM
Work °C: -30° – +80 °C **ID:** 5 – 51 mm **Colour:** Red



2802 Oxygen ISO3821:2019
WP: 20 bar **BP:** 60 bar **Inside:** SBR/EPDM **Outside:** EPDM
Work °C: -30° – +80 °C **ID:** 5 – 51 mm **Colour:** Blue



2803 Oxygen / Acetylene ISO3821:2019 **Outside:** EPDM
WP: 20 bar **BP:** 60 bar **Inside:** (Ace) EPDM (Oxy) SBR/EPDM
Work °C: -30° – +80 °C **ID:** 4x4 – 10x10 mm **Colour:** Red / Blue



2808 Oxygen / LPG (Propane / Butane) ISO3821:2019
WP: 20 bar **BP:** 60 bar **Inside:** NBR **Outside:** SBR
Work °C: -25° – +80 °C **ID:** 5x5 – 10x10 mm **Colour:** Blue/Orange



2823 Argon ISO3821:2019
WP: 20 bar **BP:** 60 bar **Inside:** CIIR **Outside:** CIIR
Work °C: -25° – +100 °C **ID:** 5.2 – 15 mm **Colour:** Black



Codan Rubber A/S

Since 1925 Codan has been devoted to creating flexible connections, rubber moulded parts and sealing solutions.

Codan now holds a leading position as an OEM and Tier 1 supplier to the automotive, industrial and agriculture sectors.

Codan production facilities are TS16949 / ISO9001 and ISO14001 accredited.

Codan's 6000 m² European warehouse, production and test site in Køge stocks hoses for immediate delivery.

Codan's flexible hose systems are specified for respiratory equipment, vehicles, construction and farming machinery, food processing, gas and welding appliances and for use in the manufacturing industry.

Codan's extruded profiles and moulded parts are used extensively in cars, buses and plant machinery and are designed to meet OEM specifications.

Authorized Codan Rubber dealership

Codan Rubber A/S
Værkstedsvej 45-49 · DK-4600 Køge · Tlf. +45 56646464 · www.codan.com