

Danish Krone

CI-10 CASHINFINITY® Compact cash recycling system

SMART Cash Management

GLORY Retail Solution offers SMART cash management. It provides total secure closed cash handling, centralised control of cash inventory and optimisation of all cash processes throughout a store. CASHINFINITY[®] is the most advantageous cash management system with remarkable flexibility and extensibility for retailers to fit any size of store, various business segments and each investment plan.





reddot design award winner 2012

Glory Global Solutions is a World Expert in cash management, delivering technology and solutions that provide security, productivity and innovation to our customers. These solutions are supported by the technical expertise of GLORY Group of Japan, the pioneer in development and manufacture of money handling machines across the financial, retail, vending machine, amusement and gaming industries for nearly 100 years. Across the world, Glory Global Solutions is trusted by thousands of organisations to ensure their cash is managed securely and efficiently whilst delivering the ultimate in productivity. 2,500 professionals, including over 1,300 service and support staff and 350 business partners cover over 128 countries delivering these solutions – wherever money moves.

0

0

CI-10 – Technical Information



CI-10

The compact cash recycling system CI-10 which consists of a banknote recycler (CI-10B) and a coin recycler (CI-10C) can be applied to various markets: bakeries, shops, supermarkets, and hypermarkets, etc. The CI-10 integrated into an existing POS system enables automated cash handling, improves security, staff productivity, customer service and fund efficiency. The CI-10 is stylishly designed with straight lines, it can be easily integrated into cash desks and self-checkouts. A "Follow me" LED sign assists the customer to operate the system independently and comfortably. If the CI-100 cash recycling system is added, the CI-10 and CI-100 offer a secure closed cash management solution. A stacking collection cassette is also available in case the CI-100 is not part of the system.

- Data interface protocol: SOAP over HTTP(S)
- Data interface port: LAN

Secure closed cash management with CI-100

The interface cassette of the CI-10 enables secure closed cash management (possible with CI-100).



Stylish design and "Follow me" LED sign

Easy integration into cash desks and self-checkouts and intuitive operation for any customer.





Avoids handing over partial

change to a customer in the

Exit shutter



*SCC: Stacking collection cassette *IFC: Interface cassette *The capacity of coins is calculated in DKK 1 krone

If an error occurs, the POS screen can show a troubleshooting animation to resolve the problem.



CI-SERVER, cash management software

The CI-SERVER, which can be operated via a web browser, offers centralised cash management.





Glory Global Solutions Forest View, Crockford Lane, Chineham Business Park, Basingstoke, Hampshire RG24 8QZ, UK T +44 (0)1256 368000 F +44 (0)1256 368001 info@uk.glory-global.com www.gloryglobalsolutions.com *The CI-10 was awarded with the "red dot award: product design 2012". *Specifications are subject to change without notice. *Please read the instruction manual carefully to ensure correct equipment usage.

Glory Global Solutions is part of GLORY LTD.

This document is for general guidance only. As the Company's products and services are continually being developed it is important for customers to check that the information contained herein includes the latest particulars. Although every precaution has been taken in preparation of this document, the Company and the publisher accept no responsibility for errors or omissions. The Company and the publisher accept no liability for loss or damages resulting from the use of the information contained herein. This document is not part of a contract or licence save insofar as may be expressly agreed. All capabilities and capacity and throughput figures are subject to note/coin size, note/coin quality and process used. GLORY is a registered trademark of GLORY LTD. in Japan, the United States of America, and EU. All trademarks are owned by the GLORY LIMITED of companies. © Glory Global Solutions (International) Limited 2014.

Dimensions (W × D × H)		CI-10B (banknote recycler)	CI-10C (coin recycler)		
		240mm × 483mm × 820-850mm	240mm × 483mm × 820-850mm 9.4" × 19" × 32.3"-33.5"		
		9.4" x 19" x 32.3"-33.5"			
		(height can be adjusted)		ght can be adjust	· · · · · · · · · · · · · · · · · · ·
Weight		Approx. 60 kg / 132lbs.	Approx. 59 kg / 130lbs.		
Function		"Follow me" LED sign	"Follow me" LED sign		
Number of recycle modules		3 recycle modules	8 recycle modules		
		Free layout recycle module	Free	Free layout recycle module	
Capacity		Approx. 100 notes / recycle		Danish Krone	Approx. 90 coins
			10	Danish Krone	Approx. 120 coins
			5	Danish Krone	Approx. 90 coins
			2	Danish Krone	Approx. 120 coins
			1	Danish Krone	Approx. 250 coins
				Danish Krone	Approx. 200 coins
Other currencies		Approx. 100 notes / recycle	Please contact us for further information		
Coin overflow tray capacity			<option> Approx. 500 coins</option>		
Collection capacity		Selectable collection			
		Approx. 450 notes (SCC)			
		Approx. 300 notes (IFC)			
Total capacity of		Approx. 750 notes (SCC)	Depends on a recycle module configuration		
banknotes/coins		Approx. 600 notes (IFC)			
Deposit	Capacity of inlet:	Up to 30 notes	Up to 50 coins		
	Speed of cash in:	Approx. 3 notes / sec	Approx. 5 coins / sec		
Dispensing		Up to 10 notes	Up to 50 coins		
	Speed of cash out:	Approx. 3 notes / sec	Approx. 4 coins / sec		
Functions		Two ways to deposit/dispense,	Reje	ect foreign object	
		loose notes and interface cassette			
		Exit shutter	Collection through outlet		
Recognition unit		Counterfeit detection	Counterfeit detection		
Currencies		Danish Krone	Danish Krone		
		Other currencies on request			
Other functions		Error recovery animation	Error recovery animation		
		Slide extension unit	Slide extension unit		
		Control PC included			
		(Controls CI-10B, CI-10C)			
Supply voltage range		AC100V-240V	AC100V-240V		
Nominal frequency		50/60Hz	50/60Hz		
Approval		CE, UL	CE, UL		