

# BKT

GROWING TOGETHER

# ATV

LAWN & GARDEN / ALL TERRAIN SPORT TIRES







LAWN & GARDEN / ALL TERRAIN SPORT TIRES

# ATV

Whether you love competitive sport or traveling through natural landscapes, BKT has the right tire for your ATV. We design and build tires that are able to withstand all stress ATVs are continuously subject to especially under extreme conditions while riding over dry grounds or mud on tortuous paths, or rocky surfaces. In short: no matter which challenge you are going to face, BKT is by your side ensuring safety, performance, and great fun.

## TECHNOLOGIES AND PERFORMANCE

 <b>Comfort</b>	 <b>Deep Tread</b>	 <b>Durability</b>	 <b>Extra Deep Tread</b>	
 <b>Field Protection</b>	 <b>Handling &amp; Comfort</b>	 <b>Larger Footprint</b>	 <b>M+S</b>	
 <b>On/Off Road</b>	 <b>Sport</b>	 <b>Stability</b>	 <b>Steering Control</b>	 <b>Traction</b>



**Radial**  
Radial tires have cord plies that are arranged running radially from bead to bead around the tire. Sidewall and tread have independent functional features providing more flexibility, great performance, durability, and fuel economy.



**Bias**  
Bias tires have cord plies that are arranged running diagonally from bead to bead across the tire. Layers overlap forming a crisscross pattern. This design features extraordinary sidewall resistance, puncture resistance and high load capacity.



# ATV TIRES

  
SIERRA MAX



[ p. 6 ]

  
BOGMAX



[ p. 7 ]

  
W 207



[ p. 8 ]

  
AT 108



[ p. 16 ]

  
AT 109



[ p. 18 ]

  
AT 110



[ p. 19 ]

  
AT 111



[ p. 10 ]

  
AT 111 HD



[ p. 12 ]

  
AT 171



[ p. 14 ]

  
AT 112



[ p. 20 ]

  
AT 119



[ p. 21 ]

  
SIERRA MAX PRO



[ p. 22 ]







Radial



Technologies



M+S

Performance



Sport



Comfort



Traction



# SIERRA MAX

SIERRA MAX is the BKT tire for both all-terrain and lawn and garden applications. Its radial construction provides a significantly smoother and more comfortable ride over extreme terrains such as deserts, or dirty and rocky surfaces. The special tread design along with its wider footprint provides outstanding forward and lateral traction.

Ø 12"	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Type	Version
			Rec.	Alt.							
	AT 25 X 8 R 12	43 N	6.5	-	206	640	292	1899	-	TL	STD
	AT 25 X 10 R 12	50 N	8.0	-	260	640	294	1923	-	TL	STD
Ø 14"	AT 26 X 9 R 14	48 N	7.00	-	230	675	307	2005	-	TL	STD
	AT 26 X 11 R 14	54 N	9.00	-	280	675	310	2027	-	TL	STD
	AT 27 X 9 R 14	50 N	7.00	-	230	700	316	2070	-	TL	STD
	AT 27 X 11 R 14	56 N	9.00	-	280	700	318	2091	-	TL	STD

STD: Standard



# BOGMAX

BOGMAX has been specially designed for all-terrain applications. The very deep tread pattern ensures excellent traction whereas the sidewall protectors reduce impacts and possible damages. BOGMAX is a 6-ply-rated tire with M+S technology - perfect for sport performance in every condition.

Ø 14"	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
	AT 30 X 10 - 14	7.0 AT	7.5 AT ; 8.0 AT	260	760	-	-	STD	6	TL	58 F
	AT 32 X 10 - 14	8.0 AT	8.5 AT	250	810	-	-	STD	6	TL	62 F

STD: Standard



Bias



Technologies



Deep Tread



M+S

Performance



Sport



Traction





# W 207

W 207 is BKT's ATV tire for all-terrain sports. Thanks to M+S technology and a special design, it provides the best traction in any condition. This tire features an excellent puncture resistance over challenging terrains.

### Technologies



M+S

### Performance



Sport



Traction

Ø 8"	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
	AT 22 X 11 - 8	9.0 AT	8.5 AT	272	561	-	-	STD	6	TL	-
Ø 9"	AT 22 X 11 - 9	9.0 AT	8.5 AT	272	561	-	-	STD	6	TL	-
	AT 25 X 12 - 9	9.5 AT	9.0 AT ; 10.0 AT	300	632	-	-	STD	6	TL	-
	AT 25 X 13 - 9	10.5 AT	10.0 AT	330	635	-	-	STD	6	TL	-
Ø 10"	AT 22 X 11 - 10	9.0 AT	8.5 AT	272	561	-	-	STD	6	TL	-
	AT 22 X 7 - 10	5.5 AT	6.0 AT	178	559	-	-	STD	6	TL	-
	AT 22 X 8 - 10	6.5 AT	6.0 AT	203	559	-	-	STD	6	TL	-
	AT 23 X 10 - 10	8.0 AT	7.5 AT ; 8.5 AT	249	587	-	-	STD	6	TL	-
	AT 23 X 7 - 10	5.5 AT	6.0 AT	177	584	-	-	STD	6	TL	-
	AT 23 X 8 - 10	6.5 AT	6.0 AT	203	589	-	-	STD	6	TL	-
	AT 24 X 11 - 10	9.0 AT	8.5 AT	279	610	-	-	STD	6	TL	-
	AT 25 X 11 - 10	9.0 AT	8.5 AT	285	640	-	-	STD	6	TL	-
	AT 25 X 12 - 10	9.5 AT	9.0 AT ; 10.0 AT	297	640	-	-	STD	6	TL	-
Ø 11"	AT 23 X 8 - 11	6.5 AT	6.0 AT	203	584	-	-	STD	6	TL	-
	AT 24 X 10 - 11	8.0 AT	7.5 AT ; 8.5 AT	249	612	-	-	STD	6	TL	-

STD: Standard



Ø 11"	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
	AT 24 X 8 - 11	6.5 AT	6.0 AT	203	612	-	-	STD	6	TL	-
	AT 24 X 9 - 11	7.0 AT	7.5 AT	226	610	-	-	STD	6	TL	-
	AT 25 X 10 - 11	8.0 AT	7.5 AT ; 8.5 AT	249	638	-	-	STD	6	TL	-
	AT 25 X 8 - 11	6.5 AT	6.0 AT	203	638	-	-	STD	6	TL	-
Ø 12"	AT 24 X 8 - 12	6.5 AT	6.0 AT	198	615	-	-	STD	6	TL	-
	AT 25 X 10 - 12	8.0 AT	6.5 AT ; 7.5 AT ; 8.5 AT	249	638	-	-	STD	6	TL	-
	AT 25 X 11 - 12	9.0 AT	8.5 AT	284	638	-	-	STD	6	TL	-
	AT 25 X 8 - 12	6.5 AT	6.0 AT	198	638	-	-	STD	6	TL	-
	AT 26 X 10 - 12	8.0 AT	7.5 AT ; 8.5 AT	241	658	-	-	STD	6	TL	-
	AT 26 X 12 - 12	9.5 AT	8.0 AT ; 8.5 AT ; 9.0 AT	299	658	-	-	STD	6	TL	-
	AT 26 X 8 - 12	6.50 AT	6.00 AT	204	660	-	-	STD	6	TL	-
	AT 27 X 10 - 12	8.0 AT	7.5 AT ; 8.5 AT	241	683	-	-	STD	6	TL	-
	AT 27 X 12 - 12	9.5 AT	8.5 AT ; 9.0 AT	299	683	-	-	STD	6	TL	-
	AT 28 X 10 - 12	8.0 AT	7.5 AT ; 8.5 AT	241	706	-	-	STD	6	TL	-
	AT 28 X 12 - 12	9.5 AT	8.5 AT ; 9.0 AT	299	706	-	-	STD	6	TL	-

STD: Standard - SPL: Special





# AT 111

AT 111 is suitable for all-terrain sport racing with ATVs.  
An "HD" version with a deep tread is available for users who need improved durability and traction.

Performance



Ø 8"	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
	AT 18 X 10 - 8	8.0 AT	7.5 AT; 8.5 AT	254	457	-	-	STD	2	TL	-
	AT 18 X 10 - 8	8.0 AT	7.5 AT; 8.5 AT	254	457	-	-	STD	4	TL	-
	AT 20 X 11 - 8	9.0 AT	8.5 AT	282	508	-	-	STD	6	TL	-
	AT 22 X 11 - 8	9.0 AT	8.5 AT	282	559	-	-	STD	6	TL	-
Ø 9"	AT 18 X 10 - 9	8.0 AT	7.5 AT; 8.5 AT	254	457	-	-	STD	4	TL	-
	AT 20 X 11 - 9	9.0 AT	8.5 AT	279	508	-	-	STD	4	TL	-
	AT 20 X 11 - 9	9.0 AT	8.5 AT	279	508	-	-	STD	6	TL	-
	AT 22 X 11 - 9	9.0 AT	8.5 AT	282	559	-	-	STD	4	TL	-
	AT 22 X 11 - 9	9.0 AT	8.5 AT	282	559	-	-	STD	6	TL	-
Ø 10"	AT 18 X 10 - 10	8.0 AT	7.5 AT; 8.5 AT	254	457	-	-	STD	4	TL	-
	AT 19 X 6 - 10	5.0	-	152	472	-	-	STD	4	TL	-

STD: Standard

Ø 10"	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
	AT 20 X 6 - 10	5.0	-	152	500	-	-	STD	2	TL	-
	AT 20 X 6 - 10	5.0	-	152	500	-	-	STD	4	TL	-
	AT 20 X 11 - 10	9.0 AT	8.5 AT	275	508	-	-	STD	6	TL	-
	AT 21 X 7 - 10	5.5 AT	6.0 AT	178	541	-	-	STD	4	TL	-
	AT 21 X 7 - 10	5.5 AT	6.0 AT	178	541	-	-	STD	6	TL	-
	AT 22 X 11 - 10	9.0 AT	8.5 AT	282	559	-	-	STD	4	TL	-
	AT 22 X 7 - 10	5.5 AT	6.0 AT	175	559	-	-	STD	4	TL	-
	AT 22 X 11 - 10	9.0 AT	8.5 AT	282	559	-	-	STD	6	TL	-
	AT 22 X 7 - 10	5.5 AT	6.0 AT	175	559	-	-	STD	6	TL	-
	AT 22 X 8 - 10	6.5 AT	6.0 AT	208	559	-	-	STD	6	TL	-
	AT 23 X 7 - 10	5.5 AT	6.0 AT	178	584	-	-	STD	4	TL	-
	AT 23 X 7 - 10	5.5 AT	6.0 AT	178	584	-	-	STD	6	TL	-

STD: Standard





Bias



Technologies



Extra Deep Tread

Performance



Sport



Durability



Traction



# AT 111 HD

AT 111 HD is suitable for all-terrain sport racing with ATVs. The increased tread depth and the thick sidewall provide extra grip and braking control in addition to extraordinary traction and high-speed control in power slides. AT 111 HD ensures an extended tire life-cycle.

Ø 9"	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
	AT 20 X 11 - 9	9.0 AT	8.5 AT	275	515	-	-	STD	6	TL	43 J
	AT 22 X 11 - 9	9.0 AT	8.5 AT	279	560	-	-	STD	6	TL	-
Ø 10"	AT 20 X 11 - 10	9.0 AT	8.5 AT	279	505	-	-	STD	6	TL	-

STD: Standard



Ø 10"	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
	AT 21 X 7 - 10	5.5 AT	6.0 AT	178	533	-	-	STD	6	TL	30 J
	AT 22 X 11 - 10	9.0 AT	8.5 AT	279	560	-	-	STD	6	TL	-
	AT 22 X 7 - 10	5.5 AT	6.0 AT	174	560	-	-	STD	6	TL	-
	AT 23 X 7 - 10	5.5 AT	6.0 AT	174	585	-	-	STD	6	TL	-

STD: Standard







Bias



Performance



Traction



# AT 171

AT 171 has been specifically designed for mud bogger tractors. The special directional and extra-deep tread design provides excellent traction on wet and muddy surfaces.

Ø 14"	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
	AT 28 X 9 - 14	W 7	W 6	205	715	-	-	STD	6	TL	77A8 / 53 F
	AT 30 X 9 - 14	W 7	W 6	211	755	-	-	STD	6	TL	77A8 / 53 F
Ø 16"	AT 31 X 9 - 16	W 7	W 6	211	785	-	-	STD	6	TL	80A8 / 56 F
Ø 18"	AT 33 X 8 - 18	W 6	W 5.5	200	845	390	2525	STD	6	TL	83A8 / 59 F
	AT 35 X 10 - 18	W 8	-	241	900	417	2646	STD	8	TT	90A8 / 66 F
	AT 35 X 10 - 18	W 8	-	241	900	417	2646	STD	8	TL	90A8 / 66 F
Ø 20"	AT 33 X 9 - 20	W 7	W 6	205	838	387	2616	STD	6	TL	85A8 / 61 F
	AT 35 X 9 - 20	W 7	W 6	200	895	419	2670	STD	6	TT	85A8 / 61 F
	AT 35 X 9 - 20	W 7	W 6	200	895	419	2670	STD	6	TL	85A8 / 61 F

STD: Standard



Ø 20"	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
	AT 38 X 10 - 20	W 8	W 7	235	950	442	2835	STD	6	TT	93A8 / 69 F
	AT 38 X 10 - 20	W 8	W 7	235	950	442	2835	STD	6	TL	93A8 / 69 F
Ø 22"	AT 35 X 9 - 22	W 7	W 6	210	890	-	-	STD	6	TL	88A8 / 64 F
	AT 37 X 9 - 22	W 7	W 6	205	945	444	2778	STD	8	TT	88A8 / 64 F
	AT 37 X 9 - 22	W 7	W 6	205	945	444	2778	STD	8	TL	88A8 / 64 F
	AT 40 X 10 - 22	W 8	W 7	235	1005	469	2955	STD	8	TT	95A8 / 71 F
	AT 40 X 10 - 22	W 8	W 7	235	1005	469	2955	STD	8	TL	95A8 / 71 F
	AT 40 X 9 - 24	W 7	W 6	211	995	462	3112	STD	8	TL	90A8 / 66 F

STD: Standard







# AT 108

AT 108 is an all-terrain tire suitable for ATVs.  
Its tread design provides excellent comfort and performance on-and-off the road.

Performance



Ø 8"	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
	AT 20 X 7 - 8	5.5 AT	6.0 AT	170	508	-	-	STD	4	TL	-
	AT 22 X 11 - 8	9.0 AT	8.5 AT	277	560	-	-	STD	4	TL	-
Ø 9"	AT 22 X 10 - 9	8.0 AT	7.5 AT; 8.5 AT	254	559	-	-	STD	4	TL	-
	AT 22 X 11 - 9	9.0 AT	8.5 AT	275	557	-	-	STD	4	TL	-
	AT 22 X 11 - 9	9.0 AT	8.5 AT	275	557	-	-	STD	6	TL	-
	AT 25 X 12 - 9	9.5 AT	9.0 AT; 10.0 AT	292	640	-	-	STD	4	TL	-
	AT 25 X 13 - 9	10.5 AT	10.0 AT	320	635	-	-	STD	4	TL	-
	AT 25 X 13 - 9	10.5 AT	10.0 AT	320	635	-	-	STD	6	TL	-
Ø 10"	AT 20 X 10 - 10	8.0 AT	7.5 AT; 8.5 AT	250	514	235	1426	STD	4	TL	-
	AT 22 X 11 - 10	9.0 AT	8.5 AT	270	564	-	-	STD	4	TL	-
	AT 22 X 8 - 10	6.5 AT	6.0 AT	206	557	-	-	STD	4	TL	-
	AT 22 X 8 - 10	6.5 AT	6.0 AT	206	557	-	-	STD	6	TL	-
	AT 22 X 11 - 10	9.0 AT	8.5 AT	270	564	-	-	STD	6	TL	-
	AT 23 X 8 - 10	6.5 AT	6.0 AT	210	594	-	-	STD	4	TL	-
	AT 23 X 10 - 10	8.0 AT	7.5 AT; 8.5 AT	259	594	-	-	STD	4	TL	-

STD: Standard



Ø 10"	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
	AT 24 X 11 - 10	9.0 AT	8.5 AT	284	608	-	-	STD	4	TL	-
	AT 24 X 11 - 10	9.0 AT	8.5 AT	284	608	-	-	STD	6	TL	-
	AT 25 X 12 - 10	9.5 AT	9.0 AT; 10.0 AT	298	630	-	-	STD	4	TL	-
	AT 25 X 12 - 10	9.5 AT	9.0 AT; 10.0 AT	298	630	-	-	STD	6	TL	-
Ø 11"	AT 22 X 7 - 11	5.5 AT	-	181	557	-	-	STD	4	TL	-
	AT 23 X 8 - 11	6.5 AT	6.0 AT	191	594	-	-	STD	4	TL	-
	AT 23 X 8 - 11	6.5 AT	6.0 AT	191	594	-	-	STD	6	TL	-
	AT 24 X 8 - 11	6.5 AT	6.0 AT	206	610	-	-	STD	4	TL	-
	AT 24 X 9 - 11	7.0 AT	7.5 AT	220	605	-	-	STD	4	TL	-
	AT 24 X 9 - 11	7.0 AT	7.5 AT	220	605	-	-	STD	6	TL	-
	AT 24 X 10 - 11	8.0 AT	7.5 AT; 8.5 AT	254	615	-	-	STD	4	TL	-
Ø 12"	AT 25 X 8 - 12	6.5 AT	6.0 AT	212	630	-	-	STD	4	TL	-
	AT 25 X 8 - 12	6.5 AT	6.0 AT	212	630	-	-	STD	6	TL	-
	AT 25 X 10 - 12	8.0 AT	6.5 AT; 7.5 AT; 8.5 AT	254	640	-	-	STD	4	TL	-
	AT 25 X 10 - 12	8.0 AT	6.5 AT; 7.5 AT; 8.5 AT	254	640	-	-	STD	6	TL	-

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index





# AT 109

AT 109 is an all-terrain tire for ATVs. Its tread design provides excellent field protection.

Performance



Ø 6"	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
	AT 145 X 70 - 6	4.5	-	137	366	-	-	STD	2	TL	-
Ø 7"	AT 16 X 8 - 7	6.5 AT	6.0 AT	183	419	-	-	STD	2	TL	-
Ø 8"	AT 18 X 9.5 - 8	7.5 AT	8.0 AT	220	468	-	-	STD	2	TL	-
	AT 20 X 7 - 8	5.5 AT	6.0 AT	170	504	-	-	STD	2	TL	-
	AT 21 X 9 - 8	7.0 AT	6.5 AT; 7.5 AT	222	536	-	-	STD	2	TL	-
	AT 22 X 11 - 8	9.0 AT	8.5 AT	230	579	-	-	STD	2	TL	-
Ø 9"	AT 25 X 12 - 9	9.5 AT	9.0 AT; 10.0 AT	269	617	-	-	STD	2	TL	-

STD: Standard



# AT 110

AT 110 is BKT's tire suitable for all-terrain applications with ATVs. Thanks to its extraordinary steering control, AT 110 is the ideal front axle tire for your vehicle.

Performance



Ø 8"	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
	AT 20 X 7 - 8	5.5 AT	6.0 AT	183	508	-	-	STD	4	TL	-
Ø 9"	AT 21 X 8 - 9	6.5 AT	6.0 AT	204	541	-	-	STD	4	TL	-
Ø 10"	AT 21 X 7 - 10	5.5 AT	6.0 AT	178	531	-	-	STD	4	TL	-
	AT 22 X 8 - 10	6.5 AT	6.0 AT	204	548	-	-	STD	4	TL	-
	AT 23 X 7 - 10	5.5 AT	6.0 AT	178	584	-	-	STD	4	TL	-

STD: Standard





# AT 112

AT 112 is an all-terrain tire for ATVs. It is particularly suitable for sport performance.

Performance



Ø 8"	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
	AT 20 X 10 - 8	8.0AT	7.5AT; 8.5AT	240	510	-	-	STD	4	TL	-
Ø 10"	AT 20 X 10 - 10	8.0AT	7.5AT; 8.5AT	240	510	-	-	STD	4	TL	-
Ø 12"	AT 23 X 10 - 12	8.0AT	7.5AT; 8.5AT	240	585	-	-	STD	4	TL	-

STD: Standard



# AT 119

AT 119 is suitable for both all-terrain and lawn and garden applications with mowers. Its tread design provides excellent field protection.



Performance



Ø 8"	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
	AT 22 X 11 - 8	9.0AT	8.5AT	280	580	-	-	STD	2	TL	-
	AT 22 X 11 - 8	9.0AT	8.5AT	280	580	-	-	STD	4	TL	-

STD: Standard







Radial



# SIERRA MAX PRO

SIERRA MAX PRO is the perfect BKT tire for all-terrain vehicles in ATV applications, also including side-by-side racing. Its radial construction and special wider foot print area provide a smoother ride and an optimized lateral as well as forward traction. Special sturdy lugs have been studied specifically to provide excellent traction and firm grip on the terrain. These features ensure an extraordinarily comfortable ride providing safety and driving control. SIERRA MAX PRO provides excellent performance on every kind of terrain, from hard pack terrains to loose soils.

### Technologies



Larger Footprint

### Performance



Handling & Comfort



Traction



Stability



Steering Control

Ø 12"	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
	AT 25 X 8 R 12	43 N	6.50	-	200	630	-	-	-	STD
Ø 14"	AT 27 X 11 R 14	56 N	9.00	-	285	708	-	-	-	STD

STD: Standard





## Load Index Table

The load index is a code that defines a tire's maximum weight capacity at the speed given by its speed index provided that the usage conditions recommended by the Manufacturer are fully complied with.

### Corresponding values of load index (LI) and load capacity per wheel (kg)

LI	kg	LI	kg	LI	kg	LI	kg
50	190	85	515	120	1400	155	3875
51	195	86	530	121	1450	156	4000
52	200	87	545	122	1500	157	4125
53	206	88	560	123	1550	158	4250
54	212	89	580	124	1600	159	4375
55	218	90	600	125	1650	160	4500
56	224	91	615	126	1700	161	4625
57	230	92	630	127	1750	162	4750
58	236	93	650	128	1800	163	4875
59	243	94	670	129	1850	164	5000
60	250	95	690	130	1900	165	5150
61	257	96	710	131	1950	166	5300
62	265	97	730	132	2000	167	5450
63	272	98	750	133	2060	168	5600
64	280	99	775	134	2120	169	5800
65	290	100	800	135	2180	170	6000
66	300	101	825	136	2240	171	6150
67	307	102	850	137	2300	172	6300
68	315	103	875	138	2360	173	6500
69	325	104	900	139	2430	174	6700
70	335	105	925	140	2500	175	6900
71	345	106	950	141	2575	176	7100
72	355	107	975	142	2650	177	7300
73	365	108	1000	143	2725	178	7500
74	375	109	1030	144	2800	179	7750
75	387	110	1060	145	2900	180	8000
76	400	111	1090	146	3000	181	8250
77	412	112	1120	147	3075	182	8500
78	425	113	1150	148	3150	183	8750
79	437	114	1180	149	3250	184	9000
80	450	115	1215	150	3350	185	9250
81	462	116	1250	151	3450	186	9500
82	475	117	1285	152	3550	187	9750
83	487	118	1320	153	3650	188	10000
84	500	119	1360	154	3750	189	10300

## Speed Index Table

The speed code is a value that indicates the maximum admitted speed at which the tire can carry the weight corresponding to its load index provided that the usage conditions recommended by the Manufacturer are fully complied with.

Speed index	A1	A2	A3	A4	A6	A8	B	C	D	E	F	J
Km/h	5	10	15	20	30	40	50	60	65	70	80	100
mph	3	6	9	12	19	25	31	37	40	43	50	62



# Notes



GROWING TOGETHER

PROUD SPONSOR OF:



OFFICIAL PARTNER OF



OFFICIAL PARTNER OF







### Corporate Office

**Balkrishna Industries Ltd.**

BKT HOUSE, C/15, Trade World, Kamala Mills Compound, Senapati Bapat Marg, Lower Parel, Mumbai - 400013, India  
Tel: (+91) 22-6666 3800 - Fax: (+91) 22-6666 3898/99 - e-mail: info@bkt-tires.com - bkt-tires.com

### BKT Europe srl

Viale Della Repubblica,133  
20831 Seregno (MB), Italy  
Tel: (+39) 0362 33 03 28  
(+39) 0362 32 51 07  
Fax: (+39) 0362 23 24 72

### BKT USA Inc.

202 Montrose West Ave. Suite 240  
Copley, Ohio 44321  
Tel: (+1) 330 836 1090  
Fax: (+1) 330 836 1091  
Toll Free: (+1) 888 660 0662

### BKT Tires (CANADA) Inc.

55 York Street, Suite 401  
Toronto, Ontario M5J 1R7, Canada  
Tel: AG/IND (+1) 905 641 5636  
OTR (+1) 780 888 5667  
Fax: (+1) 416 229 1711



[bkt-tires.com](http://bkt-tires.com)