

Construction machinery

Joysticks and handles



Individual control concepts -
We realize your solution

TRADITION AND EXPERTISE

The company was founded in Blaubeuren by Karl Spohn and David Burkhardt in 1920 and is still 100 percent family-owned.

Today, with 200 employees, we manufacture a broad production program of joysticks, control stands and resistors of recognized quality at two locations.

With engineering knowledge and decades of experience, we solve your problems together with you and accompany you from start to finish. That is our strength and at the same time the basis of our success.

As a Swabian medium-sized company, our strength lies in the unbeatable advantage of being able to react quickly

and flexibly. When technology is moved around the world, Spohn + Burkhardt is usually the trigger.

FACTS AND FIGURES

- Founded in 1920 by Karl Spohn and David Burkhardt
- Headquarters Blaubeuren
- Plant Schelklingen
- About 65 representatives in 45 countries
- About 200 employees

BENEFITS

- Made in Germany
- Decades of experience in joystick design and manufacturing
- Optimum combination options of our joysticks and handles
- Harmonious relationship between joystick and equipment
- Deliveries from single pieces up to series production
- Upmost quality and service life
- Large dealer network providing service worldwide
- Custom designed solutions per customer requirements



Joysticks/Mini steering wheel

ST0	ST1	ST4	CS1	NS3	HS0	HS2	ML
 <ul style="list-style-type: none"> • Metal drive mechanism • Maximum 5-0-5 stages • Long mechanical service life of up to 6 million switching cycles • Long-lasting lightweight plastic potentiometer or non-contact Hall sensors • Friction brake or spring-return • Optional mechanical neutral position lock 	 <ul style="list-style-type: none"> • Metal drive mechanism • Chrome-plated cast aluminum housing with high front-side IP protection rating for extreme environmental requirements • Long-lasting lightweight plastic potentiometer or non-contact Hall sensors • Friction brake or spring-return • Optional mechanical neutral position lock 	 <ul style="list-style-type: none"> • Metal drive mechanism • Sealed high-quality plastic housing prevents entry of water from above, even if the rubber sheath is damaged • High mechanical service life of up to 6 million switching cycles • Long-lasting lightweight plastic potentiometer or non-contact Hall sensors • Friction brake or spring-return • Optional mechanical neutral position lock with Reed contact 	 <ul style="list-style-type: none"> • Metal drive mechanism, drive block made of high-quality plastic • Long mechanical service life of up to 10 million switching cycles • Non-contact HALL sensors or lightweight plastic potentiometers • Microswitches for hardware wiring • Optionally integrated interfaces for CANopen, SAEJ1939, Profibus • Combinable with several SPOBU handles 	 <ul style="list-style-type: none"> • Metal drive mechanism and drive block • Long mechanical service life of up to 20 million switching cycles • Non-contact HALL sensors and/or lightweight plastic potentiometers • Microswitches for hardware wiring • Optionally integrated interfaces for CANopen, CANopenSafety, Profibus, ProfiNet, ProfiNet with ProfiSafe protocol • Combinable with several SPOBU handles 	 <ul style="list-style-type: none"> • Metal drive and housing • Long mechanical service life of up to 10 million switching cycles • Non-contact 3D Hall sensors • Low installation depth • Redundant analogue exit • Optional external interfaces for CANopen, SAEJ1939, Profibus, ProfiNet • Combinable with several SPOBU handles 	 <ul style="list-style-type: none"> • Metal drive and housing • Long mechanical service life of up to 10 million switching cycles • Non-contact 3D Hall sensors • Redundant analogue exit • Optional integrated interfaces for CANopen, SAEJ1939, Profibus, ProfiNet • Combinable with several SPOBU handles 	 <ul style="list-style-type: none"> • Extremely sensitive, zero-play metal mechanics • Optionally with oil damping for smooth and precise control • Long mechanical service life • Sensors with HALL sensors or lightweight plastic potentiometers • Combinable with various electronic interfaces

Handles

Standard handles

- M054**
- Standard handle for M0 joysticks
 - Optional pushbutton
 - Version M054-Z for mechanically locking joystick



- G22**
- Plastic handle Ø 40 mm
 - A maximum of 1 pushbutton can be integrated
 - Recessed or protruding pushbutton installation
 - Version G22Z for mechanically locking joystick
 - Combinable with several SPOBU joysticks



- G27**
- Plastic handle Ø 27 mm
 - A maximum of 1 pushbutton can be integrated
 - Recessed or protruding pushbutton installation
 - Combinable with joystick ST0



- G57**
- Standard handle for joystick HS0
 - Compact design
 - Ideal for installation in remote controls



- G21**
- Plastic handle Ø 45 mm
 - A maximum of 2 pushbuttons can be integrated
 - Recessed or protruding pushbutton installation
 - Version G21Z for mechanically locking joystick
 - Combinable with several SPOBU joysticks



Palm handles

- G40**
- Ball handle with several installation options
 - Push buttons on the side and/or on top
 - Alternatively with toggle switch on top
 - Optionally with hand rest
 - Combinable with several SPOBU joysticks



- G4T**
- Forward-tilting ball handle
 - Lever switch on front
 - Optionally with toggle switch, pushbutton or rotary potentiometer on top
 - Combinable with several SPOBU joysticks



- G9**
- Compact ball handle with/without pushbuttons
 - Optionally with capacitive hand recognition sensor
 - Operable with 2 fingers or whole hand
 - Combinable with several SPOBU joysticks



- G25**
- Compact plastic handle
 - Operable with 2 fingers or whole hand
 - Up to 6 pushbuttons can be integrated
 - Combinable with several SPOBU joysticks



- G51**
- Compact plastic handle
 - Up to 6 pushbuttons can be integrated
 - Combinable with several SPOBU joysticks



Ball handles

- KG40/50**
- Solid ball handle
 - Versions with 40 and 50 mm diameter
 - Combinable with several SPOBU joysticks



- KG56-IKKZ**
- Ball handle for mechanical locking for VNS0, NNS0, VNS2 joysticks
 - in combination with slot or cross gates
 - Optionally with contact



T-handles

- G1**
- T-handle with/without pushbuttons
 - Optional mechanical pivoting for individual adjustment
 - Version G1Z for mechanically locking joysticks
 - Optionally with dead man's function by pressing down
 - Optionally integrated capacitive hand recognition sensor
 - Combinable with several SPOBU joysticks



- G13**
- T-handle with/without pushbutton
 - Stationary or rotating with a maximum of 2-0-2 stages
 - Version G13Z for mechanically locking joystick
 - Optionally with capacitive hand recognition sensor
 - Combinable with several SPOBU joysticks



Rotary handles

- G50**
- Handle with integrated rotating function
 - Sensors with lightweight plastic potentiometers with direction recognition
 - Combinable with several SPOBU joysticks



Universal handles

G56



- Ergonomically shaped for left or right hand
- Integrated hand rest for work without fatigue
- Modular design with standard or custom equipment of insert panels
- Optionally integrated capacitive hand recognition sensor
- Optionally rotating
- Combinable with several SPOBU joysticks

G58



- Compact, symmetrical, can be used for left or right hand
- Ergonomically shaped for work without fatigue
- Modular design with standard or custom insert panels
- Catch on the rear
- Optionally integrated capacitive hand recognition sensor
- Combinable with several SPOBU joysticks

UGA




- Can be used for left or right hand
- Modular design with optional combination of wide and narrow handle halves
- High variability with installation of command devices on top, front or side
- Lever switch on the rear
- Optionally with hand rest, can also be updated
- Optionally rotating
- Optionally integrated capacitive hand recognition sensor
- Combinable with several SPOBU joysticks

UGN



- Compact handle can be used for left or right hand
- Ergonomically shaped for work without fatigue
- High variability with installation of command devices on top, front or side
- Integrated surrounding hand rest
- Optionally integrated capacitive hand recognition sensor
- Combinable with several SPOBU joysticks

Representatives of Spohn + Burkhardt National and international



ASI Automatikk AS
Sankt Hallvards vei 3
3414 Lierstranda
Norway

Tel.: +47 900 61 100
E-mail: info@asiflex.no
Website: www.asiflex.no