

Dust Control Matting

www.notrax.eu

Catalogue Nr. 6



www.notrax.eu

رليد

Index and Guide

Product Test	•	3
	tting Pictograms	3 3 3 3 3
About Notra	x®	3
Warranty		3
Benefits of E	Entrance Mats	3
Art. Code	Product name	Page
-	Custom Printed Mats	8/9
190	Logo Washable™	10/11
010	Uni Washable™	10/11
198	Logo Superior™	12/13
018	Uni Superior™	12/13
193	Logo Standard™	14/15
015	Uni Standard [™]	14/15
196	Logo Brush™	16/17
016	Uni Brush™	16/17
178	Déco Design™ Superior	18/19
170	Déco Design™ Washable	18/19
175	Déco Design™ Standard	18/19
Indoor – Cor	ntract and Installation Matting	20/21
380	Swisslon Classic XT [™]	22/23
389	Swisslon Plus™	24/25
388	Swisslon Uni™	26/27
387	Swisslon Flair™	28/29
113	Master Trax™	30/31
103	Master Trax Lite [™]	30/31
1 · · · ·		
Indoor – Loo	ose Lay Carpet Mats	32/33
380	Swisslon Classic™	34/35
145	Preference®	36/37
138	Uptown™	38/39
238	Silverline™	40/41
137	Opera™	42/43
231	Prelude™	42/43
150	Aqua Trap®	44/45
166	Guzzler™	46/47
118		48/49
185	Essence™	50/51
130	Polyplush™	52/53
123		54/55
117		54/55
109		54/55
136		54/55
1)0	Totymb	رر /4/
Indoor/Outd	oor – Contract and Installation	
Matting		56/57
590	Master Flex™ D23	58/59
591	-	58/59
592	Master Flex™ D12	60/61
593	Master Flex [™] C12	60/61
599	Oct-O-Flex [™] 12 mm	62/63
539		64/65
ورر		
Outdoor - Co	ontract and Installation Matting	
564	-	66/67
273		68/69
274		68/69
271		68/69
Outdoor - Lo	oose Lay Scraper Mats	
599B	Oct-O-Flex™ Bevelled	70/71
539B	Gripwalker Edge™	72/73
345	Rubber Brush™	74/75
565	Soil Guard™	74/75
267	Wayfarer [®] 16 mm	76/77
266	Wayfarer® 14 mm	76/77
265	Wayfarer [®] 10 mm	76/77
Accessories		
083	Bevelled Nosing 2 mm	78
084	Bevelled Nosing 4 mm	78
325	Bevelled Nosing 11 mm	78
113K	Master Trax [™] Stitched Bevels 11 mm	
092	Mat Seaming Tape	78
086	Notrax [®] Super Glue	78
093	Recess Fillers 6 mm	79
093	Recess Fillers 8 mm	79 79
094	Recess Fillers 10 mm	
095	Velcro [®] Carpet Anchor	79
085	Mat Hold	79 79
090	Hat Hota	19



www.notrax.eu

ErgoFloor A/S, Viborgvej 9, 7160 Terring, Tlf. 76 90 20 01, www.ergofloor.dk

2

Notrax[®] Pictograms

Heavy Traffic

environments.

Light Traffic

Dirt Scraping

entering the building.



Indoors or indoor use.



Portico Can be used outdoors in protected, covered or portico areas that are not exposed to rain.



Outdoors Can be used outdoors in any weather.



hospitality and commercial environments. **Medium Traffic**

Suitable for light foot traffic conditions

Scraping function removes dirt from

soles to prevent dirt and grime from

in offices and retail shops.

Suitable for heavy foot traffic conditions in busy public areas,





Wheel-chair friendly

Stairs

Washable up to 50° Celsius.

Suitable for installation on stairs.

Smooth top surface or low profile

and bevelled edges are ideal for wheelchairs, carts or suitcase wheels.



Absorbing Absorption capacity is measured in litres per square meter.



Drainage Allows water to drain through, leaving a clean and dry surface.



Fire Retardant Fire rating of Bfl-S1 or Cfl-S1 tested according to EN 13501-1. Matting is designed to resist the spread of fire.





Cold Resistant

extremes.

Interlocking mats allow on-site customization with snap together units that can be assembled in any shape or form.

Can withstand exposure to weather



substantiated by test certifications from independent laboratories.

Product Testing

shoes.

Notrax[®] Floor Matting Products are subject to rigorous testing by independent laboratories prior to their introduction to the market. Our Product Testing Chart shows the following relative comparisons between the Notrax® mats featured in this brochure:



Water Retention

Indicates the moisture retention of an entrance mat in actual usage. The higher the pointer in the test chart, the more litres of water per square meter that can be contained within the mat.

Crush Resistance

Indicates the time it takes for a mat to lose its attractive appearance and functionality. This test simulates the wear an entrance mat will receive under normal foot traffic. The higher the pointer in the test chart, the greater its resistance to wear and crushing.



Product Testing

Water Retention

Crush Resistance

Dust Control

Dust Control

Indicates the amount of debris an entrance mat can

capture, hold and hide in actual usage. The effectiveness of this function is owed to a combination of manufacturing techniques and the quality of yarns used. The higher the

pointer in the test chart, the more debris is scraped off

GOOD BETTER BEST

www.ergofloor.dk

www.notrax.eu

Viborgvej 9, 7160 Tørring,

Tlf. 76 90 20 01,

Example Product Testing Chart

Benefits of entrance mats

The entrance is the building's first impression. As with any introduction – to people, places, or products – first impressions are critical. Entrances have to satisfy a variety of requirements including attractive design, high throughput rate (even during the busiest of times) and excellent functionality. Entrance mats come in a range of colours and patterns to match any interior and improve the overall aesthetics of the entrance giving it a professional, stylish and upscale appearance making every first impression a great one. Even in between cleanings, entrance mats should continue to look great after thousands of people have walked over them.

The benefits of entrance mats have been recognized by many sustainable and environmental building assessors, such as LEED (Leadership in Energy and Environmental Design) and BREEAM (Building Research Establishment Environmental Assessment Method). A proper entrance matting system contributes to improving indoor air quality, acoustic performance, extending the useable life of interior flooring materials and reducing maintenance and cleaning costs. LEED therefore recommends a permanent entryway walk-off system of at least 10 feet long (up from 6 feet in previous versions of LEED) at all regularly used, exterior-to-interior entrances and entrances from covered parking garages.

Entrance mats reduce cleaning costs

70-80% of the dust, dirt and grime in public buildings is tracked in from the outside and spread throughout the floors (International Sanitary Supply Association). Over a 20-day period, 1000 people can walk in 9.6 kilograms (24 pounds) of dirt into a building (ISSA). Twelve times as much dirt is tracked in during wet weather conditions based on field tests conducted by BST Laboratory over a 11-month period. Large commercial buildings with heavy traffic areas can see as much as 5000 crossings a day.

The benefits of a good entrance matting system are very measurable in annual savings of cleaning costs. The more dirt removed at the entrance, the less can become airborne inside the building. Entrance matting is the first line of defense in keeping dirt and debris from entering the building and can remove up to 85% of dirt.



Entrance mats contribute to improved indoor air quality

In building design, designers often overlook the benefits of designing entryways and managing buildings to remove tracked-in pollutants from shoes that improve air quality through reduction of air particles. Outside dirt can be a carrier of particulate matter such as dust, pollen, pesticides, bacteria, fungi, animal faeces and insect parts. Dirt particles are deposited on the floor, where they are ground into smaller particles as they are walked on. The smallest particles are suspended in the air, while the larger ones settle back on the floor, where they are ground again. These airborne particles are a large contributor to indoor air pollution which can cause breathing problems, allergies and aggravate asthma. Indoor air pollution is one of the top five environmental risks to public health as often indoor air is found to be up to 70 times more polluted than outdoor air; (Environmental Protection Agency) and most people spend 60-90% of their time indoors. (American Lung Association). Controlling the concentration of particulates through prevention and cleaning can help relieve symptoms and prevent disease.

Entrance mats protect and preserve interior flooring

Constant tracking of dirt into the building is also a prime factor in the wearing of interior floors and carpeting. Dirt and soils have a texture that is similar to a razor which are ground into floors during walking, causing scraping on smooth flooring and as carpets are walked on, their fibres can be cut. Within the first 6 feet, 42 % of the floor's finish or carpet nap will be removed after only 1500 people have entered thereby shortening the overall life span of interior flooring. Entrance mats are made with coarser fibres that are designed to preserve the floor by absorbing much of the initial abuse that would otherwise shorten the interior flooring or carpeting useable life to protect the investment.

Entrance mats help to prevent slips, trips and falls

Slips and falls are the leading cause of accidents in homes, hotels, restaurants, and public buildings. (70% occur on flat and level surfaces).

The four main causes of slip and trip accidents are:

- · Slippery/wet surfaces caused by water and other fluids
- Slippery surfaces caused by dry or dusty floor contamination
- Obstructions both temporary and permanent
- Uneven surfaces and changes of level

In dry weather, entrance ways can accumulate dirt on the surface. Sand, bits of gravel and dirt are commonly called "boulder dust" because they act as miniature ball bearings when caught between a hard floor surface and a smooth shoe sole. The shoe loses traction and skids away causing the person to lose control and fall. During bad weather conditions including rain, snow and sleet, interior flooring can quickly become slippery and interior carpet can become saturated thereby increasing the risk of slips and falls.

Entrance mats play a role in reducing slips and falls due to wet floors by properly drying wet shoes and in keeping indoor and outdoor entrances accessible for people with mobility impairments such as walking aids and wheelchairs.



The Zones

Matting solutions that are successful in stopping dirt and preventing slips and falls, address three major zones:

Zone 1:

Scraping Zone catches the first wave of heavy debris with up to 40% of dirt/moisture being removed from shoes.

Zone 2:

Cleaning Zone scrapes fine debris and absorbs moisture in the indoor foyer area for up to 70%.

Zone 3:

Drying Zone completes the drying process and virtually all dirt and moisture is removed from shoes.

Logo Mats and Custom Printed Mats

Logo matting provides the option to completely customize a quality dust control entrance mat with the company image, logo or message for powerful branding. As visitors enter, the entrance mat becomes a large promotional opportunity to enhance your company identity and truly welcome guests, because as they enter most people primarily look to the floor.

Mat functionality

The main function of a mat is to clean and dry shoes. A proper mat stops dirt and moisture from getting tracked into facilities, reduces interior cleaning costs, prevents slips and falls on wet floors, preserves interior flooring by absorbing the initial abuse and improves indoor air quality.

The size, material and density of the mat therefore play a role in its ability to perform this main function, but also in its durability, water absorption and dirt removal capacity. Notrax® has a selection of high quality logo mats that perform this function well, yet also provide an excellent opportunity to promote a brand or company name.

High definition printing

Notrax[®] uses the latest printing technology and high definition printing making it easy to print complex logo designs, shading and 3 dimensional effects. A high resolution results in a photo quality print with superior image representation. The sharp definition of fine lines, contours and smooth gradations produce precise details for each mat to have its truly individual image. The height of the carpet pile enhances the depth of the image for a truly brilliant effect.

Unlimited colour possibilities

Notrax[®] logo mats are printed with an extended process colour printing method that produces vibrant, stable colours with almost infinite colour possibilities. The large colour variations allow vivid colours, superb blacks for stark contrasts, and smooth gradations for infinite shading resulting in exceptional photo quality printing to really make the logo stand out.

Multi-coloured logos, complicated designs, artwork and even photos can easily be replicated. Select any of the thousands of Notrax[®] existing colours, or supply a PMS (Pantone Matching System), RAL (Reichs-Ausschuss für Lieferbedingungen) or other colour matching system codes, and we will match your logo colours for a true representation of your logo.

ErgoFloor A/S, Viborgvej 9, 7160 Tørring, Tlf. 76 90 20 01, www.ergofloor.dk

Match Your Mat[™]

BrilliantStep[™] can also be printed in just one colour to match your mat to any interior design or colour scheme using our colour matching system with thousands of bold colours to provide quick and accurate colour matches. Or simply indicate your preferred colour using PMS, RAL or other colour matching system codes, and we will match your mat. Uni-coloured mats can also be used together with the custom printed logo mats for a complete colour coordinated matting system.

Custom lengths and sizes

As with all Notrax[®] products, Notrax[®] loose lay entrance mats are available in a multitude of standard sizes as well as custom lengths, available per linear meter. Our specialized production team can customize Notrax[®] logo mats to any size, shape or length with mounted bevelled nosing to finish off the mat and prevent tripping. Even special shapes or forms, including circles, half-moons, and arches can be produced for custom installations. All customized matting can be supplied with recommended accessories such as bevelled edging, 090 Mat Hold[™] or 085 Velcro[®] Carpet Anchor strips.

Production method

Notrax[®] logo mats are produced to order using the BrilliantStep[™] state-of-the-art printing technology. The BrilliantStep[™] printing method ensures brilliant and vibrant colours with a colour fastness that is ensured in accordance with DIN54006. Unlike screen printing or flocking that only treats the surface, BrilliantStep[™] printing penetrates deep into the mat fibres so the colour is visible all the way through to ensure the print lasts for the lifetime of the mat and does not fade over time.

Production time

Notrax[®] has expanded its logo printing capacity and capabilities. Plus the "Lean" organization of our operations enables us to stay competitive and provide extremely fast service for both standard and custom products. Logo mat designs are created and sent for approval in 24 hours. Once approved, the logo design is sent to production to be printed, packaged and shipped in 24 hours.

No minimum quantities

Our brand of Notrax[®] mats for professional use has become synonymous with quality, flexibility and customer service. We offer full logo matting and customizations services with no minimum order quantities, extremely fast service and drop shipment possibilities.

How to order?

1. Project Title:

Give any name relevant to reference the design. This name will be used in all correspondence and on the order.

2. Mat Type:

Choose from the range of logo matting types: 190 Logo Washable™ 198 Logo Superior™ 193 Logo Standard™ 196 Logo Brush™.

3. Logo:

Send logo or image to designer@notrax.com. Acceptable formats are JPG, TIF, EPS, PCX, Adobe illustrator, PDF.

4. Size:

Indicate mat size whether from available sizes, custom lengths or custom shapes or sizes. For non-standard shapes, a bleed is recommended around the print area.

5. Orientation:

Indicate whether the design is to be created in landscape or portrait.

ErgoFloor A/S, Viborgvej 9,

6. Background Colour:

Select a colour for the background of the mat. Dark colours are recommended for the background. Lighter colours appear dirty much faster.

7160 Tørring,

Tlf. 76 90 20 01,

www.ergofloor.dk

7. Finishing:

Indicate whether bevelled nosing is desired for loose lay or whether the mat will be installed in a recessed matwell frame.

8. Quantity:

Indicate number of mats. There are no minimum quantities, but more mats per design lowers the cost.

Artwork supplied in 24-hours. Mat is printed 24 hours after artwork approval is given!

www.notrax.eu





www.notrax.eu

Functional and washable logo entrance mat can be completely personalized using BrilliantStep[™] full colour printing with almost infinite colour combinations. This high quality multi-functional dust control mat not only cleans and dries shoes, to prevent dirt and moisture getting tracked in to facilities; it also provides an excellent opportunity to promote a brand or company name because most people primarily look to the floor. Nitrile rubber backing is washable up to 50°C with cleated pattern to minimize movement on all surfaces and to keep the mat elevated on hard floors to allow drying underneath. The BrilliantStep[™] printing method ensures brilliant colours all the way through with a colour fastness that is ensured, in accordance with DIN54006. Artwork supplied in 24-hours. Mat is printed 24 hours after artwork approval is given!

190 Logo Washable™

Logo Washable[™] can be fully customized with BrilliantStep[™] state-ofthe-art printing technology allowing 3-dimensional effects, fine lines and colour shading, for each mat to have its truly individual image.

Recommended use:

- Suitable for medium to heavy traffic conditions.
- For placement inside entrances of hotels, shops, department stores, schools, universities, restaurants, supermarkets.

Specifications:

- Tufted cut loop pile consisting of 100% non-crush polyamide 6.6 high twist yarns.
- 700 grams of yarns per m².
- Backing: nitrile rubber.
- Nitrile rubber borders: 2.5 cm on each side.
- Overall thickness: 8.5 mm.
- Weight: 2.8 kg per m².
- Fire rating: EN 13501-1 Bfl-S1.

Stock sizes:

- 60 cm x 85 cm
- 85 cm x 115 cm
- 85 cm x 150 cm
- 115 cm x 180 cm
- 115 cm x 240 cm
- 150 cm x 240 cm
- 150 cm x 300 cm

Cleaning tip:

• Machine washable at 50 °C or vacuum clean.

010 Uni Washable™

Uni Washable[™] can be printed as a mono-coloured mat in full colour to match your mat to any interior colour scheme or to use together with the custom printed logo mats for a colour coordinated matting system.

Recommended use:

- Suitable for medium to heavy traffic conditions.
- For placement inside entrances of hotels, shops, department stores, schools, universities, restaurants, supermarkets.

Specifications:

- Tufted cut loop pile consisting of 100% non-crush polyamide 6.6 high twist yarns.
- 700 grams of yarns per m².
- Backing: nitrile rubber.
- Nitrile rubber borders: 2.5 cm on each side.
- Overall thickness: 8.5 mm.
- Weight: 2.8 kg per m².
- Fire rating: EN 13501-1 Bfl-S1.

Stock sizes:

- 60 cm x 85 cm
- 85 cm x 115 cm
- 85 cm x 150 cm
- 115 cm x 180 cm
- 115 cm x 240 cm
- 150 cm x 240 cm
- 150 cm x 300 cm

Cleaning tip:

Machine washable at 50 °C or vacuum clean.

Product Testing

Water Retention			
Crush Resistance			
Dust Control			
	GOOD	BETTER	BEST



Product Testing

Water Retention			
Crush Resistance			
Dust Control			
	GOOD	BETTER	BEST



ErgoFloor A/S,

Viborgvej 9, 7160 Tørring,

g, Tlf. 76 90 20 01,

www.ergofloor.dk

Indoor Absorbent Printed





ErgeFloor A/S, Viborgvej 9, 7160 Tørring, Tlf. 76 90 20 01, www.ergofloor

With almost infinite colour combinations, Logo Superior™ logo mats can be printed in standard sizes, custom lengths and custom sizes up to 200 cm wide for loose lay or in recessed frames allowing tailor made matting solutions. This superior dust control mat is densely tufted to ensure a high water absorption capacity and dirt removal for a truly effective solution.

A durable vinyl backing with smooth finish adapts to any surface. The BrilliantStep[™] printing method ensures brilliant colours all the way through with a colour fastness that is ensured, in accordance with DIN54006. Artwork supplied in 24-hours. Mat is printed 24 hours after artwork approval is given!

198 Logo Superior™

Logo Superior™ can be fully customized with BrilliantStep™ state-ofthe-art printing technology allowing 3-dimensional effects, fine lines and colour shading, for each mat to have its truly individual image.

Recommended use:

- Suitable for medium to heavy traffic conditions.
- For placement inside entrances of hotels, shops, department stores, schools, universities, restaurants, supermarkets.

Specifications:

- Tufted cut loop pile consisting of 100% non-crush polyamide 6.6 twist yarns.
- 600 grams of yarns per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 8 mm.
- Weight: 3 kg per m². Fire rating: EN 13501-1 Cfl-S1.

Recommended accessories:

083 Bevelled Nosing 2 mm

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 150 cm
- 130 cm x 200 cm

Custom lengths and custom sizes:

- Up to 135 cm wide per linear meter
- Up to 200 cm wide per linear meter

Cleaning tip:

Vacuum clean.

018 Uni Superior™

Uni Superior[™] can be printed as a mono-coloured mat in full colour to match your mat to any interior colour scheme or to use together with the custom printed logo mats for a colour coordinated matting system.

Recommended use:

- Suitable for medium to heavy traffic conditions.
- For placement inside entrances of hotels, shops, department stores, schools, universities, restaurants, supermarkets.

Specifications:

- Tufted cut loop pile consisting of 100% non-crush polyamide 6.6 twist yarns.
- 600 grams of yarns per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 8 mm.
- Weight: 3 kg per m².
- Fire rating: EN 13501-1 Cfl-S1.

Recommended accessories:

083 Bevelled Nosing 2 mm

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 150 cm
- 130 cm x 200 cm

Custom lengths and custom sizes:

- Up to 135 cm wide per linear meter
- Up to 200 cm wide per linear meter

Cleaning tip:

Vacuum clean.

Product Testing Water Retention **Crush Resistan Dust Control** GOOD BETTER BEST



Product Testing

Water Retention Crush Resistar Dust Control GOOD BETTER BEST



www.ergofloor.dk

www.notrax.eu

ErgoFloor A/S,

Viborgvej 9, 7160 Tørring. Tlf. 76 90 20 01,

13

Indoor Absorbent Printed



ErgoFloor A/S, Viborgvej 9, 7160 Tø

7160 Tørring, Tlf. 76 90 20 01, www.ergofloor.dk

Logo Standard[™] is the ideal promotional matting solution for light duty applications.

Using BrilliantStep[™] full colour printing with almost infinite colour combinations, the densely tufted entrance

mat allows fine printing and true colour presentation.

A durable vinyl backing with smooth finish adapts to any surface. The BrilliantStep[™] printing method ensures brilliant colours all the way through with a colour fastness that is ensured, in accordance with DIN54006. Artwork supplied in 24-hours. Mat is printed 24 hours after artwork approval is given!

193 Logo Standard™

Logo Standard[™] can be fully customized with BrilliantStep[™] state-ofthe-art printing technology allowing 3-dimensional effects, fine lines and colour shading, for each mat to have its truly individual image.

Recommended use:

- Suitable for light traffic conditions.
- For placement inside entrances of offices, shops, restaurants, grocery shops, bakeries, specialty stores.

Specifications:

- Tufted cut loop pile consisting of 100% non-crush polyamide 6.0 high twist yarns.
- 405 grams of yarns per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 6 mm.
- Weight: 2.7 kg per m².

Recommended accessories:

083 Bevelled Nosing 2 mm

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 120 cm
- 90 cm x 150 cm
- 90 cm x 300 cm
- 120 cm x 180 cm

Custom lengths and custom sizes:

- Up to 90 cm wide per linear meter
- Up to 120 cm wide per linear meter

Cleaning tip:

• Vacuum clean.

015 Uni Standard[™]

Uni Standard[™] can be printed as a mono-coloured mat in full colour to match your mat to any interior colour scheme or to use together with the custom printed logo mats for a colour coordinated matting system.

Recommended use:

- Suitable for light traffic conditions.
- For placement inside entrances of offices, shops, restaurants, grocery shops, bakeries, specialty stores.

Specifications:

- Tufted cut loop pile consisting of 100% non-crush polyamide 6.0 high twist yarns.
- 405 grams of yarns per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 6 mm.
- Weight: 2.7 kg per m².

Recommended accessories:

083 Bevelled Nosing 2 mm

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 120 cm
- 90 cm x 150 cm
- 90 cm x 300 cm
- 120 cm x 180 cm

Custom lengths and custom sizes:

- Up to 90 cm wide per linear meter
- Up to 120 cm wide per linear meter

Cleaning tip:

• Vacuum clean.



lesting

Water Retention Crush Resistance Dust Control





7160 Tørring.

Product Testing



ergofloor.dk

15



obloor



A new alternative brush mat for loose lay or installation in recessed matwell frames. The Logo Brush[™] is a perfect scraper mat for porticos and outdoor protected areas. Made from a densely tufted AstroTurf[®] scraper yarn that is extremely durable, the Logo Brush[™] offers exceptional scraping and cleaning in all interior and exterior entrances.

A durable vinyl backing with smooth finish adapts to any surface. The BrilliantStep[™] printing method ensures brilliant colours all the way through with a colour fastness that is ensured, in accordance with DIN54006. Artwork supplied in 24-hours. Mat is printed 24 hours after artwork approval is given!

196 Logo Brush™

Logo Brush can be fully customized with BrilliantStep[™] state-of-the-art printing technology allowing 3-dimensional effects, fine lines and colour shading, for each mat to have its truly individual image.

Recommended use:

- Suitable for heavy traffic conditions.
- For placement indoors or outdoors in protected areas.
- For placement in recessed matwell frames (depth 16 mm) inside entrances of hotels, shops, department stores, schools, universities, restaurants, supermarkets.
- For placement as loose lay mat with recommended mounted bevels.

Specifications:

- Tufted cut loop pile consisting of 100% non-crush polyamide 6.6 high twist yarns.
- 1650 grams of yarns per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 18 mm.
- Weight: 4 kg per m².

Recommended accessories:

325 Bevelled Nosing 11 mm

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 150 cm
- 120 cm x 180 cm

Custom lengths and custom sizes:

- Up to 105 cm wide per linear meter, including bevels
- Up to 150 cm wide per linear meter, including bevels

Cleaning tip:

• Vacuum clean.

016 Uni Brush™

Uni Brush[™] can be printed as a mono-coloured mat in any of these 16 colours to match your mat to any interior colour scheme or to use together with the custom printed logo mats for a colour coordinated matting system.

Recommended use:

- Suitable for heavy traffic conditions.
- For placement indoors or outdoors in protected areas.
- For placement in recessed matwell frames (depth 16 mm) inside entrances of hotels, shops, department stores, schools, universities, restaurants, supermarkets.
- · For placement as loose lay mat with recommended mounted bevels.

Specifications:

- Tufted cut loop pile consisting of 100% non-crush polyamide 6.6 high twist yarns.
- 1650 grams of yarns per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 18 mm.
- Weight: 4 kg per m².

Recommended accessories:

• 325 Bevelled Nosing 11 mm

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 150 cm
- 120 cm x 180 cm

Custom lengths and custom sizes:

- Up to 105 cm wide per linear meter, including bevels
- Up to 150 cm wide per linear meter, including bevels

Cleaning tip:

• Vacuum clean.

Product Testing

Water Retention				
Dust Control				
	GOOD	BETTER	BEST	SUPERIOR



Product Testing

Water Retention Crush Resistance Dust Control GOOD BETTER BEST SUPERIOR



ergofloor.de



Design

These decorative dust control mats come in a large assortment of fashionable, attractive, funky, retro and fun printed mats to coordinate to any interior design and atmosphere. This high quality multi-functional dust control mat cleans and dries shoes, to prevent dirt and moisture getting tracked into facilities. Superior colour-fastness is ensured, in accordance with DIN 54006. For more designs, visit **www.notrax.eu**.

178 Déco Design Superior™

Vinyl backing with smooth finish.

Recommended use:

- Suitable for medium to heavy traffic conditions.
- For placement inside entrances of offices, shops, restaurants, grocery shops, bakeries, specialty stores.

Specifications:

- Tufted cut loop pile consisting of 100% non-crush polyamide 6.6 twist yarns.
- 600 grams of yarns per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 8 mm.
- Weight: 3 kg per m².
- Fire rating: EN 13501-1 Cfl-S1.

Recommended accessories:

083 Bevelled Nosing 2 mm

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 150 cm
- 130 cm x 200 cm

Custom lengths and custom sizes:

- Up to 135 cm wide per linear meter
- Up to 200 cm wide per linear meter

Cleaning tip:

• Vacuum clean.



Product Testing

otrax.eu

Water Retention	_		
Crush Resistance			
Dust Control			
	GOOD	BETTER	BEST

170 Déco Design™ Washable

Nitrile rubber backing with cleated pattern to minimize movement on all surfaces and to keep the mat elevated on hard floors to allow drying underneath.

Recommended use:

- Suitable for medium to heavy traffic conditions.
- For placement inside entrances of hotels, shops, department stores, schools, universities, restaurants, supermarkets.

Specifications:

- Tufted cut loop pile consisting of 100% noncrush polyamide 6.6 high twist yarns.
- 700 grams of yarns per m².
- Backing: nitrile rubber.
- Nitrile rubber borders: 2.5 cm on each side.
- Overall thickness: 8.5 mm.
- Weight: 2.8 kg per m².
- Fire rating: EN 13501-1 Bfl-S1.

Stock sizes:

- 60 cm x 85 cm
- 85 cm x 115 cm
- 85 cm x 150 cm
- 115 cm x 180 cm
- 115 cm x 240 cm
- 150 cm x 240 cm
- 150 cm x 300 cm

Cleaning tip:

• Machine washable at 50 °C or vacuum clean.



Product Testing

Viborgvej 9,



7160 Tørring,

1<mark>75 Déco Design™</mark> Standard

Vinyl backing with smooth finish.

Recommended use:

- Suitable for light traffic conditions.
- For placement inside entrances of offices, shops, restaurants, grocery shops, bakeries, specialty stores.

Specifications:

- Tufted cut loop pile consisting of 100% non-crush polyamide 6.0 high twist yarns.
- 405 grams of yarns per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 6 mm.
- Weight: 2.7 kg per m².

Recommended accessories: • 083 Bevelled Nosing 2 mm

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 120 cm
- 90 cm x 150 cm
- 90 cm x 300 cm
 120 cm x 180 cm
- 120 CIII X 160 CIII

Custom lengths and custom sizes:

- Up to 90 cm wide per linear meter
- Up to 120 cm wide per linear meter

Cleaning tip:

• Vacuum clean.



Water Retention			
Crush Resistance			
Dust Control			
	GOOD	BETTER	BEST

ErgoFloor A/S,

Indoor entrance mats for contract use and installation

Large commercial buildings with heavy traffic areas can see as much as 5000 crossings a day. For public buildings with high daily traffic, the benefits of a good entrance matting system are very measurable. A proper entrance matting system contributes to improving indoor air quality, improving acoustic performance, extending the useable life of interior flooring materials and reducing maintenance and cleaning costs.

Properly specifying entrance mats for installation and projects is important to securing all of the benefits. The type, quality and size of mat installed will vary according to the amount of foot traffic, the use of the building, the environment in which the building is situated and many other factors.

Functionality

Size, material and density play a role in durability, water absorption capacity and dirt removal – the more the better. Polyamide and polypropylene fibres are strong and durable offering brushing and scraping and are crush resistant meaning they hold their structure well making them suitable for large and busy entrances. Crush resistant mats will tolerate more wear and keep their appearance and functionality longer in high traffic conditions. Polyamide has superb absorption qualities yet is also stain resistant.

Shoes should touchdown at least three times on the mat for proper scraping, cleaning and drying. As a rule of thumb, it takes 2 meters of a good textile surface to trap 42% of moisture and dirt, 4 meters should achieve up to 65% and 6 meters up to 90%. LEED also recommends a permanent entryway walk-off system at least 10 feet (3 meters) long (up from 6 feet (1.8 meters) in previous versions of LEED).

Safety

Wet, slippery floors are dangerous. Entrances quickly become wet on rainy or snowy days. Smaller or inadequate matting can quickly become saturated making the situation worse. Heavily soiled mats allow contaminants to migrate to the interior floor. Entrance mats need a high water absorption rate to properly dry shoes. Absorption capacities between 4 to 6 litres of water per square meter are suitable for heavy traffic areas.

Entrances also become a main exit during fire or other emergencies. Since fire classifications vary by type of building, type of entrance and type of entrance matting system, it is recommended to consult the fire guidelines when selecting an entrance matting system.



Accessibility

Especially in public and commercial buildings, the entryway should be accessible for all. Architectural design guides specify that entrances must suit wheelchair users and accommodate people using mobility aids. Floors should have wheelchair friendly surface, be trip free and to remove water from wheels and shoes to reduce slippery surfaces within the building.

Entrance mats or recessed mat wells must be flush with the floor surface or any difference in height between the flooring surface and the mat should be limited to no more than $6 - 12 \text{ mm} (\frac{1}{4} \text{ to } \frac{1}{2})$. Carpets should be of shallow dense pile that is non-directional to allow easy passage for wheelchair users and for people using crutches. Avoid coir matting, deep pile or excessively grooved carpet. Preferably the recessed mat frame at main entrances should be as wide as the entrance.

Cleaning and maintenance affect continued effectiveness

Entrance mats function optimally when regularly cleaned. By removing soils through a combination of grooming, vacuuming, and extraction, the life span of the mat can be extended. Permanently installed mats need to undergo regular maintenance and thorough cleaning to remove the build-up of contaminants that could otherwise be tracked throughout a facility. A maintenance schedule should include daily vacuuming of the top surface, especially in heavy traffic areas, to prevent dirt from building up and being ground into the mat. Weekly grooming of the carpet will maximize vacuuming by loosening the fibres and creating easier access to the soil underneath. Grooming also helps to aerate fibres to allow quicker drying. Monthly injection and extraction shampooing will clean fibres and remove any leftover dirt.

Customization

Entrance matting is manufactured on rolls of approximately 20 meters.

The Notrax® production team tailor makes every Notrax® product to order to the exact dimensions of the client. Almost all Notrax[®] products can be customized per linear meter and factory finished, including matched bevelled nosing to finish off the mat.

Other special shapes or forms, including circles, half-moons, and arches can be produced for custom installations. All customized matting can be supplied with recommended accessories such as bevelled edging or seaming tape for width-wise expansion.

Installation

A recessed matwell frame is a sunken recess in standard entrances, under automatic doors or rotating doors. The matwell ensures the mat is flush with the floor, provides stability for the mat and helps to contain dirt and debris between cleanings.

To ensure a perfect fit of Notrax® entrance mats in the recess, select the proper thickness to ensure the mat is flush with the floor and allows proper door closure.

Notrax[®] Recess Fillers are available in various thicknesses to adjust the depth of an existing recess as needed. Gluing may not always be required. Notrax® heavy duty entrance matting generally stays in place in recessed frames. For larger entrances where gluing may be required, vinyl compatible double sided-tape or a solvent free adhesive is recommended.

Here are the glues of manufacturers that we can recommend.

UZIN

- UZIN KR430
- UZIN KE 66
- SIGAN ELEMENTS

SCHÖNOX

- SCHÖNOX EMICLASSIC
- SCHÖNOX PU 900 (component glue)

- EUROCOL
- 540 EUROSTAR SPECIAL
- 640 EUROSTAR SPECIAL (low emissions for BREEAM)

F. BALL & CO. LTD.

- F 45 copolymer emulsion with excellent resistance to plasticizer migration.
- F 74 one-pack moisture curing polyurethane adhesive.
- F 81 2-part epoxy, solvent free adhesive.
- F 83 2-part adhesive, solvent free, water-resistant.
- F 84 2-part, solvent free adhesive, for use only with STOPGAP Isolator Membrane.

ErgoFloor A/S,

www.notrax.eu

-10"

ENTRANCE

Viborgvej 9, 7160 Tørring, TIF. 76 90 20 01,

www.ergofloor.dk

Indoor Contract and Installation Matting

380 Swisslon Classic XT™



Anthracite (CH)



Cobalt (BU)



Granite (GT)



Slate Grey (GY)



Mocha (BR)



www.notrax.eu

380 Swisslon Classic XT™

Premium quality barrier matting, designed to remove walked-in moisture and finer dirt particles in large indoor entrance areas, including wall-to-wall applications.

Our new classic barrier mat, known for its softer yarns, has been enhanced with a mono-filament to offer additional scraping and provide excellent cleaning and absorbing. The new tri-colour grit pattern provides outstanding dirt-hiding characteristics.

Great ability to retain moisture (>5.8 litres per m²) and scrape debris from foot traffic while maintaining its great looking appearance for the longest time. A dense heavyweight vinyl backing ensures longevity.

Recommended use:

- Suitable for heavy traffic conditions.
- For placement in recessed matwell frames (depth 7 mm) or wall-to-wall installations in larger entrances at hotels, public buildings, schools, universities, hospitals, department stores, banks, restaurants and on stairs.

Specifications:

- Densely tufted cut loop pile (81.000 tufts per m²) consisting of 100% polyamide 6 yarns.
- 850 grams of yarn per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 9 mm.
- Weight: 3.6 kg per m².
- Fire rating: EN 13501-1 Cfl-S1.

Recommended accessories:

083 Bevelled Nosing 2 mm

Full rolls:

- 135 cm x 20 meters
- 200 cm x 20 meters

Custom lengths:

- 135 cm per linear meter
- 200 cm per linear meter

Colours:

- Anthracite (CH)
- Cobalt (BU)
- Granite (GT)
- Slate Grey (GY)
- Mocha (BR)

Cleaning tip:

Vacuum/shampooing or use injection/extraction method to clean.

Product Testing

۷	Vater Retention				
C	rush Resistance				
0	Just Control				
		GOOD	BETTER	BEST	SUPERIOR



Tlf. 76 90 20 01,

www.ergofloor.dk

23

Indoor Contract and Installation Matting

389 Swisslon Plus™ Wave colours





Wave Taupe (WT)



Wave Grey (WG)







Wave Black (WK)



389 Swisslon Plus™ Twine colours



Twine Charcoal (TC)



Twine Taupe (TT)



Twine Grey (TG)



Twine Blue (TB)



Twine Black (TK)



389 Swisslon Plus™

Plush entrance matting with exceptional scraping and unsurpassed water absorbing qualities (5.5 litres per m²) for large indoor entrance areas, including wall-to-wall applications and stairs. Coarse yarns provide superb scraping and absorbing of dirt and moisture. Stylish yet subtle chevron pattern or streaked pattern versions hide dirt to maintain their elegant appearance. A dense heavyweight vinyl backing ensures longevity.

Recommended use:

- Suitable for heavy traffic conditions.
- For placement in recessed matwell frames (depth 7 mm) or wallto-wall installations in larger entrances at hotels, shopping malls, cinemas, public buildings, department stores, banks, restaurants and on stairs.

Specifications:

- Densely tufted cut loop pile (73,340 tufts per m²) consisting of coarse 100% polyamide 6.6 yarns.
- 900 grams of yarn per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 8.5 mm.
- Weight: 3.4 kg per m².
- Fire rating: EN 13501-1 Cfl-S1.

Recommended accessories:

083 Bevelled Nosing 2 mm

Full rolls:

- 130 cm x 20 meters
- 200 cm x 20 meters

Custom lengths:

- 130 cm per linear meter
- 200 cm per linear meter

Wave colours:

- Wave Charcoal (WC)
- Wave Red (WR)
- Wave Taupe (WT)
- Wave Blue (WB)
- Wave Grey (WG)
- Wave Black (WK)

Twine colours:

- Twine Charcoal (TC)
- Twine Red (TR)
- Twine Taupe (TT)
- Twine Blue (TB)
- Twine Grey (TG)
- Twine Black (TK)

Cleaning tip:

Vacuum/shampooing or use injection/extraction method to clean.

Product Testing

Water Retention				
Crush Resistance				
Dust Control				
	600D	BETTER	REST	SUPERIOR



Indoor Contract and Installation Matting

388 Swisslon Uni™



Blue (BU)



Brown (BR)



388 Swisslon Uni™

Uni-coloured entrance matting with exceptional scraping and unsurpassed water absorbing qualities (5.5 litres per m²) for large indoor entrance areas, including wall-to-wall applications and stairs.

Coarse yarns provide superb scraping and absorbing of dirt and moisture. Rich mono-colour tones stay bright even after prolonged use and hide dirt to maintain their elegant appearance.

A dense heavyweight vinyl backing ensures longevity.

Recommended use:

- Suitable for heavy traffic conditions.
- For placement in recessed matwell frames (depth 7 mm) or wallto-wall installations in larger entrances at hotels, shopping malls, cinemas, public buildings, department stores, banks, restaurants and on stairs.

Specifications:

- Densely tufted cut loop pile (73,340 tufts per m²) consisting of coarse 100% polyamide 6.6 yarns.
- 900 grams of yarn per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 8.5 mm.
- Weight: 3.4 kg per m².
- Fire rating: EN 13501-1 Cfl-S1.

Recommended accessories:

083 Bevelled Nosing 2 mm

Full rolls:

- 130 cm x 20 meters
- 200 cm x 20 meters

Custom lengths:

- 130 cm per linear meter
- 200 cm per linear meter

Colours:

- Charcoal (CH)
- Red (RD)
- Taupe (TP)
- Black (BL)Grey (GY)
- Blue (BU)
- Brown (BR)

Cleaning tip:

• Vacuum/shampooing or use injection/extraction method to clean.

Product Testing

Water Retention				
Crush Resistance				
Dust Control				
	6000	RETTER	REST	SUPERIOR



Indoor Contract and Installation Matting

387 Swisslon Flair™



Charcoal (CH)



Red-Black (RB)



Taupe (TP)



Blue-Black (BB)



Grey (GY)



Brown (BR)



387 Swisslon Flair™

Stylish and modern entrance matting with exceptional scraping and unsurpassed water absorbing qualities (5.5 litres per m²) for large indoor entrance areas, including wall-to-wall applications and stairs. Coarse yarns provide superb scraping and absorbing of dirt and moisture. Contemporary streaked pattern hides dirt to maintain the classy appearance. A dense heavyweight vinyl backing ensures longevity.

Recommended use:

Suitable for heavy traffic conditions.

For placement in recessed matwell frames (depth 7 mm) or wallto-wall installations in larger entrances at hotels, shopping malls, cinemas, public buildings, department stores, banks, restaurants and on stairs.

Specifications:

- Densely tufted cut loop pile (133,600 tufts per m²) consisting of coarse 100% polyamide 6.6 yarns.
- 750 grams of yarn per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 8 mm.
- Weight: 3.5 kg per m².
- Fire rating: EN 13501-1 Cfl-S1.

Recommended accessories:

083 Bevelled Nosing 2 mm

Full rolls:

- 130 cm x 20 meters
- 200 cm x 20 meters

Custom lengths:

- 130 cm per linear meter
- 200 cm per linear meter

Colours:

- Charcoal (CH)
- Red-Black (RB)
- Taupe (TP)
- Blue-Black (BB)
- Grey (GY)
- Brown (BR)

Cleaning tip:

• Vacuum/shampooing or use injection/extraction method to clean.

Product Testing

Water Retention				
Crush Resistance				
Dust Control				
	GOOD	BETTER	BEST	SUPERIOR



www.notrax.eu

ErgoFloor A/S, Viborgvej 9,

7160 Tørring,

Tlf. 76 90 20 01,

29

Indoor Contract and Installation Matting

Stock colours: Full rolls or per linear meter



Course (CV)

Grey (GY)

Brown (BR)



Red (RD)



Natural (NA)



Autumn Black (AB)

Autumn Brown (AM)

Special colours: Full rolls



Royal-Blue (RY)



Burgundy (WI)



in more firest

Autumn Ochre (AO)

30.



Green (GN)



Autumn Burgundy (AW)



Autumn Green (AG)



Durable carpet flooring, designed for large indoor entrance areas, including wall-to-wall applications. Offers many possibilities for creative combinations that will allow the entrance to become part of the complete interior design. Great ability to retain moisture and scrape debris from foot traffic while maintaining its great looking appearance for the longest time. Mould and mildew resistant, UV stabilized, crush resistant and remains unaffected by climate extremes. Synthetic rubber backing.

113 Master Trax[™]

Recommended use:

- Suitable for the heaviest of traffic conditions.
- For placement inside entrances or outside if not exposed to rain.
- In recessed frames (depth 10 mm) or wall-to-wall installations in shopping malls, airports, hospitals, hotel lobbies, banks, restaurants, golf facilities (spike resistant), fitness centers, elevators, locker rooms, ski lodges, skating rinks, automobile showrooms, any public or professional building.
- For placement as loose lay mat with recommended mounted bevels.

Specifications:

- Nibbed needle punched carpet consisting of anti-static 100% polypropylene fibres.
- Easy to install, can be cut to any size or shape without edge ravel.
- 1700 grams of yarn per m².
- Backing: synthetic rubber.
- No borders.
- Overall thickness: 11 mm.
- Weight: 3.2 kg per m².
- Fire rating: ASTM D2859 passes DOC-FF-1-70.

Recommended accessories:

- 113K Master Trax[™] Stitched Bevels
- 325 Bevelled Nosing 11 mm

Full rolls:

- 200 cm wide, length may vary based on production
- 400 cm wide rolls available on request.

Custom lengths:

• 200 cm per linear meter

Colours:

- Charcoal (CH)
- Red (RD)
- Grey (GY)
- Blue (BU)
- Brown (BR)
- Natural (NA)
- Autumn Black (AB)
- **Cleaning tip:**

www.notrax.eu

• Vacuum/shampooing or use injection/extraction method to clean.

Product Testing

Water Retention				
Crush Resistance				
Dust Control				
	GOOD	BETTER	BEST SUPERIOR	



Autumn Brown (AM)

Royal-Blue (RY)

Burgundy (WI)

Green (GN)

Special colours: Full rolls only

Autumn Burgundy (AW)

Autumn Ochre (AO)

Autumn Green (AG)

103 Master Trax Lite™

Recommended use:

- Suitable medium to heavy traffic conditions.
- For placement inside entrances or outside if not exposed to rain.
- In recessed frames (depth 8 mm) or wall-to-wall installations.
- For placement as loose lay mat with recommended mounted bevels.

Specifications:

- Nibbed needle punched carpet consisting of anti-static 100% polypropylene fibres.
- Easy to install, can be cut to any size or shape without edge ravel.
- 1200 grams of yarn per m².
- Backing: synthetic rubber.
- No borders.
- Overall thickness: 9 mm.
- Weight: 2.2 kg per m².
- Fire rating: ASTM D2859 passes DOC-FF-1-70.

Recommended accessories:

084 Bevelled Nosing 4 mm

Full rolls:

• 200 cm wide, length may vary based on production

Custom lengths:

200 cm per linear meter (Charcoal only)

Special colours: Full rolls only

- Charcoal (CH)
- Red (RD)
- Grey (GY)
- Blue (BU)
- Brown (BR)

Cleaning tip:

• Vacuum/shampooing or use injection/extraction method to clean.

Product Testing





Indoor loose lay entrance mats are suitable for any entrance

Entrance matting is the first line of defense in keeping dirt and debris from entering the building and can remove up to 80% of dirt. The benefits of a good entrance matting system are very measurable in annual savings of cleaning costs. In building design, however, the functionality of mats in entryways to trap dirt, remove tracked-in pollutants from shoes and improve air quality, is often overlooked.

Entrances that lack a mat are more susceptible to slips and falls due to wet or dirty floors. During bad weather conditions including rain, snow and sleet, interior flooring can quickly become slippery and interior carpet can become saturated. In dry weather, entrance ways can accumulate dirt on the surface. Sand, bits of gravel and dirt are commonly called "boulder dust" because they act as miniature ball bearings when caught between a hard floor surface and a smooth shoe sole. The shoe loses traction and skids away causing the person to lose control and fall.

Functionality

Loose lay entrance mats are a practical and quick solution for entrances, large or small, where there is no matting, inadequate matting, where slips are common or when current matting becomes saturated in extreme weather conditions. Entrance mats can be easily rolled out over any existing flooring. Entrance mats can also complement an existing matting system by extending the entrance mat area or by adding an additional cleaning or drying zone.

As with installation matting, size, material and density of loose lay mats play a role in durability, water absorption capacity and dirt removal – the more the better.

Shoes should touchdown at least three times on the mat for proper scraping and drying. LEED also recommends a permanent entryway walk-off system at least 10 feet (3 meters) long (up from 6 feet (1.8 meters) in previous versions of LEED).



CAUTION WET FLOOR

ErgoFloor A/S,

Viborgvej 9, 7160 Tørring,

rring, Tlf. 76 90 20

www.ergofloor.dk

www.notrax.eu

In smaller entrances, it is not always possible to install a large matting system. It is then advised to split the 3 zones into an outdoor or portico scraping zone, and an interior cleaning and drying zone with an indoor mat made of a higher quality material to maximize the functionality.

Polyamide has superb absorption qualities yet is also stain resistant. Polyamide and polypropylene fibres are strong and durable offering brushing and scraping and are crush resistant meaning they hold their structure well making it suitable for large and busy entrances. Crush resistant mats will tolerate more wear and keep their appearance and functionality longer in high traffic conditions.

Safety

With loose lay matting, it is important to frequently inspect the mats to ensure they have not buckled or curled to prevent tripping hazards.

Matting should be placed on a clean and level surface. Make sure that your mats are firmly secured to the floor to prevent migration. Larger mats will remain in place due to the size and weight of the mat. To prevent shifting of smaller mats, Notrax[®] 090 Mat Hold[™] or 085 Velcro[®] Carpet Anchor strips can be attached to the mat backing to keep the mat in place on smooth flooring or carpet.

Entrances also become a main exit during fire or other emergencies. Since fire classifications vary by type of building, type of entrance and type of entrance matting system, it is recommended to consult the fire guidelines when selecting an entrance matting system. Although for loose lay matting, fire classifications are less stringent, since the mat can be easily removed in the event of a fire.

Customization and Finishing

Notrax[®] loose lay entrance mats are available in a multitude of standard sizes as well as custom lengths, available per linear meter. Matting is customized to any length and fully factory finished including mounted bevelled nosing to finish off the mat and prevent tripping. Other special shapes or forms, including circles, half-moons, and arches can be produced for custom installations. All customized matting can be supplied with recommended accessories such as bevelled edging, 090 Mat Hold[™] or 085 Velcro[®] Carpet Anchor strips.

Maintenance & Cleaning

Loose lay entrance mats function optimally when regularly cleaned and weekly maintenance is required by sustainable and environmental building assessors, such as LEED (Leadership in Energy and Environmental Design) and BREEAM (Building Research Establishment Environmental Assessment Method).

A maintenance schedule should include daily vacuuming of the top surface, especially in heavy traffic areas, to prevent dirt from building up and being ground into the mat. Grooming of the carpet will maximize vacuuming by loosening the fibres and creating easier access to the soil underneath. Grooming also helps to aerate fibres to allow quicker drying. Also sweep or vacuum under the mat to clean the floor or carpet underneath. Injection and extraction shampooing will clean fibres and remove any leftover dirt. By removing soils through a combination of grooming, vacuuming, and extraction, the life span of the mat can be extended.

ww.notrax.eu

ErgoFloor A/S,

Viborgvej 9, 716

7160 Tørring, T

Tlf. 76 90 20 01, www.ergofloor.dk

Indoor Loose Lay Carpet Mats Elegance

380 Swisslon Classic™



Blue (BU)



Blue Grey (BG)



Charcoal (CH)



ErgoFloor A/S,

380 Swisslon Classic™

Premium quality barrier matting designed to remove walked-in moisture and finer dirt particles in large indoor entrance areas.

Our Swisslon Classic[™] barrier mat is well known for its soft yarns that offer excellent cleaning and absorbing while the duo-colour diamond pattern provides outstanding dirt-hiding characteristics.

Great ability to retain moisture (>5 litres per m²) and scrape debris from foot traffic while maintaining its great looking appearance for the longest time. A dense heavyweight vinyl backing ensures longevity.

Recommended use:

- Suitable for heavy traffic conditions.
- For placement as loose lay mat, in larger entrances at hotels, public buildings, schools, universities, hospitals, department stores, banks, restaurants.

Specifications:

- Densely tufted cut loop pile (85.500 tufts per m²) consisting of 100% polyamide yarns.
- 950 grams of yarn per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 9.4 mm.
- Weight: 3.8 kg per m².
- Fire rating: EN 13501-1 Bfl-S1.

Stock sizes:

- 90 cm x 150 cm
- 120 cm x 180 cm

Colours:

- Blue (BU)
- Blue Grey (BG)
- Charcoal (CH)

Cleaning tip:

Vacuum/shampooing or use injection/extraction method to clean.

Product Testing

www.notrax.eu



doFloor



vei 9, 7160 Tørring,

T.If. 76 90 20 01, www.ergoflo

Indoor Loose Lay Carpet Mats Elegance

145 Preference®



Charcoal (CH)





Navy Blue (NB)



Brown (BR)



Burgundy (BD)



Green (GN)



145 Preference®

Exceptional performance in high visibility areas that require an attractive yet functional matting product.

Combination of tough and soft yarns provides excellent scraping and absorption. Its low profile allows foot and wheel traffic to traverse easily.

The mat is crush resistant and the dense heavyweight vinyl backing ensures longevity and minimum movement.

Recommended use:

- Suitable for medium to heavy traffic conditions.
- For placement inside entrances in offices, hotels, banks, professional buildings, restaurants, department stores.

Specifications:

- Loop pile carpet of tough polypropylene grass yarns and soft Decalon[®] yarns, tufted in attractive chessboard design.
- 900 grams of dual yarns per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 8 mm.
 Weight: 4 kg per m².
- Fire rating: ASTM D2859 passes DOC-FF-1-70.

Recommended accessories:

083 Bevelled Nosing 2 mm

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 120 cm
- 90 cm x 150 cm
- 120 cm x 180 cm
 120 cm x 240 cm

Full rolls:

- 120 cm x 18.3 meters
- 180 cm x 18.3 meters

Custom lengths:

- 120 cm per linear meter
- 180 cm per linear meter

Colours:

- Charcoal (CH)
- Red (RB)
- Navy Blue (NB)
- Brown (BR)Burgundy (BD)
- Green (GN)

Cleaning tip:

Vacuum clean.

Product Testing

www.notrax.eu



Indoor Loose Lay Carpet Mats Upscale

138 Uptown[™]







Navy Blue (NB)



Brown (BR)





Green (GN)



www.notrax.eu
138 Uptown[™]

The Uptown[™] absorbent mat with its aesthetically appealing design presents an upscale look that is functional too.

The checked pattern easily hides dirt and debris while providing the functionality of drying and retaining moisture.

The mat is crush resistant and the dense heavyweight vinyl backing ensures longevity and minimum movement.

Recommended use:

- Suitable for medium to heavy traffic conditions.
- For placement inside entrances in offices, hotels, banks, professional buildings, restaurants, department stores.

Specifications:

- Loop pile carpet densely tufted high-low pattern of 100% Decalon[®] yarns.
- 1270 grams of yarns per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 9.5 mm.
 Weight: 4.6 kg per m².
- Fire rating: ASTM D2859 passes DOC-FF-1-70.

Recommended accessories:

083 Bevelled Nosing 2 mm

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 150 cm
- 120 cm x 180 cm

Full rolls:

- 120 cm x 18.3 meters
- 180 cm x 18.3 meters

Custom lengths:

- 120 cm per linear meter
- 180 cm per linear meter

Colours:

- Charcoal (CH)
- Red (RB)
- Navy Blue (NB)
- Brown (BR)
- Burgundy (BD)Green (GN)
- dicen (dit)

Cleaning tip:

• Vacuum or use injection/extraction method to clean.

Product Testing

Water Retention			
Crush Resistance			
Dust Control			
	GOOD	BETTER	BEST



www.notrax.eu

ErgoFloor A/S,

Viborgvej 9, 7160

7160 Tørring, Tlf.

Tlf. 76 90 20 01, www.ergofloor.dk

Indoor Loose Lay Carpet Mats Upscale

238 Silverline™



Silver Charcoal (CB)



Silver Blue (BU)



Silver Brown (SB)

238 Silverline™

The Silverline[™] absorbent mat with its aesthetically appealing duo-tone design presents an upscale look that is functional too.

The silver-lined pattern easily hides dirt and debris while providing the functionality of drying and retaining moisture.

The mat is crush resistant and the dense heavyweight vinyl backing ensures longevity and minimum movement.

Recommended use:

- Suitable for medium to heavy traffic conditions.
- For placement inside entrances in offices, hotels, banks, professional buildings, restaurants, department stores.

Specifications:

- Silver line pattern loop pile carpet densely tufted high-low pattern of 100% Decalon[®] yarns.
- 1270 grams of yarns per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on all sides.
- Overall thickness: 9.5 mm.
 Weight: 4.6 kg per m².
- Fire rating: ASTM D2859 passes DOC-FF-1-70.

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 150 cm
- 120 cm x 1<mark>80 cm</mark>

Colours:

- Silver Charcoal (CB)
- Silver Blue (BU)
- Silver Brown (SB)

Cleaning tip:

• Vacuum or use injection/extraction method to clean.

Product Testing



orgvej 9.

Indoor Loose Lay Carpet Mats Elegance

137 Opera™



Zone 2 Grey (GY)



Zone 3 Grey (GY)

231 Prelude™

Grey (GY)



137 Opera[™]

A Notrax[®] exclusive: the Opera[™] mat is the first of its kind with a 3-zone system in one beautiful mat design.

Zone 1:

Scrape: aggressively scrapes heavy debris off shoe soles.

Zone 2:

Clean: combines scraping and drying in a striped pattern that follows the flow of traffic to thoroughly complete the cleaning process.

Zone 3:

Dry: dries shoes to prevent slipping.

Low profile allows foot and wheel traffic to traverse easily. A dense heavyweight vinyl backing ensures longevity and minimum shifting or movement.

Recommended use:

- Suitable for medium to heavy traffic conditions.
- For placement inside entrances in offices, hotels, banks, professional buildings schools, universities, restaurants, and department stores.

Specifications:

- Loop pile carpet of tough polypropylene grass yarns and soft Decalon[®] yarns, tightly tufted in an attractive design consisting of 3 different zones.
- 800 grams of dual yarns per m².
- Backing: vinyl (DOP free).
- Vinyl borders: 2.5 cm on all sides.
- Overall thickness: 7 mm.
- Weight: 4 kg per m².
- Fire rating: ASTM D2859 passes DOC-FF-1-70.

Stock sizes:

- 90 cm x 305 cm (L)
- 120 cm x 366 cm (XL)
- 180 cm x 366 cm (XXL)

Colours:

Grey (GY)

Cleaning tip:

Vacuum or use injection/extraction method to clean.

231 Prelude™

A coarse heavy duty surface that aggressively scrapes debris off shoe soles suitable for placement outdoors in porticos and protected areas to prevent dirt from entering the building. The 231 Prelude™ has coarse grass yarns for ultimate crush resistance. The dense heavyweight vinyl backing ensures longevity and minimum movement. Low profile allows foot and wheel traffic to traverse easily. The 231 Prelude[™] colour coordinates with the 137

Opera[™] and can be used as an external mat extension

or in tandem.

Recommended use:

- · Suitable for medium to heavy traffic conditions.
- Suitable for outdoor use in covered or protected areas or for placement inside entrances in offices, hotels, banks, professional buildings, restaurants, department stores.

Specifications:

- Tufted loop pile of high grade non-absorbent scraping polypropylene grass yarns.
- 800 grams of yarns per m².
- Backing: vinyl (DOP free).
- Vinyl borders: 2.5 cm on all sides.
- Overall thickness: 7 mm.
- Weight: 4 kg per m².
- Fire rating: ASTM D2859 passes DOC FF 1-70.

Stock sizes:

- 90 cm x 150 cm
- 120 cm x 180 cm
- 120 cm x 240 cm

Colours:

• Grey (GY)

Cleaning tip:

• Vacuum or use injection/extraction method to clean.



Product Testing

Water Retention **Crush Resistan** Dust Control

GOOD BETTER BEST



Indoor Loose Lay Carpet Mats Heavy Duty

150 Aqua Trap®



Charcoal (CH)



Red (RB)



Blue (BU)



Grey (GY)



Brown (BR)



www.notrax.eu

150 Aqua Trap®

True to its name, this patented perimeter "Aqua Dam" forms a tray that can hold up to 6 litres of water per square meter and is treated with an anti-microbial carpet treatment to stop bacteria and germs at the entrance.

The textile top surface is high pressure moulded into a bubble design on an indestructible rubber base to withstand the heaviest of foot traffic.

Unsurpassed ability to scrape debris from shoes while maintaining its great looking appearance for the longest time.

Unique slip resistant gripper pattern on the back.

Recommended use:

- Suitable for the heaviest of traffic conditions.
- For placement inside entrances in schools, universities, public buildings, sports facilities, shopping malls.

Specifications:

- Heavy duty needle punched polyester fibers are permanently bonded onto a heavy duty contour moulded rubber base.
- 850 grams of yarns per m².
- Backing: natural rubber.
- Fabric covered borders: 2.5 cm on all sides.
- Overall thickness: 13 mm.
 Weight: 5.2 kg per m².
- Fire rating: ASTM D2859 passes DOC-FF-1-70.

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 150 cm
- 120 cm x 180 cm

Colours:

- Charcoal (CH)
- Red (RB)
- Blue (BU)
- Grey (GY)
- Brown (BR)

Cleaning tip:

 Vacuum or use extraction method to clean or hose off with water and hang to dry.



Product Testing

Water Retention Crush Resistance Dust Control GOOD BETTER BEST SUPERIOR

ErgoFloor A/S,



Indoor Loose Lay Carpet Mats Heavy Duty

166 Guzzler™



Charcoal (CH)



Red (RB)



Grey (GY)



Blue (BU)



Brown (BR)



Green (GN)



166 Guzzler™

Tough, long-lasting carpet mat with raised rubber borders on all 4 sides acts as a containment barrier and can hold up to 6 litres of water per square meter.

The raised waffle pattern works double duty to remove and trap dirt and moisture.

Rubber reinforced borders and backing provide maximum strength.

Cleated backing minimizes movement on all surfaces and keeps mat elevated allowing wet hard floors to dry underneath.

Recommended use:

- Suitable for medium to heavy traffic conditions.
- For placement inside entrances in schools, universities, public buildings, sports facilities, shopping malls.

Specifications:

- Tufted looped pile carpet top consisting of absorbing Decalon[®] yarns moulded in to a waffle pattern on to a rubber base.
- 830 grams of yarns per m².
- Backing: natural rubber.
- Rubber borders: 2.5 cm on all sides.
- Overall thickness: 10.5 mm.
- Weight: 4.4 kg per m². Fire rating: ASTM D2859 passes DOC-FF-1-70.

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 120 cm
- 90 cm x 150 cm
- 120 cm x 180 cm

Colours:

- Charcoal (CH)
- Red (RB)
- Grey (GY)
- Blue (BU)
- Brown (BR)
- Green (GN)

Cleaning tip:

 Vacuum or use extraction method to clean or hose off with water and hang to dry.



Product Testing

Water Retention Crush Resistance Dust Control GOOD BETTER BEST



Indoor Loose Lay Carpet Mats Heavy Duty

118 Arrow Trax[™]



Grey (GY)



Brown (BR)



Autumn Brown (AB)



118 Arrow Trax™

The non-directional chevron pattern of the Arrow Trax[™] ensures a very aggressive scraping action making it one of our most popular carpet mats offering tremendous value.

The needle punched fibers are durable and crushresistant for extreme grime retention making it suitable for heavy traffic areas. Dense vinyl backing is moisture resistant and slip resistant to keep the mat in place.

Recommended use:

- Suitable for heavy traffic conditions.
- For placement inside entrances in schools, universities, public buildings, offices, sports facilities, shopping malls.

Specifications:

- Needle punched carpet consisting of anti-static 100% polypropylene fibres.
- 1200 grams of fibres per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 10 mm.
- Weight: 3.7 kg per m².
 Fire rating: ASTM D2859 passes DOC-FF-1-70.

Recommended accessories:

• 083 Bevelled Nosing 2 mm

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 150 cm
- 120 cm x 180 cm
- 130 cm x 300 cm
- 130 cm x 600 cm

Full rolls:

- 130 cm x 20 meters
- 200 cm x 20 meters

Custom lengths:

- 130 cm per linear meter
- 200 cm per linear meter

Colours:

- Charcoal (CH)
- Grey (GY)
- Brown (BR)
- Autumn Brown (AB)

Cleaning tip:

• Vacuum clean.

Product Testing

	GOOD	BETTER	BEST
Dust Control			
Crush Resistance			
Water Retention			



Indoor Loose Lay Carpet Mats Functional

185 Essence™



Dark Grey (DG)





Black (BL)



Light Grey (GY)



Brown (BR)



185 Essence™

Affordable yet very functional with a high water absorption capacity of over 4 litres per square meter. This product is the perfect solution to fit any budget while providing a quality entrance matting solution.

The uni-colours are made from soft nylon yarns with rich colour tones that stay bright even after prolonged use and hides dust and fine particles.

Low profile allows foot, cart and wheelchair traffic to move easily over the mat.

Vinyl backing is moisture resistant and slip resistant.

Recommended use:

- Suitable for light to medium traffic conditions.
- For placement inside entrances of schools, offices, shops.

Specifications:

- Tufted cut pile carpet made of 100% polyamide 6.0 yarns.
- 520 grams of yarns per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 6 mm.
- Weight: 2.8 kg per m².

Recommended accessories:083 Bevelled Nosing 2 mm

- Stock sizes:
- 60 cm x 90 cm
- 90 cm x 150 cm
- 90 cm x 120 cm
- 120 cm x 180 cm

Colours

- Dark Grey (DG)
- Red (RD)
- Black (BL)
- Light Grey (GY)
- Brown (BR)

Full rolls:

130 cm x 20 meters

Custom lengths: (Dark Grey and Red only)

• 130 cm per linear meter

Cleaning tip:

Vacuum or use injection/extraction method to clean.

Product Testing



Indoor Loose Lay Carpet Mats Functional

130 Polyplush™



Blue (BU)

Red Black (RB)



Brown (BR)



ErgoFloc

Simple, stylish and affordable yet very functional entrance mats with a high water absorption capacity that also captures dirt. Plush matting in muted uni-colours easily blends in any interior yet hides dirt and fine particles. These entrance mats are our top sellers for use in moderate foot traffic areas. Vinyl backing is moisture resistant and slip resistant.

130 Polyplush™

Recommended use:

- Suitable for light to medium traffic conditions.
- For placement inside entrances of schools, offices, shops.

Specifications:

- Tufted cut pile carpet made of 100% Decalon[®] yarns.
- 700 grams of yarn per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 6.5 mm.
- Weight: 3.2 kg per m².
- Fire rating: ASTM D2859 passes DOC-FF-1-70.

Recommended accessories:

083 Bevelled Nosing 2 mm

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 120 cm
- 90 cm x 150 cm
- 120 cm x 180 cm
 120 cm x 240 cm
- 120 cm x 240 cm

Full rolls:

- 90 cm x 18.3 meters
- 120 cm x 18.3 meters
- 180 cm x 18.3 meters

Custom lengths:

- 90 cm per linear meter
- 120 cm per linear meter
- 180 cm per linear meter

Colours

- Grey (CH)Red Black (RB)
- Blue (BU)
- Brown (BR)
- Green (GN)

Cleaning tip:

Vacuum clean.

Product Testing

Water Retention Crush Resistance Dust Control GOOD BETTER BEST

123 Polyplush Lite™

Recommended use:

- Suitable for light traffic conditions.
- For placement inside entrances of offices, shops.

Specifications:

- Tufted cut pile carpet made of 100% polypropylene yarns.
- 350 grams of yarn per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 4.5 mm.
- Weight: 2.4 kg per m².
- Fire rating: EN 13501-1 Cfl-S1.

Recommended accessories:

083 Bevelled Nosing 2 mm

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 150 cm
- 120 cm x 180 cm

Full rolls:

- 90 cm x 20 meters
- 120 cm x 20 meters

Custom lengths:

- 90 cm per linear meter
- 120 cm per linear meter

Colours

- Grey (GY)
- Red Black (RB)
- Blue (BU)
- Brown (BR)

Cleaning tip:

• Vacuum clean.

Product Testing

Water Retention Crush Resistance Dust Control GOOD BETTER BEST



Tlf. 76 90 20 01, www.ergofloor.dk



Indoor Loose Lay Carpet Mats Good Value

117 Heritage Rib®



Brown (BR)

115-1122111111





Green (GN)

109 Heritage Rib Lite®



Charcoal (CH)

Brown (BR)

136 Polynib®



Charcoal (CH)

Brown (BR)



Blue (BU)



Green (GN)

TIF. 76 90 20 01

These are economical yet highly effective entrance mat products. Durable fibres offer good scraping action, preventing moisture and grime from being walked into facilities.

Low profile allows foot, cart and wheelchair traffic to move easily over the mat. Vinyl backing is moisture resistant and slip resistant.

117 Heritage Rib®

Recommended use:

- Suitable for light to medium traffic conditions.
- For placement inside entrances of schools, offices, shops.

Specifications:

- Ribbed needle punched carpet consisting of anti-static 100% polypropylene fibres.
- 650 grams of fibres per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 7.5 mm.
- Weight: 3.1 kg per m².
- Fire rating: ASTM D2859 passes DOC-FF-1-70.

Recommended accessories:

083 Bevelled Nosing 2 mm

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 120 cm
- 90 cm x 150 cm
- 120 cm x 180 cm
- 120 cm x 240 cm

Full rolls:

• 120 cm x 20 meters

Custom lengths:

• 120 cm per linear meter

Colours:

- Charcoal (CH)
- Red (RB)
- Brown (BR)
- Green (GN)

Cleaning tip:

Vacuum clean.



Product Testing

Dust Control		
Crush Resistance		
Water Retention		

BETTER BEST

109 Heritage Rib Lite®

Recommended use:

- Suitable for light traffic conditions.
- For placement inside entrances of offices and retail shops.

Specifications:

- Ribbed needle punched carpet consisting of anti-static 100% polypropylene fibres.
- 400 grams of fibres per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on all sides.
- Overall thickness: 5.5 mm.
- Weight: 2.5 kg per m².

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 150 cm
- 120 cm x 180 cm

Colours:

- Charcoal (CH)
- Brown (BR)

Cleaning tip:

Vacuum clean.

136 Polynib®

Recommended use:

- Suitable for light to medium traffic conditions.
- For placement inside entrances of schools, offices, shops.

Specifications:

- Nibbed needle punched carpet consisting of anti-static 100% polypropylene fibres.
- 650 grams of fibres per m².
- Backing: black vinyl (DOP free).
- Vinyl borders: 2.5 cm on each side.
- Overall thickness: 7.5 mm.
- Weight: 3.1 kg per m².
- Fire rating: ASTM D2859 passes DOC-FF-1-70.

Recommended accessories:

083 Bevelled Nosing 2 mm

Stock sizes:

- 60 cm x 90 cm
- 90 cm x 150 cm
- 120 cm x 180 cm

Full rolls:

- 120 cm x 20 meters
- 200 cm x 20 meters

Custom lengths:

- 120 cm per linear meter
- 200 cm per linear meter

Colours:

- Charcoal (CH)
- Blue (BU)
- Brown (BR)
- Green (GN)

Cleaning tip:

• Vacuum clean.



Product Testing

	GOOD	BETTER	BEST
Dust Control			
Crush Resistance			
Water Retention			

Product Testing

GOOD BETTER BEST

Water Retention **Crush Resistanc Dust Control**

www.notr

Outdoor Scraper Mats

Outdoor entrance mats are the first line of defense against dirt. Over a 20 day period, 1000 people can walk in 9.6 kilograms (24 pounds) of dirt into a building (ISSA). Twelve times as much dirt is tracked in during wet weather conditions based on field tests conducted by BST Laboratory over a 11-month period. The main function of outdoor zone 1 mats is to remove the majority of dirt, mud and grime. Up to 40% of dirt and debris can be removed before entering the building.

Outdoor entrance mats are not absorbent and should be used in combination with an interior matting solution to continue the cleaning and drying of shoes to prevent slips and falls due to slippery floors.

Functionality

Outdoor mats are often constructed in an open, grid or grate design to maximize the flow of water, snow, ice, sand, mud and debris away from the surface to keep the walking area clear. Raised studs allow drainage of water under the mat in all directions. Classic rubber mats include the Oct-O-Mat[™] ring mat with its large octagonal ring and the Rubber Brush[™] fingertip mat. The weight of the rubber keeps the mat in place to prevent moving or shifting. Newer designs include the next generation Oct-O-Flex[™] with smaller octagonal drainage holes that are wheelchair friendly and EU compliant for public entrances.

Properly specifying entrance mats for outdoors is important. The type, quality and size of mat installed will vary according to the amount of foot traffic, the degree of exposure to the elements in a covered or open entrance, the type of dirt in the environment in which the building is situated, the weight and intensity of wheeled traffic, and many other factors. Since these mats are placed outdoors, the mats should be made from durable materials to be able to perform well in all weather conditions.



ErgoFloor A/S, Viborgvej 9, 7160 Tørring, Tlf. 76 90 20 01,



Notrax[®] heavy duty rubber compounds are naturally resilient to adapt to any outdoor surface and is extremely waterproof. Extruded PVC offers durable yet flexible material that is ultra violet resistant, oil resistant, and performs well in different climates.

Safety

Slippery entrances are the main safety concern. Due to large amounts of rain and snow in bad weather conditions, entrances can become soaked and slippery. In dry weather, entrance ways can accumulate dirt on the surface thereby increasing the risk of slips and falls. Outdoor rubber mats have moulded patterns or grooves to enhance the anti-slip properties even when wet.

Accessibility

Especially in public and commercial buildings, the entryway should be accessible for all. Architectural design guides specify that entrances must suit wheelchair users and accommodate people using mobility aids. Floors should have a wheelchair friendly surface, be trip free and remove water from wheels and shoes to reduce slippery surfaces within building. Entrance mats or recessed mat wells must be flush with the floor surface or any difference in height between the flooring surface and the mat should be limited to no more than $6 - 12 \text{ mm} (\frac{14}{7} \text{ to } \frac{17}{7})$. Mats should also allow easy passage for wheelchair users and for people using crutches. Preferably the recessed mat frame at main entrances should be as wide as the entrance.

Installation

Outdoor entrance mats can be installed in large entrances, wall-to-wall, or in recessed matwell frames. A recessed matwell frame is a sunken recess in standard entrances or under automatic doors or rotating doors. The matwell ensures the mat is flush with the floor, provides stability for the mat and helps to contain dirt and debris between cleanings. To ensure a perfect fit of Notrax[®] entrance mats in the recess, select the proper thickness to ensure the mat is flush with the floor and allows proper door closure. Notrax[®] Recess Fillers are available in various thicknesses to adjust the depth of an existing recess as needed.

Customization and Finishing

Notrax[®] outdoor rubber mats are available in a multitude of standard sizes for installation or loose lay. The new Master Flex[™] is available in a modular mat tile or per square meter in two thicknesses for installation or with corresponding bevels for loose lay. The extruded PVC mats are also available in custom lengths per linear meter. Other special shapes or forms, including circles, half-moons, and arches can be produced for custom installations.

Maintenance & Cleaning

As with indoor mats, outdoor entrance mats also perform optimally when regularly cleaned, though they do not need to adhere to the strict regimen of daily cleaning and maintenance. Outdoor mats can easily be cleaned by hosing the mat off with water on a regular basis. Also sweep or vacuum under the mat to remove any debris.

www.notrax.e

r A/S.



Introducing the revolutionary modular multi-zone entrance mat tile. The new Master Flex[™] design blends the functionalities of multizone entrance matting with the ease of on-site modular installation into an effective and ingenious matting solution. This full service matting system offers a smooth and harmonious transition from outdoor to indoor as well as from scraping to cleaning to drying.

Based on the unique design of the Oct-O-Flex[™], the outdoor rubber mat scrapes shoes to stop dirt, grit and grime from entering the building with small drainage holes that are EU compliant for public entrances. Plus its smooth surface makes it suitable for wheeled access (carts, wheelchairs, suitcases, etc.). The quality carpet mat inserts allow a large variety of colours and customization possibilities to easily coordinate with the aesthetics of the building and interior design while providing excellent absorption of moisture to dry shoes and prevent slips and falls.

The Master Flex[™] system offers all the benefits of a matting tile that is easily installed, rearranged or replaced. What makes it revolutionary is the interlocking system that creates a durable and seamless connection that can be effortlessly installed without glue. The 50 cm x 50 cm tiles cover sizeable areas easily and can be assembled on-site for installation in recessed matwell frames in large entrances. Made from a durable natural rubber compound that is inherently resilient, anti-slip and withstands the heaviest foot traffic. The mat has excellent adherence and adapts to any surface while the raised studs underneath allow water to drain through, keeping the surface clean and dry. Bevelled ramp accessories are available for loose lay installations to prevent tripping and facilitate access of wheelchairs and carts.

592 Master Flex[™] D12

The 592 Master Flex[™] D12 modular rubber mat tile has an open construction with small drainage holes and a depth of 12 mm.

Recommended use:

- Out- or indoor heavy foot traffic areas.
- For placement in interior or exterior recessed matwell frames.

Specifications:

- Natural rubber compound.
- Octagonal ring design with open construction.
- Suitable for use in extreme weather.
- Small holes diameter 14 mm, compliant with EU norm for public entrances.
- Overall thickness: 12 mm.
- Weight: 2.4 kg/tile.

592 Master Flex[™] D12 is available in a nitrile oil resistant or a fire retardant Bfl-S1 rubber compound on request.

Recommended accessories:

• Attachable safety ramps for loose lay installations

Stock sizes:

• 50 cm x 50 cm modular tiles

Custom sizes:

• Any size - on demand, calculated per m².

Cleaning tip:

• Hose off with water.

Product Testing





593 Master Flex[™] C12

The 593 Master Flex™ C12 matting system can be completely personalized with a large selection of carpet inserts in a variety of colours.

Recommended use:

- Out- or indoor heavy foot traffic areas.
- For placement in interior or exterior recessed matwell frames.

Specifications:

- Tile: Natural rubber compound.
- Octagonal ring design with open construction.
- Suitable for use in extreme weather.
- Small holes diameter 14 mm, compliant with EU norm for public entrances.
- Overall thickness: 12 mm.
- Weight: 2 kg/tile.

593 Master Flex[™] C12 is available in a nitrile oil resistant or a fire retardant Bfl-S1 rubber compound on request.

Recommended carpet inserts:

- 103 Master Trax Lite[™] carpet insert. See page 31.
- 380 Swisslon Classic XT carpet insert. See page 23.
- 388 Swisslon Uni™ carpet insert. See page 27.

Recommended accessories:

• Attachable safety ramps for loose lay installations

Stock sizes:

• 50 cm x 50 cm modular tiles

Custom sizes:

Any size – on demand, calculated per m².

Cleaning tip:

Vacuum clean.

Product Testing





Indoor / Outdoor Contract and Installation Next Generation

590 Master Flex™ D23



591 Master Flex™ C23

113 Master Trax™ carpet insert. See page 31. The classic rubber honeycomb mat has been transformed into a revolutionary modular multi-zone entrance mat tile. The new Master Flex™ D23 design blends the functionalities of multi-zone entrance matting with the ease of on-site modular installation into an effective and ingenious matting solution. This full service matting system offers a smooth and harmonious transition from outdoor to indoor as well as from scraping to cleaning to drying.

Based on the unique design of the traditional octagonal Oct-O-Mat[™], the outdoor rubber mat has large holes to scrape shoes to stop dirt, grit and grime from entering the building while allowing excellent drainage. The quality carpet mat inserts allow a large variety of colours and customization possibilities to easily coordinate with the aesthetics of the building and interior design while providing excellent absorption of moisture to dry shoes and prevent slips and falls.

The Master Flex[™] D23 system offers all the benefits of a matting tile that is easily installed, rearranged or replaced. What makes it revolutionary is the interlocking system that creates a durable and completely seamless connection that can be effortlessly installed. The 50 cm x 50 cm tiles cover sizeable areas easily and can be assembled on-site for installation in recessed matwell frames in large entrances. Bevelled ramp accessories are available for loose lay installations. Made from a durable natural rubber compound that is inherently resilient, anti-slip and withstands the heaviest foot traffic. The mat has excellent adherence and adapts to any surface while the raised studs underneath allow water to easily drain through, keeping the surface clean and dry.

590 Master Flex[™] D23

The 590 Master Flex[™] D23 modular rubber mat tile has an open octagonal construction with large drainage holes and a depth of 23 mm.

Recommended uses:

- Out- or indoor heavy foot traffic areas.
- For placement in interior or exterior recessed matwell frames.

Specifications:

- Natural rubber compound.
- Octagonal ring design with open construction.
- Suitable for use in extreme weather.
- Large holes for excellent drainage.
- Overall thickness: 23 mm.
- Weight: 3.7 kg/tile.

Recommended accessories:

• Attachable safety ramps for loose lay installations

Stock sizes:

• 50 cm x 50 cm modular tiles

Custom sizes:

• Any size - on demand, calculated per m².

Cleaning tip:

Hose off with water.

591 Master Flex[™] C23

The 591 Master Flex[™] C23 matting system can be completely personalized with the 113 Master Trax[™] carpet inserts in a variety of colours.

Recommended uses:

- Out- or indoor heavy foot traffic areas.
- For placement in interior or exterior recessed matwell frames depending on carpet insert.

Specifications:

- Tile: Natural rubber compound.
- Octagonal ring design with open construction.
- Suitable for use in extreme weather.
- Overall thickness: 23 mm.
- Weight: 3.9 kg/tile.

Recommended carpet inserts:

• 113 Master Trax[™] see page 31.

Recommended accessories:

Attachable safety ramps for loose lay installations

Stock sizes:

• 50 cm x 50 cm modular tiles

Custom sizes:

• Any size - on demand, calculated per m².

Cleaning tip:

• Vacuum clean.

Product Testing

Crush Resistance Dust Control GOOD BETTER BEST SUPERIOR



Product Testing

Water Retention	
Crush Resistance	
Dust Control	
GOOD BETTER BEST SUPERIOR	





599 Oct-0-Flex™

The Oct-O-Flex[™] outdoor rubber mat scrapes shoes to stop dirt, grit and grime from entering the building.

Its unique design of small drainage holes are EU compliant for public entrances and its smooth surface makes it the ideal mat for wheeled access (carts, wheelchairs, suitcases, etc.).

Made from durable rubber compounds that withstand the heaviest of foot traffic, Oct-O-Flex[™] mats are easy to clean and practically weather proof. The mat has excellent adherence and adapts to any surface while the raised knobs underneath allow water to easily drain through, keeping the surface clean and dry.

Recommended use:

- Out- or indoor heavy foot traffic areas.
- For placement in interior or exterior recessed matwell frame.

Specifications:

- Natural rubber compound.
- Octagonal ring design with open construction.
- Suitable for use in extreme weather.
- Small holes diameter 14 mm, compliant with EU norm for public entrances.
- Overall thickness: 12 mm.
- Weight: 9.8 kg/m².

599 Oct-O-Flex™ is available in a nitrile oil resistant or fire retardant compound on request.

Recommended accessories::

Connectors to cover larger areas.

Stock sizes:

- 75 cm x 100 cm
- 100 cm x 150 cm

Custom sizes:

Any size – on demand, calculated per m².

Cleaning tip:

Hose off with water.



Product Testing

Crush Resistant
Dust Control
GOOD BETTER BEST





539 Gripwalker

The distinctive waved design of the Gripwalker[™] matting creates a slip-resistant walking surface and is EU compliant for public entrances and its smooth surface makes it the ideal mat for wheeled access (carts, wheelchairs, suitcases, etc.). The open grid of extruded vinyl scrapes dirt and moisture off shoes, allowing it to fall in to the mat and not be tracked in to the building.

Heavy duty yet flexible material is durable, ultra violet resistant, performs well in different climates and adapts to any surface. Suitable for the heaviest traffic conditions. Free of DOP, free of DMF, free of ozone depleting substances, free of silicone and free of heavy metals.

Gripwalker[™] is oil resistant making it ideal for placement at petrol stations or entrances with oil exposure.

Recommended use:

- Out- or indoor heavy foot traffic areas.
- For placement in interior or exterior recessed matwell frame.
- For placement as loose lay mat with recommended mounted bevels.

Specifications:

- Durable extruded vinyl.
- Diagonal waved design with open construction.
- UV resistant and performs well in different climates.
- Small holes compliant with EU norm for public entrances.
- Overall Thickness: 11 mm.
- Weight: 8.5 kg/m².

Recommended accessories:

325 Bevelled Nosing 11 mm

Full rolls:

- 91 cm x 12.2 m
- 122 cm x 12.2 m

Custom lengths:

- 91 cm x 12.2 m
- 122 cm x 12.2 m

Cleaning tip:

• Hose off with water.



Product Testing





www.notrax.eu

ErgoFloor A/S,

Viborgvej 9,

7160 Tørring, Tlf. 76 90 20 01,

www.ergofloor.dk

Outdoor Contract and Installation Rubber Classics

564 Oct-O-Mat™

The traditional octagonal Oct-O-Mat[™] outdoor rubber mat is known for its large holes that provide traction and excellent drainage in extreme weather conditions and scrape shoes to stop dirt, grit and grime from entering the building.

Made from a durable rubber compound, these heavy duty mats withstand intense foot traffic, are easy to clean and practically weather proof.

The resilient rubber offers excellent adherence and adapts to any surface while the raised knobs underneath allow water to easily flow away in all directions, keeping the surface clear.

Recommended use:

- Outdoor Heavy foot traffic areas.
- For placement in interior or exterior recessed matwell frame.

Specifications:

- Raised knobs underneath allow excellent drainage, leaving a clean and dry surface.
- Heavy weight assures non-shifting.
- Overall thickness: 23 mm.
- Weight: 13.3 kg per m².

564 Oct-O-Mat[™] is available in a nitrile oil resistant or fire retardant compound on request.

Accessories:

- Connectors
- Insert brushes

Stock sizes:

- 60 cm x 80 cm
- 50 cm x 100 cm
- 75 cm x 100 cm
- 80 cm x 120 cm
- 100 cm x 150 cm

Custom sizes:

• Any size - on demand, calculated per m².

Cleaning tip:

Hose off with water.



Product Testing

Crush Resistant

GOOD BETTER BEST SUPERIOR





Outdoor Contract and Installation Spaghetti

273 CiTi™ 16 mm backed 274 CiTi™ 14 mm unbacked





Anthracite (CH)

Green (GN)





Grey (GY)



Black (BL)

Red (RD)







Navy Blue (DB)







Grey (GY)

68

Anthracite (CH)

Blue (BU)

Green (GN)

Gold (YL)



Brown (BR)







271 CiTi™ 10 mm backed

www.notrax.eu

Vinyl loops scrape dirt and moisture off shoes to trap dirt in the mat and prevent it from being tracked into the building. Durable flexible material is ultra violet resistant, performs well in different climates and adapts to any surface. Does not absorb water. Choice of backed or unbacked construction. Backed version ensures minimum movement and keeps debris away from the floor in indoor areas. Backing is a non-porous vinyl layer which is cured into the upper web for maximum non-delaminating durability. Unbacked version allows water to flow through for maximum drainage. Slip resistance tested R11 according to DIN51130 and BRG181. Free of DOP, free of DMF, free of ozone depleting substances, free of silicone and free of heavy metals.

273 CiTi™ 16 mm backed

Recommended use:

- Suitable for heavy traffic conditions.
- For placement in interior facility entrances or recessed wells.
- For loose lay placement with mounted bevels.

Specifications:

- Thick coils (strand diameter 1 mm) of extruded from 100% PVC.
- Backing: vinyl (DOP free).
- Overall thickness: 16 mm.
- Weight: 5 kg per m².
- Fire rating: EN 13501 Bfl-S1.

Recommended accessories:

• 325 Bevelled Nosing 11 mm

Full rolls:

- 120 cm x 18 meter
- 120 cm x 6 meter

Custom lengths:

120 cm per linear meter

Colours:

- Anthracite (CH)
- Green (GN)
- Brown (BR)
- Grey (GY)

Cleaning tip:

Vacuum clean or wash off with a hose.

274 CiTi™ 14 mm unbacked

Recommended use:

- Suitable for heavy traffic conditions. · For placement in exterior facility entrances or
- recessed wells.
- For loose lay placement with mounted bevels.

Specifications:

- Thick coils (strand diameter 1 mm) of extruded from 100% PVC.
- Overall thickness: 14 mm.
- Weight: 4.5 kg per m².
- FFire rating: EN 13501 Bfl-S1.

Recommended accessories:

• 325 Bevelled Nosing 11 mm

Full rolls:

- 120 cm x 18 meter
- 120 cm x 6 meter

Custom lengths:

120 cm per linear meter

Colours:

- Anthracite (CH)
- Navy Blue (DB) Green (GN)
- Brown (BR)
- Grey (GY)
- Vacuum clean or wash off with a hose.

For placement in interior facility entrances or recessed wells.

conditions.

271 CiTi™

10 mm backed

Recommended use:

For loose lay placement with mounted bevels.

• Suitable for light to medium traffic

Specifications:

- Fine coils (strand diameter 0.35 mm) of extruded from 100% PVC.
- Backing: vinyl (DOP free).
- Overall thickness: 10 mm.
- Weight: 3.8 kg per m².
- Fire rating: EN 13501 Bfl-S1.

Recommended accessories:

084 Bevelled Nosing 4 mm

Full rolls:

- 120 cm x 18 meter
- 120 cm x 6 meter

Custom lengths:

120 cm per linear meter

Colours:

- Gold (YL)
- Brown (BR)
- Green (GN)
- Anthracite (CH)

Blue (BU)

Grey (GY)

Vacuum clean or wash off with a hose.

10 mm
5. K. X
Product Testing
Crush Resistant
Dust Control
GOOD BETTER BEST





Product Testing

Crush Resistant			
Dust Control			
	GOOD	BETTER	BES



GOOD BETTER BEST

7160 Tørring,

Tlf. 76 90 20 01, www.ergofloor.dk

- **Cleaning tip:**



ErgoFloor A/S, Viborgvej 9

• Black (BL)

Red (RD)

Navy Blue (DB)

Cleaning tip:

14 mm

Dust Control



599B Oct-O-Flex Bevelled™

The Oct-O-Flex Bevelled[™] outdoor rubber mat is known for its octagonal ring design with small drainage holes and smooth surface making this next generation mat EU compliant for public entrances makes and the ideal mat for wheeled access (carts, wheelchairs, suitcases, etc.). Moulded edges on all four sides are bevelled to allow easy access onto the mat and prevent tripping.

Made from a durable rubber compound that withstands the heaviest of foot traffic, Oct-O-Flex[™] mats are easy to clean and practically weather proof.

The Oct-O-Flex Bevelled[™] has excellent adherence and adapt to any surface while the raised knobs underneath allow water to easily drain through, keeping the surface clean and dry.

Recommended use:

- Suitable for heavy foot traffic areas.
- For loose lay placement indoors or outdoors.

Specifications:

- Natural rubber compound.
- Bevelled rubber borders on all four sides.
- Octagonal ring design with open construction.
- Suitable for use in extreme weather.
- Small holes diameter 14 mm, compliant with EU norm for public entrances.
- Overall thickness: 12 mm.
- Weight: 9.8 kg/m².

599B Oct-O-Flex[™] Bevelled is available in a nitrile oil resistant or fire retardant compound on request.

Stock sizes:

- 70 cm x 90 cm
- 90 cm x 150 cm
- 120 cm x 180 cm

Cleaning tip:

• Hose off with water.



Product Testing





7160 Tørring, Tlf. 76 90 20 01,

www.ergofloor.dk

Outdoor Loose Lay Next Generation

-72 ErgeFloor A/S, Viborgvej 9, 7160 Tørring, Tlf. 76 90 20 01, www.ergofloo

ww.notrax.eu

539B Gripwalker Edge™

The Gripwalker Edge[™] grid matting is constructed of durable extruded vinyl in a waved designed to scrape dirt and moisture off shoes, allowing it to fall in to the mat and not be tracked in to the building.

The small drainage holes and smooth surface making this next generation mat EU compliant for public entrances makes and the ideal mat for wheeled access (carts, wheelchairs, suitcases, etc.). Pressed edges on all four sides allow easy access onto the mat and prevent tripping.

Durable flexible material is ultra violet resistant, performs well in different climates and adapts to any surface. Free of DOP, free of DMF, free of ozone depleting substances, free of silicone and free of heavy metals.

Gripwalker Edge™ is oil resistant making it ideal for placement at petrol stations or entrances with oil exposure.

Recommended use:

- Suitable for heavy foot traffic areas.
- For loose lay placement indoors or outdoors.

Specifications:

- Durable extruded vinyl.
- Bevelled pressed borders on all four sides.
- Diagonal waved design with open construction.
- UV resistant and performs well in different climates.
- Small holes compliant with EU norm for public entrances.
- Overall thickness: 11 mm.
 Weight: 8.5 kg/m².
- Stock sizes:
- 60 cm x 90 cm
- 90 cm x 150 cm

Cleaning tip:

• Hose off with water.



Product Testing





ErgoFloor A/S,

7160 Tørring,

Viborgvej 9,

Tlf. 76 90 20 01,



Classic outdoor scraper mats stop dirt, grit and grime from entering the building. Made from a durable rubber compound, these mats withstand the heaviest of foot traffic, are easy to clean and practically weather proof. These mats have excellent adherence and adapt to any surface. Bevelled edges improve safety and allow easy cart access.

345 Rubber Brush[™]

Thousands of flexible fingers provide automatic shoe cleaning action when foot pressure is applied. Moulded rubber backing has non-shifting suction cup design underneath.

Recommended use:

- Suitable for heavy foot traffic areas.
- For loose lay placement indoors or outdoors.

Specifications:

- Natural rubber compound.
- Bevelled rubber borders on all four sides.
- Flexible fingers moulded with rubber backing.
- Suitable for use in extreme weather.
- Overall thickness: 16 mm.
- Weight: 13.6 kg per m².

Stock sizes:

- 60 cm x 80 cm
- 80 cm x 100 cm
- 90 cm x 150 cm
- 90 cm x 180 cm

Cleaning tip:

• Hose off with water.

565 Soil Guard™

High traction rubber mat with a raised striated design to provide traction. The gripper backing prevents the mat from shifting.

Recommended use:

- Suitable for heavy foot traffic areas.
- For loose lay placement indoors or outdoors.

Specifications:

- Natural rubber compound.
- Bevelled rubber borders on all four sides.
- Raised striated design with rubber backing.
- Suitable for use in extreme weather.
- Overall thickness: 7 mm.
- Weight: 6.7 kg per m².

Stock sizes:

• 90 cm x 150 cm

Cleaning tip:

Hose off with water.



www.notrax.eu

ErgoFloor A/S,

Viborgvej 9, 7160 Tørring,

rring, Tlf. 76 90 20 01,

1, www.ergofloor.dk

Outdoor Loose Lay Spaghetti

267 Wayfarer® 16 mm backed



Charcoal (GY)



Navy Blue (NB)



Red (RD)

266 Wayfarer[®] 14 mm unbacked



Charcoal (GY)



Navy Blue (NB)



Red (RD)

265 Wayfarer[®] 10 mm backed



Charcoal (GY)



www.notrax.eu

Loose lay CiTi[™] mats with pressed bevelled borders on all four sides. Vinyl loops scrape dirt and moisture off shoes and trap it in the mat which prevents dirt from being tracked into the building. Made from a durable flexible material that is ultra violet resistant, the Wayfarer[®] mat performs well in different climates and adapts to any surface. Spaghetti mats do not absorb water. The Wayfarer[®] line offers a choice of backed versions that ensures minimum movement or an unbacked version that allows water to flow through for maximum drainage. Slip resistance tested R11 according to DIN51130 and BRG181. Free of DOP, free of DMF, free of ozone depleting substances, free of silicone and free of heavy metals.

267 Wayfarer[®] 16 mm backed

Recommended use:

- Suitable for heavy foot traffic areas.
- For loose lay placement indoors or outdoors.

Specifications:

- Thick coils (strand diameter 1 mm) of extruded from 100% PVC.
- Backing: vinyl (DOP free).
- Pressed borders on all sides.
- Overall thickness: 16 mm.
- Weight: 6 kg per m².
- Fire rating: EN 13501-1 Bfl-S1.

Stock sizes:

- 90 cm x 150 cm
- 120 cm x 180 cm

Colours:

- Charcoal (GY)
- Red (RD)
- Navy Blue (NB)

Cleaning tip:

Vacuum clean or wash off with a hose.

266 Wayfarer[®] 14 mm unbacked

Recommended use:

- Suitable for heavy foot traffic areas.
- For loose lay placement indoors or outdoors.

Specifications:

- Thick coils (strand diameter 1 mm) of extruded from 100% PVC.
- · Pressed borders on all sides.
- Overall thickness: 14 mm.
- Weight: 4.8 kg per m².
- Fire rating: EN 13501-1 Bfl-S1.

Stock sizes:

- 90 cm x 150 cm
- 120 cm x 180 cm

Colours:

- Charcoal (GY)
- Red (RD)
- Navy Blue (NB)

Cleaning tip:

• Vacuum clean or wash off with a hose.

265 Wayfarer[®] 10 mm backed

Recommended use:

- Suitable for light to medium foot traffic areas.
- For loose lay placement indoors or outdoors.

Specifications:

- Fine coils (strand diameter 0.35 mm) of extruded from 100% PVC.
- Backing: vinyl (DOP free).
- Pressed borders on all sides.
- Overall thickness: 10 mm.
- Weight: 3 kg per m².
- Fire rating: EN 13501-1 Bfl-S1.

Stock sizes:

- 90 cm x 150 cm
- 120 cm x 180 cm

Colours:

Charcoal (GY)

Cleaning tip:

• Vacuum clean or wash off with a hose.



7160 Tørring,

Viborgvej 9,

Tlf. 76 90 20 01, www.ergofloor.dk

Accessories

Bevelled Nosing

- Easy to apply nosing gives on-site cut mats a factory-finished look.
- Apply adhesive to thin side of nosing and attach to back of mat.
- Three sizes available for best application with different product thicknesses.

Recommended uses:

• Use on custom cut borders to produce a safe & clean bevelled edge.

083 Bevelled Nosing 2 mm

Recommended for articles:

015, 018, 117, 118, 123, 130, 136, 138, 145, 175, 178, 185, 193, 198, 238, 380, 387, 388, 389

Available sizes:

- Full rolls: 45.7 m
- Per linear meter
- Per linear meter mounted

084 Bevelled Nosing 4 mm

Recommended for articles:

• 103, 271

Available sizes:

- Full rolls: 30.4 m
- Per linear meter
- Per linear meter mounted

325 Bevelled Nosing 11 mm

Recommended for articles:

• 016, 113, 196, 273, 274, 539

Available sizes:

- Full rolls: 18.3 m
- Per linear meter
- Per linear meter mounted



086 Notrax[®] Super Glue

- Used for application of bevelled nosing, Mat Seaming Tape and Velcro[®] Carpet Anchors.
- Plastic bottle of 50 g.

113K Master Trax™ Stitched Bevels

Recommended for articles: • 113

Available sizes:

• Per linear meter mounted and stitched





092 Mat Seaming Tape

- Black vinyl seaming tape with patterned gluing surface for a secure bond.
- Embossed protective paper ensures gluing surface remains clean.
- Apply Notrax[®] Glue to patterned side of seaming tape.
- It is recommended to seam mats from the same roll in the same direction of the carpet grain for an undetectable seam.

Recommended uses:

 For width wise or lengthwise seaming of vinyl backed carpet matting.

Available sizes:

- Full rolls: 5 cm x 45.7 m
- Per linear meter
- Per linear meter mounted



ErgoFloor A/S,





085 Velcro® Carpet Anchor

• Easy to apply strips anchor mats to loop pile carpet.

Recommended uses:

• To place indoor entrance mats on carpet surfaces.

Full rolls:

• 2.54 cm x 22.8 m

Custom Lengths:

• Per linear meter

Recess Fillers

- Used to adjust the depth of an existing recess or matwell frame.
- To ensure a perfect fit in the recess, select the proper thickness so the mat is flush with the floor and allows proper door closure.
- Three thicknesses available.

093 Recess Fillers 6 mm:

- Full rolls: 10 m
- Per linear meter



094 Recess Fillers 8 mm:

- Full rolls: 8 m
- Per linear meter



095 Recess Fillers 10 mm:

- Full rolls: 6 m
- Per linear meter



090 Mat Hold

- · Needle punched polyester mesh pad adheres to floor and back of mat.
- Reversible material. White side down is suitable for use on carpet. Grey side down is suitable for use on hard floors.
 - Ensures an almost immobile mat yet does not transfer adhesive to carpet or tile.
- Recommended application is to place pad approximately 10 cm from edge of mat ٠ bottom surface.

Recommended uses:

For placement under loose lay mats to prevent indoor carpet mats from shifting.

Full rolls:

- 60 cm wide
- 91 cm wide

Custom Lengths:

Per linear meter in 60 cm or 91 cm widths



on carpet

Viborgvej 9,

7160 Tørring,

www.notrax.eu

ErgoFloor A/S,

Tlf. 76 90 20 01, www.ergofloor.dk