RAVAS GO

SPECIAL PROMOTION LIMITED EDITION











RAVAS GO

FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Automatic tare over the full scale. Pre-set tare maximum first range (200 kg)
- Totalling with sequence number
- Error messages in display
- Automatic switch-off after 30 minutes of non-use
- Low battery warning in display

STANDARD SPECIFICATIONS

STANDARD SPECIFICATIONS				
٠	Weighing capacity	2,000 kg		
•	Graduation	multirange: 0 - 200 kg: graduation 0.2 kg 200 - 500 kg: graduation 0.5 kg 500 - 2,000 kg: graduation 1 kg		
•	Max. tolerance	0.1% of the load lifted		
•	Display	LCD, digit height 18 mm		
•	Keypad	3 function keys, on/off key		
٠	Protection class	load cells IP67, indicator IP65		
•	Battery	12Vdc/1.2Ah, exchangeable; battery charger included		
•	Battery life	35 hours, low battery indication in display		
	Charger	230V/12Vdc - 300 mA		

Charger 230V/12Vdc - 300 mACharging time approximately 6 hours

Steering wheels


Loading wheels polyurethane, tandem

Pump quick liftOwn weight 120 kg

Colour red (RAL 3000), epoxy painted

rubber

DIMENSIONS IN MM



Α	Fork length	1150
В	Fork width	170
С	Minimum fork height	90
	Space underneath fork	22
D	Maximum fork height	180
	Lifting height	90
Ε	Width over forks	540
F	Height to top indicator	800
	Tolerance +/- 3 mm	

Standard



OPTIONS*

Extra exchangeable battery pack

RAVAS Europe B.V.

Veilingweg 17, 5301 KM Zaltbommel, The Netherlands T: +31 418 515220 E: salesoffice@ravas.com

WWW.RAVAS.COM

