


C-FRAME PRESS

# CFP

30 Ton

60 Ton

100 Ton



Stroke Adjustment



Manometre  
Manometer



Pressure Adjustment  
Valve



## GENERAL FEATURES

- Easy to operate
- Steel construction welded frame
- Ability to stop any position
- Manometer
- Relief valve for overloading
- Stepless stroke adjustment
- T-slot top and bottom table
- Two guide piston both side
- Safety barrier
- Two hand control




Two Hand Control



Light Curtain

OPTIONAL





Two Hand Control and Foot Pedal




Light Curtain



Press Brake Tooling



		30	60	100	
	<b>CFP</b>				
	Press Power	kN	300	600	1000
	Stroke	mm	400	400	400
	Max. Working Pressure	bar	244	236	263
	Advance Speed	mm/sec	28	30	23
	Working Speed	mm/sec	5.5	6	5.5
	Return Speed	mm/sec	23	47	27
	Gap Depth	mm	880	880	650
	Throat Depth	mm	650	650	420
	Working Length	mm	700	700	800
	Bottom Table Dimension	mm	600x700x45	600x700x45	530x800x75
	Top Table Dimension	mm	350x700x45	350x700x45	350x800x45
	Hole Diameter	mm	100	100	100
	Motor Power	kW	3	7.5	11
	Oil Tank	lt	90	90	130
	L Length	mm	1150	1230	1250
	W Width	mm	1550	1570	1570
	H Height	mm	2200	2250	2250
	Weight	kg	2620	3520	5400

