



GENERALE DIMENSIONS

Boom dimension	4800 mm			
Arm dimension	2000 mm	*2300 mm	2600 mm	2900 mm
A - Overall length	7710 mm	7710 mm	7680 mm	7650 mm
B - Overall height (to top of boom)	2700 mm	2810 mm	2940 mm	3030 mm
C - Overall width (of lower structure)	*2490 / 2590 / 2690 mm			
D - Idler distance	3035 mm			
E - Tall swing radius	1500 mm			
E' - Tall swing distance	1520 mm			
F - Upperstructure ground clearance	940 mm			
G - Crawler height	830 mm			
H - Min. Ground clearance	430 mm			
I - Track gauge	1990 mm			
J - Shoe width	*500 / 600 / 700 mm			
K - Overall length of crawler	3780 mm			
L - Length over ground	5190 mm	5040 mm	4910 mm	4710 mm
M - Overall height (to top of cab)	2960 mm			
N - Upperstructure width	2500 mm			

* Standard

WORKING DIMENSIONS

Boom dimension	4800 mm			
Arm dimension	2000 mm	*2300 mm	2600 mm	2900 mm
S - Max. digging reach	8140 mm	8420 mm	8730 mm	8750 mm
T - Max. digging reach at ground level	7980 mm	8270 mm	8580 mm	8600 mm
U - Max. digging depth	4970 mm	5270 mm	5580 mm	5910 mm
V - Max. digging height	9400 mm	9670 mm	9960 mm	9740 mm
W - Max. dumping height	6900 mm	7170 mm	7460 mm	7240 mm
W' - Min. dumping height	3420 mm	3170 mm	2920 mm	2180 mm
X - Max. vertical digging depth	3900 mm	4230 mm	4570 mm	4950 mm
Y - Min. swing radius	1830 mm	1990 mm	2160 mm	2160 mm
Z - Max. digging depth	4840 mm	5150 mm	5460 mm	5720 mm

DIGGING PERFORMANCE

Standard Bucket Capacity (SAE)	0,6 m ³			
Bucket Digging Force (Power Boost) ISO	9100 (10000) kgf			
Arm Crowd Force (Power Boost) ISO	7500 (8200) kgf	6800 (7500) kgf	6200 (6800) kgf	5700 (6300) kgf

HIDROMEK®

FACTORY - HEAD OFFICE

Ahi Evran OSB Mahallesi Osmanlı Caddesi No:1 06935 Sincan / ANKARA / TURKEY
Tel: (+90) 312 267 12 60 Fax: (+90) 312 267 12 39
www.hidromek.com

Notice:
Hidromek has the right to modify the specifications and design of the model indicated on this brochure without prior notice.