

your global specialist

Detailed information

More than food safety.

Speciality lubricants for the beverage industry





Combine food safety and production reliability	3
Filling, capping, seaming and labelling machines	4
Seals, Conveyor system and Roller bearings	6
Enclosed gears	8
Shrink wrap, Vacuum pumps, Screw threads and General maintenance	10
Compressors	12
The right lubricant at the right place at the right time	14

Combine food safety and production reliability

There are three aspects which are particularly important for you as a beverage production specialist: consumer protection through food safety, reliable manufacturing processes and reduced operational and maintenance cost.

During the peak season of production, lubrication failures can prove very expensive for you. Just imagine the loss of production due to a lubrication failure in glue roller bearings in the labeling machine or problems with EPDM seals in the mixing area of the filling machine. A wrong lubricant used in the centralised lubrication system in the blow moulding machine could bring production to a complete halt.

Avoiding contamination is one of the biggest challenges in the beverage industry. In that regard, lubricants, which are considered as chemical contaminants, need some special attention. The use of industrial lubricants in critical control points could lead to food safety issues and product recalls.

H1 lubricants across the line

Klüber's synthetic high-performance lubricants with H1 registration help you obtain these objectives, as they are capable of a lot more than friction reduction, lowering operating temperatures and increasing components' service life. Depending on your application conditions, you can select lubricants meeting a wide range of requirements from hygienic filling in aseptic areas to high resistance to water washdown from this brochure.

We offer you a comprehensive range of valuable H1-registered speciality lubricants for all lubrication points in your plant, across the entire production line. These H1 lubricants are designed for incidental, technically unavoidable contact with the food product.

Additionally, Klüber H1 Lubricants are produced according to the highest standards of ISO 21469 to ensure hygienic products. ISO 21469 standard defines hygiene requirements for the formulation, manufacture and use of lubricants that could have unintentional product contact. To obtain the certification, lubricant manufacturers must develop a hygiene strategy taking all chemical, physical and biological hazards of lubricant application into account.

We also offer more than 100 different lubricants with halal and kosher certification that are H1-registered, enabling Klüber to support compliance with these requirements across the complete production line.

Tested quality for the beverage industry

The lubricants we developed especially for the production of beverages are the result of our long-standing and close cooperation with both machine manufacturers and end-users in the beverage industry. Designers of machines and installations can build on this experience right from the very start of machine development. Klüber Lubrication is already a member of EHEDG, an organisation which works with machine manufacturers to ensure food safety right from the design stage. Beverage manufacturers can trust in our experience on every step of the beverage production process. Hence, our lubricants are a valuable contribution towards food safety.

The combination of personal consultation and a comprehensive lubricant range is our particular strength.

KlüberEfficiencySupport – beyond food safety...

Klüber Lubrication is more than just a manufacturer of speciality lubricants. As a partner for our customers we offer you the best package of finely matched lubricants and competent services fitting to your individual requirements going beyond just lubrication needs.

In case environmental goals play an important role in your company, our KlüberEfficiencySupport solutions aimed at saving energy, water and resources help you to identify and realise unused potentials by providing a remarkable level of plant transparency.

If your company uses maintenance programs like TPM, our solutions to increase the efficiency in your maintenance and improving your equipment efficiency support most of them in a unique way. These are just two examples of topics covered by KlüberEfficiencySupport

In short: we work in close cooperation with you to improve lubrication processes in your plant systematically, allowing you to benefit from your machines and your staff's know-how to the maximum. Production volumes can be increased while simultaneously reducing operating cost and avoiding wastage of natural resources. Please contact our KlüberEfficiencySupport specialists, who will introduce you to interesting and often surprising solutions to save costs.

Filling, capping, seaming and labelling machines

Application	Application points / machine components	Klüber speciality lubricant	NLGI grade	Base oil	Thickener
Filling, capping, seaming and labelling machines	Lifting rods and guides in filling machines	PARALIQ P40 Spray	Not applicable	Paraffinic mineral oil ¹⁾	None
		Klüberfood 4 NH1 100	Not applicable	Synthetic hydrocarbon oil	None
		Klüberfood NH1 94-6000	000	Synthetic hydrocarbon oil	Calcium complex soap
Open drive gears in filling machines		Klüberfood NH1 14-222 Spray	2	Synthetic hydrocarbon oil ¹⁾	Aluminium complex soap ¹⁾
		Klüberplex AG 11-462	2	Mineral base oil	Aluminium complex soap ¹⁾
Can seamers: Roller bearings		PARALIQ GA 351	1	Paraffinic mineral oil / synthetic hydrocarbon oil	Aluminium complex soap ¹⁾
Can seamers with oil circulating system		Klüberfood NH1 M 4-100 or 150	Not applicable	Synthetic hydrocarbon oil	None
Centralised grease systems in filling machines		Klübersynth UH1 14-151	1	Synthetic hydrocarbon oil	Aluminium complex soap
Capper bearings and sliding shafts		PARALIQ GA 343	2	Paraffinic mineral oil / synthetic hydrocarbon oil	Aluminium complex soap
Capping head sliding surfaces		PARALIQ 91 Spray	Not applicable	Ester oil	None
High-temperature bearings in labelling machines		BARRIERTA L55/2	2	PFPE	PTFE

¹⁾ of the active component



	Upper service temperature approx.	Lower service temperature approx.	Application notes and benefits
	60 ¹⁾ [°C] 140 [°F]	-10 [°C] 14 [°F]	- Light oil to reduce friction and optimise sliding actions, e.g. in capping heads
	135 [°C] 275 [°F]	-35 [°C] -31 [°F]	- Synthetic base oil with low volatility ensuring minimum carry-over, minimising contamination risks - ISO 21469 certified
	120 [°C] 248 [°F]	-45 [°C] -49 [°F]	- Good corrosion protection and good pumpability in central lubrication systems - Reduced wear and extended maintenance intervals due to good load-carrying capacity - Good low-temperature characteristics enable use in refrigerated environments - ISO 21469 certified
	120 ¹⁾ [°C] 248 [°F]	-25 [°C] -13 [°F]	- Sprayable grease for ease of application on open gears & slideways - Good wear and corrosion protection. - Good hot and cold water resistance
	150 ¹⁾ [°C] 302 [°F]	-10 [°C] -14 [°F]	- Very good adhesion even at low temperatures - Improved component performance - Less wear due to selected solid lubricants and additives - Very good corrosion protection also when exposed to saltwater
	110 ¹⁾ [°C] 230 [°F]	-40 [°C] -22 [°F]	- Applicable through central lubrication systems - Good water resistance - Good wear and corrosion protection - ISO 21469 certified
	135 [°C] 275 [°F]	-30 [°C] -22 [°F]	- Synthetic base oil with low volatility ensuring minimum carry-over, minimising contamination risks - ISO 21469 certified
	120 [°C] 248 [°F]	-45 [°C] -49 [°F]	- Applicable through central lubrication systems - Suitable for the lubrication of gears, lifting cylinders, guide bars, cam plates - Good water resistance - Good wear and corrosion protection - ISO 21469 certified
	120 [°C] 248 [°F]	-30 [°C] -22 [°F]	- Good resistance against hot and cold water - Good corrosion protection - Recommended by leading capper manufacturers - ISO 21469 certified
	Not applicable	Not applicable	- Neutral in taste and odour - NSF H1 and 3 H registered supporting process reliability - ISO 21469 certified
	260 [°C] 500 [°F]	-40 [°C] -40 [°F]	- Good wear protection and thermal stability for extended relubrication intervals - Please note that friction points should be cleaned before initial lubrication - ISO 21469 certified

Seals, Conveyor system and Roller bearings

Application	Application points / machine components	Klüber speciality lubricant	NLGI grade	Base oil	Thickener
Seals	Seals and filling taps (EPDM)	PARALIQ GTE 703	3	Silicone oil	PTFE
	Seals and filling taps (EPDM) for aseptic cold filling	Klüberfood NH1 87-703 Hyg	3	Silicone oil	PTFE
	Seals and filling taps (non EPDM)	Klübersynth UH1 64-2403	3	Synthetic hydrocarbon oil	Silicate
Conveyor systems	Palletisers, drives and conveyor chains	Klüberoil 4 UH1-1500 N Spray	Not applicable	Synthetic hydrocarbon oil / ester ¹⁾	None
	Conveyor bearings	Klübersynth UH1 14-222	2	Synthetic hydrocarbon oil	Aluminium complex soap
	Plastic slatted conveyors	Klüberfood NH1 C 4-58	Not applicable	Synthetic hydrocarbon oil	Not applicable
Roller bearings	High performance greases	Klüberfood NH1 94-402	2	Synthetic hydrocarbon oil	Calcium complex soap
		Klüberfood NH1 94-301	1	Synthetic hydrocarbon oil	Calcium complex soap

¹⁾ of the active component

²⁾ Due to the many different elastomer and plastics compositions we recommend checking compatibility prior to series application.



	Upper service temperature approx.	Lower service temperature approx.	Application notes and benefits
	150 [°C] 302 [°F]	-50 [°C] -58 [°F]	<ul style="list-style-type: none"> - For use in low-loaded bearings and EPDM²⁾ seals in filling machines without aseptic cold filling - ISO 21469 certified
	150 [°C] 302 [°F]	-45 [°C] -49 [°F]	<ul style="list-style-type: none"> - For use in low-loaded bearings and EPDM²⁾ seals in aseptic cold filling machines to improve hygiene levels - The lubricant contains an antimicrobial additive allowing extended maintenance intervals. - ISO 21469 certified
	140 [°C] 284 [°F]	-10 [°C] 14 [°F]	<ul style="list-style-type: none"> - Sealing grease suitable for beer taps, barrel fillers, filters, stuffing boxes, rubber diaphragms and seals²⁾ - ISO 21469 certified
	120 ¹⁾ [°C] 248 [°F]	-20 [°C] -4 [°F]	<ul style="list-style-type: none"> - Drive and conveyor chain lubrication where maximum adhesion is required in for example high speed applications - Good wear protection to optimise chain life - Low foaming of spray to ensure maximum penetration to main friction points of the chain - ISO 21469 certified
	120 [°C] 248 [°F]	-25 [°C] -13 [°F]	<ul style="list-style-type: none"> - Good wear protection - Good resistance against hot and cold water - High corrosion protection - ISO 21469 certified
	135 [°C] 275 [°F]	-40 [°C] -40 [°F]	<ul style="list-style-type: none"> - For plastic conveyor systems - Minimal lubrication clear reduction of bacteriological contamination and corrosion and reduction of waste water - Reduces risk of bottles toppling over and removes floor slip hazard
	160 [°C] 320 [°F]	-30 [°C] -22 [°F]	<ul style="list-style-type: none"> - Increased component availability and extended maintenance intervals owing to good load-carrying capacity and good corrosion protection
	120 [°C] 248 [°F]	-35 [°C] -31 [°F]	<ul style="list-style-type: none"> - Increased component availability and extended maintenance intervals owing to good load-carrying capacity and good corrosion protection - ISO 21469 certified

Enclosed gears

Application	Type of lubricant	Klüber speciality lubricant	NLGI grade	Base oil	Thickener
Enclosed gears (spur-, bevel- and worm gears)	High performance gear oils	Klüberoil 4 UH1 – 100 N...1500 N-series ¹⁾ Available in ISO VG 32, 46, 68, 100, 220, 320, 460, 680, 1500 viscosity grades The selection of the viscosity grade depends on the gear type and the application	Not applicable	Synthetic hydrocar- bon oil / ester	None
	High performance gear oils for extended life	Klübersynth UH1 6-100...680 ¹⁾ Available in ISO VG 100, 150, 220, 320, 460, 680 viscosity grades The selection of the viscosity grade depends on the gear type and the application	Not applicable	Polyglycol	None
	High performance gear fluid greases	Klübersynth UH1 14-1600	00	Synthetic hydrocar- bon oil	Aluminium complex soap
Klüberfood NH1 94-6000		000	Synthetic hydrocar- bon oil	Aluminium complex soap	

¹⁾ On oil viscosity selection please refer to the equipment manufacturer's manual or ask for advice.

²⁾ Due to the many different elastomer and plastics compositions we recommend checking compatibility prior to series application.



Upper service temperature approx.	Lower service temperature approx.	Application notes and benefits
120 [°C] 248 [°F] or lower (depending on viscosity)	-35 [°C] -31 [°F] or higher (depending on viscosity)	<ul style="list-style-type: none"> - Improved wear protection and load-carrying capacity to maximise component life - Oil series complies with CLP requirements DIN 51 517 part 3 - Scuffing load stage ≥ 12 in the FZG test, DIN ISO 14635-1 A/8.3/90 - Good ageing and oxidation stability for increased oil life in comparison with industrial mineral oils - Good corrosion protection - Neutral towards sealing materials and paints²⁾ - ISO 21469 certified
160 [°C] 320 [°F] or lower (depending on viscosity)	-35 [°C] -31 [°F] or higher (depending on viscosity)	<ul style="list-style-type: none"> - Improved wear protection and load-carrying capacity to maximise component life in comparison with industrial mineral oils and synthetic hydrocarbon oils - Oil series complies with CLP requirements DIN 51 517 part 3 - Scuffing load stage ≥ 12 in the FZG test, DIN ISO 14635-1 A/8.3/90 - Good ageing and oxidation stability for increased oil life - The low friction behaviour of the polyglycol base oil reduces power losses and improves efficiency - Good corrosion protection - ISO 21469 certified
120 [°C] 248 [°F]	-45 [°C] -49 [°F]	<ul style="list-style-type: none"> - Component life enhanced resulting from a special thickener with good adhesion and good corrosion protection - ISO 21469 certified
120 [°C] 248 [°F]	-45 [°C] -49 [°F]	<ul style="list-style-type: none"> - Good corrosion protection and good pumpability in central lubrication systems - Reduced wear and extended maintenance intervals due to good load-carrying capacity - Good low-temperature characteristics enable use in refrigerated environments - ISO 21469 certified

Shrink wrap, Vacuum pumps, Screw threads and General maintenance

Application	Application points/machine components	Klüber speciality lubricant	Base oil	Thickener	Upper service temperature approx.	Lower service temperature approx.
Shrink wrap tunnels	Transport and drive chains	Klüberfood NH1 CH 2-220 Plus	Ester	None	250 [°C] 482 [°F]	-20 [°C] -4 [°F]
Vacuum pumps in packaging machines	Vacuum Pumps	Klüber Summit FG 300	Synthetic Hydrocarbon Oil	None	135 [°C] 275 [°F]	-35 [°C] -40 [°F]
Screw threads	Screw threads	Klüberoil 4 UH1-15 Spray	Synthetic hydrocarbon oil/ester oil ¹⁾	None	110 ¹⁾ [°C] 230 [°F]	-45 [°C] -49 [°F]
	Screw threads and slides	Klüberpaste UH1 84-201	Synthetic hydrocarbon oil	Solid lubricant / PTFE	120 [°C] 248 [°F]	-45 [°C] -49 [°F]
General maintenance	Various applications	Klüberfood NH1 4-002 Spray	Synthetic hydrocarbon oil	None	Not applicable	Not applicable
	Various applications	Klüberfood NK1 8-001 Spray	Organic solvent	None	Not applicable	Not applicable

¹⁾ of the active component



Application notes and benefits

- Low oil evaporation rate resulting in low residue formation and reduced oil consumption
- ISO 21469 certified
- Good oxidation stability
- Synthetic base oil with low volatility ensuring minimum carry-over, minimising contamination risks
- ISO 21469 certified
- Light penetrating oil to aid disassembly and reduce downtime
- Universal white assembly and thread paste
- Excellent low-temperature behaviour; good load-carrying capacity, good corrosion protection
- Neutral towards alloyed steels
- Also suitable for low-speed plain bearings, for guide rails, hinges, rollers etc.
- ISO 21469 certified
- Good penetrating and water displacement properties
- ISO 21469 certified
- Rapid and thorough removal of oils, greases, waxes and resin residues
- NSF K1 and NSF K3-registered for applications in the food-processing industry

Compressors

Application	Application points / machine components	Klüber speciality lubricant	Base oil	Thickener	Upper service temperature approx.	Lower service temperature approx.	
Compressors	Air screw compressors & pneumatics / hydraulics	Klüber Summit FG 100 / Klüberfood 4 NH1 32 ¹⁾	Synthetic hydrocarbon oil	None	135 [°C] 275 [°F]	-45 [°C] -49 [°F]	
	Air screw compressors & pneumatics / hydraulics	Klüber Summit FG 200 / Klüberfood 4 NH1 46 ¹⁾	Synthetic hydrocarbon oil	None	135 [°C] 275 [°F]	-40 [°C] -40 [°F]	
	Air reciprocating compressors	Klüber Summit FG 250 or 300 ¹⁾	Synthetic hydrocarbon oil	None	135 [°C] 275 [°F]	-40 [°C] -40 [°F]	
	Air rotary vane compressors	Klüber Summit FG 300 ¹⁾	Synthetic hydrocarbon oil	None	135 [°C] 275 [°F]	-35 [°C] -31 [°F]	
	Refrigeration compressors		Klüber Summit R 200 ¹⁾	Synthetic hydrocarbon oil	None	Not applicable	-51 [°C] -59.8 [°F]
			Klüber Summit RHT 68	Hydrotreated paraffin based mineral oil	None	Not applicable	-39 [°C] -38.2 [°F]
			Klüber Summit RPS 52	Polyglycol oil	None	Not applicable	-40 [°C] -40 [°F]

¹⁾ On oil viscosity selection please refer to the equipment manufacturer's manual or ask for advice.



Application notes and benefits

- Synthetic base oil with low volatility ensuring minimum carry-over, minimising contamination risks and consumption, providing typically increased oil life and operating cost reduction
- KlüberMonitor analysis scheme recommended to determine the optimum duration of oil use
- Please ask your Klüber consultant for advice
- ISO 21469 certified

- Synthetic base oil with low volatility ensuring minimum carry-over, minimising contamination risks and consumption, providing typically increased oil life and operating cost reduction
- KlüberMonitor analysis scheme recommended to determine the optimum duration of oil use
- Please ask your Klüber consultant for advice
- ISO 21469 certified

- Synthetic oil with low volatility ensuring minimum carry-over, minimising contamination risks
- Low residue formation reducing contamination of valves to reduce the risk of sticking and loss of compression, resulting in increased efficiency and reduced energy consumption.
- ISO 21469 certified

- Synthetic base oil with low volatility ensuring minimum carry-over, minimising contamination risks
- Increased efficiency resulting from low residue formation to reduce contamination of vanes to prevent sticking and loss of compression
- KlüberMonitor analysis scheme recommended to determine optimum duration of oil use
- ISO 21469 certified

- Synthetic compressor oil for refrigerating compressors operating with ammonia (R717), CO₂ (R744), propane (R290), propylene (R1270) or butane (R600) as refrigerant to minimise carry-over and sludge build up, supporting a reduction in oil consumption and operating costs
- Pourpoint ≤ -45 [°C] (-49 [°F])
- ISO 21469 certified

- Low maintenance costs due to extended oil change intervals and reduced oil consumption
- Easy compressor oil conversion due to neutral behaviour towards seals
- High efficiency of the refrigerating plant due to reduced oil deposits
- Low operating costs due to long service life of filters and oil separators
- Low oil carryover and consumption compared to naphthene-based mineral oils

- Reliable operation of the compressor due to stable viscosity under the influence of refrigerants
- High efficiency of the refrigerating plants due to reduced oil deposits
- Low operating costs due to long service life of filters and oil separators
- Simplified system configuration as the product can be used with dry evaporation

The right lubricant at the right place at the right time



Systems for automatic lubrication

We in Klüber Lubrication understand ourselves as a solution provider. We not only supply high-performance oils and greases, but also „intelligent packages“ for automatic lubrication of your machines and components. Selected lubricants covering a wide range of typical applications are available in automatic lubricant dispensers for single-point lubrication. These tried-and-tested systems based on electromechanical or electrochemical

technology are available with standard, long-term or high-pressure greases, standard or high-temperature chain oils and special oils and greases for the food-processing industry. We are also able to supply other lubricants in automatic dispensers on request and for higher order volumes, provided they have been tested and approved for use – please contact your Klüber Lubrication consultant for details.

Your benefits at a glance

Profitability

Continuous production processes and predictable maintenance intervals reduce production losses to a minimum. Consistently high lubricant quality ensures continuous, maintenance-free long-term lubrication for high plant availability. Continuous supply of fresh lubricant to the lubrication points keeps friction low and reduces energy costs.

Lubrication with Klübermatic can reduce costs by up to 25 %

Safety

Longer lubrication intervals reduce the frequency of maintenance work and the need for your staff to work in danger zones. Lubrication systems from Klüber Lubrication can therefore considerably reduce occupational safety risks in work areas that are difficult to access.

Lubrication with Klübermatic can decrease the risk of accidents by up to 90 %

Reliability

Automatic lubrication systems from Klüber Lubrication ensure reliable, clean and precise lubrication around the clock. Plant availability is ensured by continuous relubrication of the application.

Lubrication with Klübermatic may help to prevent up to 55 % of rolling bearing failures

From low-cost to high-tech - automatic systems for all requirements

Klüber Lubrication offers you the following technological solutions:

- freely adjustable lubrication increments between 1 and 12 months
- range of speciality lubricants
- self-contained or machine-controlled lubrication systems (time control with programmable controller)
- combination of tried-and-tested Klüber Lubrication lubricants with proven automatic lubricant dispensers

Klübermatic FLEX



Flexible use – and for lubrication points with high requirements

Klübermatic NOVA



For applications subject to wide temperature fluctuations

Klübermatic STAR VARIO



Precise and adjustable lubricant metering

Klübermatic STAR CONTROL



Externally controlled single-point relubrication



Publisher and Copyright:
Klüber Lubrication München SE & Co. KG

Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Products from Klüber Lubrication are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Klüber Lubrication München SE & Co. KG
Geisenhausenerstraße 7
81379 München
Germany

Local first-instance court Munich, Germany
Certificate of registration 46624

www.klueber.com

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

a brand of
 **FREUDENBERG**