



FTZ-UNI-15



FTZ-MAXI-25

## Grab for Prefabricated Concrete Products FTZ

- FTZ-I:** special compact clamp for laying heavy granit kerbs.
- FTZ-BB:** designed kerb stones with high concave section for bus stops („Kassel Kerb“).
- FTZ-UNI:** Universal clamp for all kind of precast elements.
- FTZ-MAXI:** As FTZ-UNI but with a very large gripping range.

- Gripping width adjustment by spring loaded bolt. Bolt can not get lost.
- Suspension bolt for lifting device.
- Automatic release for fully automatic switch over from „full“ to „empty“.
- Exchangeable rubber grippers.
- With handles to guide the grab.
- Durable surface protection by galvanizing.

**SAFETY-INDICATOR FTZ-SI:** Visually indicates gripping safety during the entire installation process. If, for example, dirt or moisture should cause the gripped material to slip, the red indicators provide a timely warning. Suitable for mounting on all of the FTZ grabs except FTZ-I and FTZ-BB.



**NEW**

SAFETY-INDICATOR FTZ-SI

Type	Length of Gripper mm (in)	Inside Height mm (in)	Dead Weight kg (lbs)	Gripping Range mm (in)	Working Load Limit/WLL kg (lbs)	Order-Number
FTZ-I	420 (16.54)	170 (6.69)	55 (121)	50 – 520 (1.97 – 20.47)	900 (1,984)	53100120
FTZ-BB	420 (16.54)	290 (11.42)	60 (132)	50 – 480 (1.97 – 18.90)	900 (1,984)	53100202
FTZ-UNI-15	420 (16.54)	255 (10.04)	88 (194)	0 – 750 (0.00 – 29.53)	1,500 (3,307)	53100256
FTZ-UNI-25	420 (16.54)	255 (10.04)	119 (262)	0 – 750 (0.00 – 29.53)	2,500 (5,512)	53100313
FTZ-MAXI-25	420 (16.54)	255 (10.04)	132 (291)	200 – 1,200 (7.87 – 47.24)	2,500 (5,512)	53100344
FTZ-UNI-50	720 (28.35)	200 (7.87)	245 (540)	0 – 850 (0.00 – 33.46)	5,000 (11,023)	53100362
FTZ-MAXI-50	720 (28.35)	240 (9.45)	260 (573)	400 – 1,250 (15.74 – 49.21)	5,000 (11,023)	53100363

### Accessories:

- Adapter for Kassel Kerb Stone A-FTZ-KB:** for FTZ-UNI-15 to extend gripping depth on one side to 290 mm (11.41 inch).
- Adjustable Height Stop HVA-FTZ/TSZ:** for all versions of FTZ-UNI/MAXI/MULTI and TSZ-UNI. Adjustable range TSZ-UNI/MAXI approx. 55 – 140 mm (2.16 – 5.51 inch). Adjustable range FTZ-UNI/MAXI-25 and FTZ-UNI/MULTI-15 approx. 120 – 255 mm (4.72 – 10 inch). FTZ-UNI-50 approx. 55 – 155 mm (2.16 – 6.10 inch). FTZ-MAXI-50 approx. 55 – 195 mm (2.16 – 7.67 inch).

Type	Dead Weight kg (lbs)	Order-Number
Adapter for Kassel Kerb Stone A-FTZ-KB	6.9 (15)	43100575
Adjustable Height Stop HVA-FTZ/TSZ	2.5 (5.51)	43100867
SAFETY-INDICATOR FTZ-SI	15.1 (33)	43101803

01/2023 Technical data contained in this catalogue can be modified without prior notice in the interest of progress. Illustrations are exemplary and non-binding. No liability accepted for any misprints, mistakes and errors. \* Details in the general sales conditions at the end of the catalogue or at www.probst-handling.com/en/gtc