Vermilion® Seven









TR10 -20°C (-4°F) T70 -23°C (-9°F)



temperature performance

Continuous +160°C (+320°F)



qualification

Qualified to Norsok M-710 ISO 23936-2 'sour'

Qualified to API 6A FF/HH ISO 10423



Norsok M-710 / ISO 23936-2 **Testing for RGD resistance**

0000' rating at 100°C 6.99 mm / 150 bar / 90% CH₄ 10% CO₂ / 10 cycles

'0000' rating at 125°C 5.33 mm / 150 bar / 90% CH₄ 10% CO₂ / 8 cycles

Vermilion®



Seven

RGD, sour and extrusion resistance



Vermilion® Seven is a next generation enhanced performance development of James Walker's industry leading Elast-O-Lion® 101 material.

An hydrogenated nitrile (HNBR) material offering excellent rapid gas decompression (RGD) resistance at elevated temperature and good resistance to sour conditions combined with outstanding physical robustness and improved extrusion resistance.

Sealing capability confirmed down to -33°C (-27°F) in product configured testing

(See material data sheet for test details)







James Walker Worldwide

Australia

T: +61 2 9721 9500

E: sales.jwau@jameswalker.biz

Belgium

T: +32 3 820 79 00

E: sales.be@jameswalker.biz

Brazil

T: +55 11 4392 7360

E: sales.br@jameswalker.biz

China

T: +86 21 6876 9351

E: sales.cn@jameswalker.biz

France

T: +33 437 49 74 80

E: sales.fr@jameswalker.biz

Germany

T: +49 4038 60810

E: sales.de@jameswalker.biz

India

T: +91 224 0808080

E: sales.in@jameswalker.biz

Ireland

T: +353 214 323626

E: sales.ie@jameswalker.biz

Italy

T: +39 2 2578308

E: sales.it@jameswalker.biz

Middle East

T: +971 481 78888

E: sales.jwme@jameswalker.biz

Netherlands

T: +31 186 633111

E: sales.nl@jameswalker.biz

New Zealand

T: +64 9 272 1599

E: sales.nz@jameswalker.biz

Norway

T: +47 22 75 75 00

E: sales.no@jameswalker.biz

Singapore

T: +65 6715 6300

E: sales.sg@jameswalker.biz

South Africa

T: +27 31 304 0770

E: sales.za@jameswalker.biz

Spain & Portugal

T: +34 94 447 00 99

E: sales.es@jameswalker.biz

UK

T: +44 1270 536000

E: sales.uk@jameswalker.biz

USA

T: +1 708 754 4020

E: sales.jwna.us@jameswalker.biz

Information given in this publication is given in good faith and represents the results of specific individual tests carried out by James Walker or third parties in accordance with the methodologies described in this publication, performed in a laboratory. No representation or warranty is given in relation to such information. Values and/or operating limits given in this publication are not an indication that these values and/or operating limits can be applied simultaneously. While such results may comprise useful additional information and are industry standard tests, they are no substitute for conducting (or procuring from James Walker) your own tests and engineering analysis and satisfying yourself as to the suitability of the product you select. Please also note that a product tested in accordance with the published methodology may not perform to such values in application and/or under different test conditions or methodologies for a variety of reasons, including but not limited to the environment in which it is used/tested or which passes through it or otherwise affects the product, or due to the handling, storage or installation, or due to the effect of housing or other parts. Our personnel will be happy to discuss any historical examples we have of a product having been previously used in a particular application.

To ensure you are working with the very latest product specifications, please consult the relevant section of the James Walker website: www.jameswalker.biz.

James Walker Sealing Products & Services Ltd

Registered Office: Lion House, Oriental Road, Woking, Surrey GU22 8AP, United Kingdom. Reg no: 00264191 England

