



## Thermotech Portabel Induction Heater Series

Thermotech mobile induction heater. 5KW 16 Kg and 10KW 18 Kg for weld preheating. CE certified. Voltage usage from 220 V.

- Increased productivity
- Environmental friendly
- Wide suitability
- High Efficient
- User friendly



On-Site Machining | Bolt Tensioning | Heat Treatment | Leak Sealing

Thermotech AS | Kvalamarka 23 | N-5514 Haugesund | Norway | Thermotech-as.no | Tel: +47 52 70 00 80



**Technical Details for Thermotech Portabel Induction Heater Series:**

Model	Rated input voltage & frequency	Rated input power	Rated input current	Output frequency	Cooling water pressure/flow rate	Dimensions (mm)
TTIH 210 – 005A	1-Phase/230V 50/60 Hz	5KW	22 A	5-60 KHz	Air Cooled	L: 504,4 W: 242,9 D: 295,2
TTIH 210 – 010A	3- phase/400V (+/- 20%) 50/60 Hz	10KW	15A	10 - 40 KHZ	4 – 6 bar, ≥12L/min	L: 581,5 W: 283 H: 334
TTIH 210 – 010B		10KW	15A			
TTIH 210 – 015B		15KW	22A			
TTIH 210 – 020B		20KW	30A			
TTIH 210 – 025B		25KW	37A			
TTIH 210 – 030B		30KW	45A			
TTIH 210 – 035B		35KW	53A			
TTIH 210 – 040B		40KW	60A			
TTIH 210 – 050B		50KW	75A	5 – 25 KHZ	4 – 6 bar, ≥ 19L/min	L: 475,5 W: 456 H: 1290,5
TTIH 210 – 060B		60KW	91A			
TTIH 210 – 080B		80KW	121A			
TTIH 210 – 100B		100KW	152A			
TTIH 210 – 120B		120KW	182A			
TTIH 210 – 160B		160KW	243A			
TTIH 210 – 200B		200KW	303A			
TTIH 210 – 250B		250KW	380A			
TTIH 210 – 300B	300 KW	456A	4 – 6 bar, ≥ 60L/min	L: 671,5 W: 780 H: 1986,5		



On-Site Machining | Bolt Tensioning | Heat Treatment | Leak Sealing

Thermotech AS | Kvalamarka 23 | N-5514 Haugesund | Norway | Thermotech-as.no | Tel: +47 52 70 00 80