

MOT - 150N

150 LITRES

MotorClean
BY TIERRATECH

ELECTRICAL CHARACTERISTICS

- Power Supply: 240V / 400V
- Heating element: 3750W

ULTRASONIC CHARACTERISTICS

- Ultrasonic power: 1700Wp (3400W p-p)
- 1 ultrasonic generator with an output power of 1700Wp (3400W p-p)
- 1 submersible emitter with a power of 1700Wp (3400W p-p) made of 2.5 mm thick stainless steel AISI 316L. The emitter contains 34 PZT (lead zirconate titanate) piezo-electric transducers with aluminium alloy body.
- Working frequency: 40 KHz sweep system \pm 2%

CONTROL PANEL

- 4.3" touch screen. Functional and intuitive access to ultrasound time setting, temperature and peripheral or optional systems. Programmable weekly calendar
- 6 outputs and 8 inputs temperature module PLC

FINISH AND ACCESORIES

- Tank made of 2 mm thick stainless steel AISI 304L
- External panel in 1 mm thick fingerprint resistant steel
- 20 mm thick thermo-acoustic insulation
- Reinforced pneumatic platform for loading and unloading up to 60 kg
- 1" drain ball valve
- Height-adjustable silentblock legs
- Insulated tank cover in stainless steel with pneumatic shock absorber
- Air blow gun for drying the parts
- Integrated waterflow system. Sweeps the waste floating on the surface, keeping the cleaning equipment in perfect condition
- (Optional): Filtration system (stainless steel filter with polypropylene / polyester bag) for waste and mud

TECHNICAL DATA

- Capacity: 150 litres
- Internal dimensions: 700 x 480 x 540 mm
- Useful dimensions: 670 x 415 x 330 mm
- External dimensions: 1355 x 825 x 945 mm
- Weight: 175 kg
- Reinforced pneumatic platform : Up to 60kg

