







MODEL	OPAL WATERJET	
Drives	Servo AC	
Cutting width	1000 - 6000 mm	
Basic working length	1000 - 12000 mm	
Cutting thickness - Waterjet 2D	0,5 - 250 mm	
Cutting thickness - Waterjet 3D	0,5 - 150 mm	
Positioning speed	25000 mm/min	
Safety standard	EN 13850	



SOFTWARE





And many more..





Pawicka 4c, 59-220 Legnica, Poland tel: +48 (76) 856 09 28 eckert@eckert.com.pl

www.eckert.com.pl



Versatile and precise waterjet cutting





WATER

OPAL WATERJET



2-axis waterjet cutting head Allfi is utilising proven in practice hydro-abrasive cutting technology. Well designed construction head equipped with height sensor and anti collision device guarantee the best quality cuts and faultless operation.





PRO-X 3D HEAD

5-axis Pro-X 3D head provides a very high level of efficiency and insures the achievement of maximum 3-dimensional precision. The maximum cutting angle +/- 60 and automatic angle compensation ensure great precision and practically zero angle on the cutting edge. Perfect tool to minimize post processing.





Opal Waterjet cutting machine is equipped with the robust water table with double grid system. Steel, fully tinned* construction insures durability and corrosion resistance. The detached table construction ensures maximum stability and smooth running operations.



Iditional ontion



CNC CONTROLLER

The most modern i-Vision Controller is the high quality industry machine has Corning® Gorilla® Glass's touchscreen. Efficient parts and the strong construction ensures reliability Onyx working. Many functions of own software and simple controller's interface let to use all of machine's possibilities. Standalone controller delivers the unique comfort and safety of machines operator. It make also possible to watching the cutting process and controller's using at the same moment.



E

CONSTRUCTION

Opal Waterjet has gantry construction. The machine is made from steel closed profiles which ensure great stability. Rail elements where protected against harmful influence of water with protective bellows or covered by aluminium parts. Relatively low weight of the gantry and specially grounded racks furnishes our Opal Waterjet with excellent dynamics and high precision motors boosts accurate positioning.



CHARACTERISTICS

Opal Waterjet cutting machine was created in response to the need of obtaining smooth, high quality finish with no heat-affected zone or thermal distortion. Utilisation of waterjet cutting allows work with a wide variety of materials such as: stone, wood, plastics etc. up to 250 mm thickness. Optional use of PRO-X 3D cutting head widens design capability of the machine by 3D operations.

OPAL WATERJET PRO-X 3D FL

MAIN FEATURES

▶ Versatility

6

- ► There are no dust as a by-product of cutting
- ► Abrasive or pure water cutting
- ▶ Waterjet cutting system can operate with up to four cutting heads at a time

ECKERT

- ► Customised high pressure pump adjustment
- ▶ Dross free cutting minimizes post processing





BFT	ECOTRON 40.22	ECOTRON 40.30	ECOTRON 40.37	ECOTRON 40.45+	SERVOTRON 40.37	SERVOTRON 40.45+
Power [kW]	22	30	37	45	37	45
Max. flow [l/min]	2,3	3,4	3,8	4,3	3,8	4,6
Pressure [bar]	4000	4000	4000	4000	4000	4000



кмт	TL-I 30	NL-I 40	JL-I 50	SL-VI 30 PLUS	SL-VI 50 STD	SL-VI 60 PRO-III	
Power [kW]	22	29	37	22	37	45	
Max. flow [l/min]	3,1	2,7	3,8	2,6	4,3	6,0	
Pressure [bar]	3800	3800	3800	4136	3800	6200	