

T291

Small Walk-Behind Scrubber-Dryer

Small Size. Big Value.

Get a lot of value in a small scrubber-dryer with a simple control panel, comfortable ergonomics, and straight-forward operation. Daily cleaning routine is made easy due to large recovery tank access, easy spin-on, spin-off brush/pad replacement and yellow touchpoints. Perfect for retail settings, schools and hospitals.



Comfortable & Easy to Maneuver

Maintain operator health and safety with great maneuverability, and maximize comfort with adjustable controls.



Simplify Operator Training

Easy-to-use control knob that visually shows selected mode. Conveniently select from 13 language options available.



Sustainable Performance

Reduce noise levels and water consumption while increasing run-time with ECO mode.

Inside the T291

1. **Self-leveling scrub head** for optimum cleaning performance.
2. **Simplified operator training** with easy-to-use pre-programmed cleaning settings, standard and ECO.
3. **Helpful machine information** is visible with intuitive and large LCD display.
4. **Simple daily maintenance** with large sized recovery tank opening enabling full access and visibility.
5. **Excellent water pick-up** from easily adjustable squeegee design and standard Linatex® blades.
6. **Simple no-tools, no-touch brush/pad change system** simply spin-on, and spin-off.



T291 Specifications

FEATURE	SPECIFICATION	
	PAD ASSIST	SELF-PROPEL
Cleaning path	550 mm	
Productivity (per hour) theoretical max	1967 m ² /hr	2468 m ² /hr
Estimated coverage (per hour)*	1246 m ² /hr	1564 m ² /hr
Scrubbing speed	3.5 kmh	4.5 kmh
Scrub head raise/lower	manual with foot pedal	
Brush/pad speed	150 rpm	
Brush/pad pressure	19 kg	
Solution tank capacity	50 L	
Recovery tank capacity	50 L	
Battery run time - up-to hours**	2.5	3.5
Battery voltage	24V (2 x 12)	
Dimensions (L x W x H)	1327 x 563 x 1033 mm	
Squeegee width	815 mm	
Weight (with heaviest battery)	150 kg	178 kg
Sound level (operator's ear)***	56 dB	

Specifications subject to change without notice.
 * Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.
 ** Run times are based on Continuous Scrubbing Run Times.
 *** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

For a demonstration or additional information,
 call **+32 3 217 94 11** or email **europe@tennantco.com**

TENNANT EUROPE NV
 tennant.eu