

3M Water Filtration
3M™ ScaleGard® Pro Range



Scale reduction
for coffee, vending
and steamers



Market and main product claims

- There are over 3 000 000 vending machines, coffee machines, steamers and ware washing machines in Western Europe.
- The need for competitive and functional scale reduction that protects equipment and leaves the right elements in the water to make great tasting hot beverages has never been of more importance.

Range offering and key benefits

- The ScaleGard® Pro range from 3M is comprehensively split into two ranges - standard and H+ and available in most sizes with the option of a fixed bypass or non-bypass.
- This means a product that meets the needs of all types of machines whether they have a small or very high capacity.

Scale protection types and range features & benefits



3M™ ScaleGard® Pro Coffee, Vending and Steamer scale control range and technical specifications

System	Cartridge		Description	Recommended Head		Flow rate (l/min)
	Model	Part Number		Model	Part Number	
SGP range - With Bypass						
SGP124BN-E	P124BN-E	XA004809001	P124BN-E Cartridge	VH3 3/8" BSPT	70020114164	1,9
SGP145BN-E	P145BN-E	XX004814362	P145BN-E Cartridge			1,9
SGP165BN-E	P165BN-E	XX004814347	P165BN-E Cartridge			1,9
SGP195BN-E	P195BN-E	XX004814321	P195BN-E Cartridge	VH3 3/8" BSPT-NB	70020254366	3,8
SGP1175BN-E	P1175BN-E	XA004809274	P1175BN-E Cartridge			3,8
SGP range - No Bypass						
SGP115-E	P115-E	XA004809050	P115-E Cartridge	VH3 3/8" BSPT	70020114164	1,9
SGP145-E	P145-E	XX004814370	P145-E Cartridge			1,9
SGP165-E	P165-E	XX004814354	P165-E Cartridge			1,9
SGP195-E	P195-E	XX004814319	P195-E Cartridge	VH3 3/8" BSPT-NB	70020254366	3,8
SGP1175-E	P1175-E	XA004809282	P1175-E Cartridge			3,8
SGP H+ range - With Bypass						
SGP145BH	P145BH	XA004819646	H+ P145BH Cartridge	VH3 3/8" BSPT	70020114164	1,9
SGP165BH	P165BH	XA004819620	H+ P165BH Cartridge			3,8
SGP195BH	P195BH	XA004819604	H+ P195BH Cartridge			3,8
SGP1175BH	P1175BH	XA004819588	H+ P1175BH Cartridge	VH3 3/8" BSPT-NB	70020254366	3,8
SGP H+ range - No Bypass						
SGP145H	P145H	XA004819638	H+ P145H Cartridge	VH3 3/8" BSPT	70020114164	1,9
SGP165H	P165H	XA004819612	H+ P165H Cartridge			3,8
SGP195H	P195H	XA004819596	H+ P195H Cartridge			3,8
SGP1175H	P1175H	XA004819570	H+ P1175H Cartridge	VH3 3/8" BSPT-NB	70020254366	3,8
Alternative Heads						
				VH3 3/8" JG	70020211499	
				VH3 3/8" JG-NB	70020231471	
Accessories		XA004827391	Digital Flow Meter Kit			

- ## Full scale treatment offering from 3M Water Filtration

- This resin based range is part of a total range from 3M that includes scale inhibition products, softening products and Reverse Osmosis products.
- With resin the most highly used method in Europe for scale reduction and removal, this range is unique and meets customer needs from small coffee machines right through to large vending machines and steamers.



SGP195



SGP1175




VH3-BSPT head
VH3-JG head



VH3-BSPT / VH3-JG
no bracket head

Proportional/Filtered Bypass	Scale Capacity (litres) at 180 ppm	CTO Reduction	Resin	Machine Capacity	Coffee	Applications		
						Vending	Combi Ovens	Steamers
N	1600	•	Standard	S	•	•		
N	1600	•	Standard	S	•	•		
N	2300	•	Standard	M	•	•		
N	3800	•	Standard	L	•	•		
Y	6000	•	Standard	XL	•	•		
N	600	•	Standard	VS	•	•	•	•
N	1200	•	Standard	S	•	•	•	•
N	1725	•	Standard	M	•	•	•	•
N	2850	•	Standard	L	•	•	•	•
Y	4500	•	Standard	XL	•	•	•	•
N	2240	•	H+	S	•	•	•	•
N	3173	•	H+	M	•	•	•	•
N	5289	•	H+	L	•	•	•	•
Y	8400	•	H+	XL	•	•	•	•
Use where corrosion is not an issue								
N	1680	•	H+	S	•	•	•	•
N	2380	•	H+	M	•	•	•	•
N	3967	•	H+	L	•	•	•	•
Y	6300	•	H+	XL	•	•	•	•
Use where corrosion is not an issue								

Dimensions



Scale Capacity - Sizing Guide

Incoming hardness				Litres throughput									
ppm	° e	° d	° f	SGP115		SGP124 - SGP145		SGP165		SGP195 *		SGP1175	
				Litres	Cups *	Litres	Cups *	Litres	Cups *	Litres	Cups *	Litres	Cups *
140	9.8	7.8	14	771	5143	2057	13714	2914	19429	4857	32381	7714	51429
180	12.6	10.1	18	600	4000	1600	10667	2267	15111	3778	25185	6000	40000
210	14.7	11.8	21	514	3429	1371	9143	1943	12952	3238	21587	5143	34286
250	17.5	14.0	25	432	2880	1152	7680	1632	10880	2720	18133	4320	28800
280	19.6	15.7	28	386	2571	1029	6857	1457	9714	2429	16190	3857	25714
320	22.4	17.9	32	338	2250	900	6000	1275	8500	2125	14167	3375	22500
360	25.2	20.2	36	300	2000	800	5333	1133	7556	1889	12593	3000	20000
390	27.3	21.8	39	277	1846	738	4923	1046	6974	1744	11624	2769	18462
430	30.1	24.1	43	251	1674	670	4465	949	6326	1581	10543	2512	16744

Capacities are guidelines only. Actual capacity may vary.

* Cup size based on 150 ml dispense. For number of cups divide capacity in litres by 0.15.

All capacities based on 25% bypass. For non-bypass, capacity should be reduced by 25%.

For H+ range capacities are 40% higher so multiply by 1.4 to work out capacity.

For commercial use with cold water only. For all systems, heads and cartridges are sold separately. Maximum operating pressure is 100 psi (6.9 bar). Inlet and outlet connections are 3/8" BSPT or JG female. All materials are FDA CFR 21 compliant. Maximum operating temperature is 37.8 °C.

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. In line with current good practice filters should be changed every 12 months, on reaching capacity or if a noticeable drop in performance occurs. Scheduled maintenance is recommended. 3M cannot be liable for system failures due to improper maintenance.



3M United Kingdom plc

3M Water Filtration

3M Centre, Cain Road
Bracknell, RG12 8HT
United Kingdom
Tel.: 0845 602 5237
Fax: +44 (0)1344 858559
E-mail: purification.uk@mmm.com

3M and Scalegard are trademarks of the 3M Company.

For more contact addresses visit our website www.3M.eu/filtration or www.3Mpurification.com/international.

Data may be subject to change without further notice.

© 3M 2011. All rights reserved. Please recycle.

DOC10223
EURO0035 - 0511



ultrafilter trykluftprogram:

ultrafilter valideret trykluft program indenfor, filter, Køletørrer samt adsorptionstørrer.

—
ultrafilter validated Compressed air filter program with filter, dryer and desiccant dryer.



Trykluftfilter:

Trykluftfilter til brug for håndværkere, værksteder og til mindre kritiske applikation i industrien.

—
Compressed air filter for use by craftsmen, workshops, and for less critical applications in the industry.



Procesfiltrering:

Procesfilter for luft og Gas samt væskefiltrering fra 3M / Cuno , sterilfilter, dampfilter samt Membran filtrering.

—
Process filter for air / gas and liquid filtration, sterile filter steam filter, and Membran filtration.



Vandfilter

Stort program for vandfilter fra Cuno & 3M

—
A wide range of water filter from Cuno & 3M



Nitrogen og Oxygen systemer

Produktion af egen nitrogen eller oxygen, med et modul opbygget system som kan udvides efter behov.

—
Producing own nitrogen or oxygen, with a modular system which can be expanded as needed.



Måleinstrumenter

Måleudstyr til måling og overvågning af trykluft- og nitrogen udstyr.

—
Measuring equipment for measuring and monitoring of compressed air and nitrogen plant.



Service:

Vi tilbyder opstart og montering af alle vores produkter. og kan tilbyde serviceaftaler på alle vores produkter.

Vi har samarbejdspartner i Danmark, Sverige, Norge, Finland, og Island.

—
We offer start-up and installation of all our products. And we can offer service on all our products. We have partner in Denmark, Sweden, Norway, Finland, Iceland.

ultrafilter Skandinavien ApS

info@ultra-filter.dk • www.ultra-filter.dk

Telefon : +45 82 30 30 20