



Bredflensbjelker - HEA S355J2

Tekniske lev. betingelser: NS-EN 10025-2

Toleranse etter NS-EN 10 034

Dokumenter etter NS-EN 10204-3.1 CE merket

Leveringstilstand M eller AR

HEA	pr. m	kg pr. lengde				mål i mm			
		10	12	15	18	Høyde	Bredde	Steg	Flens
100	17,2	172	206	257		96	100	5,0	8,0
120	20,6	206	247	308		114	120	5,0	8,0
140	25,4	254	305	381	457	133	140	5,5	8,5
160	31,3	313	376	470	563	152	160	6,0	9,0
180	36,5	365	438	548	657	171	180	6,0	9,5
200	43,5	435	522	653	783	190	200	6,5	10,0
220	52,0	520	624	780	936	210	220	7,0	11,0
240	62,1	621	745	932	1 118	230	240	7,5	12,0
260	70,3	703	843	1 054	1 265	250	260	7,5	12,5
280	78,7	787	944	1 181	1 417	270	280	8,0	13,0
300	91,0	910	1 092	1 365	1 638	290	300	8,5	14,0
320	100,6	1 006	1 207	1 508	1 810	310	300	9,0	15,5
340	108,2	1 082	1 298	1 622	1 947	330	300	9,5	16,5
360	115,3	1 153	1 384	1 730	2 075	350	300	10,0	17,5
400	128,8		1 545	1 931	2 318	390	300	11,0	19,0
450	144,2		1 730	2 162	2 595	440	300	11,5	21,0
500	159,7		1 916	2 395	2 874	490	300	12,0	23,0
550	171,0		2 052	2 565	3 078	540	300	12,5	24,0
600	183,4		2 201	2 751		590	300	13,0	25,0

De lengdene som har ferdig utfylt vekt pr. lengde, lagerføres normalt.