

Full line - små - mellemstore - store
Et-trins centrifugal pumper

Med fokus på høj virkningsgrad

Små pumper

GG20 Støbejern
PN10
Max. 90/120°
32-65 mm
0.37-4,0 kW



NR

GG20 Støbejern
PN10
Max. 90/120°
25-65 mm
0.25-5,5 kW



NM

Type NR In-line	kW	Omdr.	Cbm/t	Løft mvs	Virk. %	Type NM End Suction	kW	Omdr.	Cbm/t	Løft mvs	Virk. %
NR4 32/160A	0,37	1450	6	7	50	NM4 25/12A/A	0,25	1450	4	5	57
NR4 32/200B	0,55	1450	8	9	50	NM4 25/160BE	0,37	1450	5	6	52
NR4 32/200A/A	0,75	1450	8	11	50	NM4 25/160AE	0,37	1450	5	7	53
NR 32/160B/A	1,1	2900	9	22	56	NM4 25/200BA	0,55	1450	7	9	53
NR 32/160A/A	1,5	2900	11	30	60	NM4 25/200A/C	0,75	1450	8	8	54
NR 32/200B/A	2,2	2900	12	33	65						
NR 32/200A/A	3,0	2900	14	40	67	NM4 32/16BE	0,37	1450	8	6	61
NR 32/200S/A	4,0	2900	16	44	66	NM4 32/16AE	0,37	1450	9	7	62
						NM4 32/20BE	0,55	1450	8	10	53
NR4 40/160A	0,37	1450	10	7	62	NM4 32/20A/B	0,75	1450	9	12	53
NR4 40/200B	0,55	1450	10	9	50	NM 32/12FE	0,55	2900	12	10	68
NR4 40/200A/A	0,75	1450	10	11	52	NM 32/12DE	0,75	2900	12	16	72
NR 40/125C	0,75	2900	14	12	67	NM 32/12A/A	1,1	2900	14	20	72
NR 40/125B/A	1,1	2900	16	16	71	NM 32/12S/A	1,5	2900	16	20	70
NR 40/125A/A	1,5	2900	18	19	72	NM 32/16A/B	2,2	2900	16	32	63
NR 40/160A/A	2,2	2900	20	24	62						
NR 40/200B/A	3,0	2900	17	20	50	NM4 40/16C/A	0,37	1450	12	5	68
NR 40/200A/A	4,0	2900	19	38	51	NM4 40/16B/A	0,55	1450	16	6	70
						NM4 40/16A/C	0,75	1450	18	7	72
NR4 50/160C	0,37	1450	15	4	65	NM 40/12F/B	1,1	2900	20	12	68
NR4 50/160B	0,55	1450	17	5	63	NM 40/12C/B	1,5	2900	26	14	70
NR4 50/160A	0,75	1450	18	6	63	NM 40/12A/C	2,2	2900	30	18	73
NR4 50/200A	1,1	1450	15	12	60	NM 40/16B/C	3,0	2900	28	25	70
NR4 50/125F/A	1,1	2900	22	12	67						
NR4 50/125C/A	1,5	2900	30	13	70	NM4 50/16B/C	1,1	1450	26	6	73
NR4 50/125A/B	2,2	2900	34	16	68	NM4 50/16A/C	1,1	1450	30	8	75
NR4 50/160B/B	3,0	2900	30	21	63	NM4 50/20B/C	1,5	1450	28	11	70
NR4 50/160A/B	4,0	2900	34	26	62	NM4 50/20A/C	2,2	1450	35	11	71
						NM 50/12F/C	2,2	2900	45	12	70
NR4 65/125F	0,37	1450	20	3	65	NM 50/12D/C	3,0	2900	50	16	72
NR4 65/125D	0,55	1450	22	4	68	NM 50/12A/C	4,0	2900	50	20	75
NR4 65/125A/B	0,75	1450	25	5	71						
NR4 65/125S/B	0,75	1450	32	4	68	NM4 65/16C/C	1,1	1450	50	5	77
NR4 65/160A/B	1,1	1450	32	7	70	NM4 65/16B/C	1,1	1450	55	6	79
NR4 65/200B/B	1,5	1450	30	10	67	NM4 65/16A/C	1,5	1450	60	7	80
NR4 65/200A/B	2,2	1450	32	11	67	NM4 65/16S/A	2,2	1450	65	8	80
						NM4 65/20B/B	2,2	1450	50	10	76
						NM4 65/20A/A	3,0	1450	80	14	81
						NM 65/12F/C	4,0	2900	95	16	83
						NM 65/12C/B	5,5	2900	105	20	83

Mellemstore pumper

GG20 Støbejern
GGG40 Sejjern
PN10, PN16 og PN25
Max. 90/120/140/150°



ESL

65-100 mm pumper
1,1 -18,5 kW

GG20 Støbejern
GGG40 Sejjern
PN10, PN16 og PN25
Max. 90/120/140/150°



ESLH

65-100 mm pumper
1,1 - 18,5 kW

Type ESL In-line	kW	Omdr.	Cbm/t	Løft mvs	Virk. %		Type ESLH End-Suction	kW	Omdr.	Cbm/t	Løft mvs	Virk. %
ESL 65-180/160	1,1	1450	30	6	74		ESLH 65-180/160	1,1	1450	32	6	80
ESL 65-180/170	1,5	1450	32	7	75		ESLH 65-180/170	1,5	1450	36	6	80
ESL 65-180/180	2,2	1450	35	8	77		ESLH 65-180/180	2,2	1450	40	7	80
ESL 65-180/125	3,0	2900	50	13	68		ESLH 65-180/130	3,0	2900	55	15	75
ESL 65-180/140	4,0	2900	55	18	72		ESLH 65-180/143	4,0	2900	60	18	77
ESL 65-180/150	5,5	2900	60	20	72		ESLH 65-180/155	5,5	2900	65	21	79
ESL 65-180/165	7,5	2900	65	25	74		ESLH 65-180/170	7,5	2900	70	26	80
ESL 65-180/180	11	2900	70	32	76		ESLH 65-180/180	11	2900	75	30	80
ESL 80-180E/160	1,1	1450	45	5	79		ESLH 80-180E/160	1,1	1450	45	6	80
ESL 80-180E/170	1,5	1450	50	6	79		ESLH 80-180E/170	1,5	1450	55	6	81
ESL 80-180E/180	2,2	1450	50	7	79		ESLH 80-180E/180	2,2	1450	60	6	81
ESL 80-180E/120	3,0	2900	70	11	70		ESLH 80-180E/120	3,0	2900	70	11	75
ESL 80-180E/125	4,0	2900	70	13	72		ESLH 80-180E/125	4,0	2900	75	14	77
ESL 80-180E/140	5,5	2900	80	17	76		ESLH 80-180E/140	5,5	2900	85	17	79
ESL 80-180E/155	7,5	2900	90	21	78		ESLH 80-180E/157	7,5	2900	90	22	80
ESL 80-180E/175	11	2900	100	28	79		ESLH 80-180E/175	11	2900	110	26	81
ESL 80-180E/180	15	2900	110	28	79		ESLH 80-180E/180	15	2900	120	26	82
ESL 100-180/140	1,1	1450	55	4	73		ESLH 100-180/140	1,1	1450	60	4	77
ESL 100-180/160	1,5	1450	65	5	78		ESLH 100-180/160	1,5	1450	70	5	79
ESL 100-180/180	2,2	1450	75	7	79		ESLH 100-180/180	2,2	1450	80	7	80
ESL 100-180/140	7,5	2900	120	16	73		ESLH 100-180/140	7,5	2900	120	14	77
ESL 100-180/160	11	2900	130	21	78		ESLH 100-180/160	11	2900	140	20	80
ESL 100-180/170	15	2900	150	24	79		ESLH 100-180/175	15	2900	160	23	80
ESL 100-180/180	18,5	2900	160	27	79		ESLH 100-180/180	18,5	2900	170	26	80




NSL

GG20 Støbejern
GGG40 Sejjern
PN10, PN16 og PN25
Max. 90/120/140/150/180°

80-350 mm pumper
1,1 -710 KW

De velkendte, store DESMI pumper



NSLH

GG20 Støbejern
GGG40 Sejjern
PN10, PN16 og PN25
Max. 90/120/140/150/180°

80-350 mm pumper
1,1 -710 KW



Mere information om vores pumper og pumpe løsninger findes på www.desmi.com

MARINE & OFFSHORE

INDUSTRY

OIL SPILL RESPONSE

DEFENCE & FUEL

UTILITY