



## Vinkelstål - S355J2

Tekniske lev. betingelser: NS-EN 10025-2

Toleranser etter NS-EN 10056-2

Dokumenter etter NS-EN 10204-3.1 CE merket

		kg pr. lengde	
Dim.mm	kg/m	6	12
LIKEBEINET			
70 x 70 x 7,0	7,5		90,4
75 x 75 x 8,0	9,2		110,5
80 x 80 x 8,0	9,9	59,1	118,2
80 x 80 x 10	12,1		145,2
100 x 100 x 10	15,4	92,4	184,8
100 x 100 x 12	18,2		218,4
120 x 120 x 12	22,0		264,0
150 x 150 x 12	28,0		335,4
150 x 150 x 14	32,3		387,6
200 x 200 x 16	49,5		594,0
250 x 250 x 18	69,8		837,6

ULIKEBEINET			
80 x 40 x 6	5,6		66,8
100 x 50 x 8,0	9,2		183,6
120 x 80 x 10	15,3		183,6
130 x 65 x 8,0	12,1		110,0
150 x 75 x 9,0	15,6		187,2
150 x 100 x 10	19,4		232,8
150 x 100 x 12	23,1		277,2
200 x 100 x 10	23,5		282,0
200 x 100 x 12	27,9		334,8

Andre lengder, dimensjoner og kvaliteter kan skaffes.