

TT - 2000N

2000 LITRES

ELECTRICAL CHARACTERISTICS

- Power Supply: 400V
- Heating element: 2x9000W

ULTRASONIC CHARACTERISTICS

- Ultrasonic power: 10200W (20400W p-p)
- 3 ultrasonic generators with an output power of 10200W (20400W p-p)
- 6 submersibles emitters with a power of 1700W (3400W p-p) made of 2.5 mm thick stainless steel AISI 316 steel. The emitter contains 34 high-performance IBL piezo-electric transducers in titanium steel
- Working frequency: 40 KHZ sweep system \pm 2%

CONTROL PANEL

- 4.3" touch screen. Functional and intuitive access to ultrasound time setting, temperature and peripheral or optional systems. Programmable weekly calendar
- 6 outputs and 8 inputs temperature module PLC

FINISH AND ACCESORIES

- Tank made of 2 mm thick stainless steel AISI 304
- External panel in 1 mm thick fingerprint resistant steel
- 20 mm thick thermo-acoustic insulation
- Reinforced pneumatic platform for loading and unloading up to 1000 kg
- 2" drain ball valve
- Height-adjustable silentblock legs
- Automatic insulated tank cover in stainless steel operated by a pneumatic cylinder
- Air blow gun for drying the parts
- Integrated waterflow system. Sweeps the waste floating on the surface, keeping the cleaning equipment in perfect condition
- (Optional): Filtration system (stainless steel filter with polypropylene / polyester bag) for waste and mud

TECHNICAL DATA

- Capacity: 2000 litres
- Internal dimensions 1750 x 1100 x 1080 mm
- Useful dimensions: 1650 x 910 x 790 mm
- External dimensions: 3130 x 1610 x 1345 mm
- Weight: 1250 kg



WARRANTY AND PRODUCT QUALITY: All equipments supplied by TierraTech®. are supplied with an instruction manual in English according to the European legislation on CE marking. The equipments comply the directives on electromagnetic compatibility and electrical safety: Directive 2004/108/EC and Directive 2006/95/EC. The equipments have 2 years warranty against manufacturing defects.

Tierra Tech S.L.

Pque. Emp. Morero, nave 27. Guarnizo - Cantabria (SPAIN)

Tel (+34) 942 26 95 43 • Fax (+34) 942 26 95 44 • tierratech@tierratech.com • www.tierratech.com