

Codan 1220 Air / Water Hose



Codan 1220 - BS5118 Type 2

Extremely sturdy and pliable hose for compressed air and water. Designed for heavy-duty work. High degree of resistance to impact and rough surfaces. Ideal for use in mines, quarries, tunnels, shipyards, etc.

Fits standard claw couplings in diameters less than 51 mm.

Please contact Codan for further information.

Type nr. 1220

Application: Air / Water Hose

Standard Length: 40 metres

Working Temperature: -30°C to 80°C

Inside: SBR/NR

Colour: Black

Reinforcement: Polyester

Outside: EPDM

Colour: Yellow

Standards: BS5118 Type 2

Std. branding: -

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
13,0	22,6	20	60	120	500	1220013000
19,0	29,4	20	60	180	670	1220019000
25,0	36,2	20	60	250	930	1220025000
32,0	45,6	20	60	320	1.300	1220032000
38,0	51,6	20	60	350	1.490	1220038000
51,0	65,4	20	60	500	2.180	1220051000
63,0	77,0	20	60	600	2.610	1220063000
76,0	91,6	20	60	900	3.100	1220076000
90,0	106,0	20	60	1.050	4.700	1220090000
102,0	118,0	20	60	1.150	5.190	1220102000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage

of vulcanised Rubber Products). The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.



Codan Rubber A/S Værkstedvej 45-49, DK-4600 Køge, Denmark Tel. +45 56 64 64 64 Mail: info@codan.com
www.codan.com

16/10/2022