

### DYNAMOMETER

Accuracy higher than 0,2% FS

- Very clear red digit LED display / Visible at long distances and in bright daylight.
- High strength steel / Compact size.
- Silver chrome plated surface.
- Fully serviceable parts.
- Built-in rechargeable batteries.
- Very easy to use.


Capacity: 2t to 120t.  
Available ex. Stock (DK).



D2000A

**Accessory options:**

- Handheld display (2000B-6V-RTX)
- PC datalog software (Dyntag)



### MECHANICAL OVERLOAD SWITCH

Minimal lifting height reduction

- Very compact size (only 150mm length).
- Quick and precise installation with simple tools.
- See visually when the switch is adjusted correctly.
- Mounted on the dead-end of the wire rope.
- Hysteresis max 4% FS.
- The same model can be adjusted to fit different wire types and capacities.
- 5-20 mm wire.


Capacity: 5t.  
Available ex. Stock (DK).



SM4065-N

**Accessory options:**

- 2 limit switches



### ELECTRONIC WEIGHING & OVERLOAD SYSTEM

Clamp-on solution with accuracy ±1% FS & overload protection

- Minimal lifting height reduction / Compact size (down to 100mm length).
- Clamp-on/Does not affect the crane's mechanical construction.
- Quick and easy to install.
- Mounted on the dead end of the wire rope.
- 6-30 mm wire.

Capacity: Up to 10t. on unit x reevings for crane capacity.  
Available ex. Stock (DK).



WT1-N & WT2-N

**Accessory options:**

- Amplifier (OL3000A)
- Remote control (Tiger)
- Local or remote display



### LOAD PINS

Accuracy down to 0,1% FS & overload protection

- Stainless steel construction
- Sealed to IP67
- Easy to install / retrofit
- Low deflection.
- Can be ATEX certified.

Capacity: 0,1t to 1000t.


Designed specifically for our customers requirements as a direct replacement for shackles and other load bearing pins in lifting equipment.



LOAD PINS

**Accessory options:**

- Amplifier (OL3000A)
- Local or remote display



### ELECTRONIC WEIGHING & OVERLOAD SYSTEM

Stainless steel

- Accuracy ±1% FS (can be affected by the wire type).
- Minimal lifting height reduction / Compact size (down to 100mm length).
- Clamp-on / Does not affect the crane's mechanical construction.
- Quick and easy to install.
- Mounted on the dead end of the wire rope.
- 6-30mm wire.

Capacity: Up to 10t. on unit x reevings for crane capacity.

**Accessory options:**

- Amplifier (OL3000A)
- Remote control (Tiger)
- Local or remote display
- Hydraulic hose.



WT1-N-SL & WT2-N-SL

### OFFSHORE DYNAMOMETER

With handheld display

- Aluminium / Compact size.
- The surface is treated with eloxed aluminium.
- Waterproofed to IP66. IP67 as option.
- Cabled and wireless version.
- Very easy to use.

Capacity: 1t to 500t.



D2000E

### LOAD PINS

Accuracy down to 0,1% FS & overload protection

- Waterproofed to IP67.
- Can be ATEX certified.

Developed according to customer requirements for many diverse applications in the marine and offshore industry.



LOAD PINS

