HAND PALLET TRUCK SCALES









RAVAS-1100

FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Totalling with sequence number
- Error messages in display
- Automatic switch-off after 3 minutes of non-use
- Low battery warning in display

STANDARD SPECIFICATIONS

 Weighing capacity 	2,000 kg	
 Graduation 	1 kg	
 Max. inaccuracy 	0.1% of the load lifted	
Display	LCD, digit height 18 mm	
 Keypad 	3 function keys, on/off key	
 Protection class 	load cells IP67, indicator IP65	
 Steering wheels 	rubber	
 Loading wheels 	polyurethane, tandem	
Colour	red (RAL 3000), epoxy painted	
 Own weight 	104 kg	
 Power supply 	4 x 1.5V AA-batteries	
Battery life	when used 5 times a day, the batteries last for a year	
Pump	quick lift	

DIMENSIONS IN MM



Α	Fork length	1150
в	Fork width	180
с	Minimum fork height	85
D	Maximum fork height	200
Е	Width over forks	555
F	Height to top indicator	600

OPTIONS*

- Built-in thermal printer
- Legal for trade version up to 2000 divisions, OIML III

* The use of options may change related specifications

TÜVRheinla

CE

ISO 9001:2008 ISO 14001:200

RAVAS Europe B.V.

P.O. Box 2023, NL-5300 CA Zaltbommel, The Netherlands T. +31 (0)418 51 52 20, F. +31 (0)418 51 53 20 backoffice@ravas.com, www.ravas.com

