



CADIS

Roll Over Wash Unit

Our CADIS models are powerful, next-generation roll over wash units. Select a tailor-made solution for your site from two design lines and a comprehensive range of equipment options.

The CADIS models have been specially designed to meet the particular requirements of gas stations and wash centres and the basic equipment version is also designed for car dealers.

Your customers will love the impressive washing experience and the modern, timeless design. CADIS produces the lowest possible noise emission while maintaining a high throughput performance (low emission, high performance).

Its compact outer dimensions and large wash width ensure a comprehensive performance. We guarantee you low costs, maximum revenue and reliability.

Highlights:

- 15% increased drying performance
- Contour-following wash with horizontal highpressure
- XL-wheel wash device
- Increased brush diameter
- VISUS display
- Compact outer dimensions
- OPTIFLEX-inclined position of the lateral brushes



STRIPE design line:

- An attractive design, even in the basic equipment version
- The STRIPE colour can be chosen from the range of Christ accent colours to suit your site
- Positioning device (FORWARD, STOP, BACK)
- Wash cycle indication

BLADE design line:

- Premium design line
- The BLADE colour can be chosen from the range of Christ accent colours to suit your site
- VISUS display







Power from all sides

High pressure prewash

- Wheel high pressure prewash with two or four rotating nozzles
- Lateral high pressure prewash with four or six rigid nozzles

Extension:


• Contour-following wash with horizontal high pressure







- 1. BLADE lights up as an advanced style element
- Brand characteristic of Christ wash systems, high recognition value
- 2. Double-sided VISUS displays
 - Easy light positioning for the wash customer, display of wash cycles
- **3. Traction drives and drives for brushes with worm gear**Quiet operation of traction drives and drives for brushes
- 4. Up to six types of chemical/wax with foam cartridge Capacity of 11 litres, dosing pumps with stroke adjustment



15% more power

Flow-optimised drying system

- SILENT-drying system
- Wider XL horizontal blower
- Specially designed for light commercial vehicles and SUVs
- Lateral blower drying height: 1750 mm

Available as an option:

- Fly-In drying
- \bullet Swivelling of 30° in the rear area



| Improved wash result

Our recommended options



Season chemistry
Dissolves insects



High-pressure wheel sill wash device Main soiling is removed



Rim chemistry spray systemFor an optimal rim cleaning result



Swivelling underbody wash device Optional: extendable via segments



Moveable underbody wash deviceWith length measurement and lower water consumption



STANDARD lateral splash protection


• Textile for clean and dry wash bay walls

PREMIUM lateral splash protection


- Solid plastic guard for clean hall walls
- Easy cleaning thanks to smooth surfaces

Design meets efficiency

+45% machine capacity



Thanks to optimised program sequences and the Vitesse option, CADIS increases machine capacity by up to 550 washes.



Operation terminal TOUCH POS:

TOUCH POS with lighting

- Modern user interface
- 10.1 inch touchscreen user interface
- Ideal for drive-in operation
- Choice of accent colour

Self-service variants:

- Transponder card reader
- PIN code system
- Barcode scanner
- Integrated bank card terminal



Foot installation

Further models can be found in the operating systems brochure

CADIS

Technical expertise



Highlights - trimming for the wash:

- Increased brush diameter
- Optimised immersion depth for a better wash result
- 1/3 higher density of trimming
- Better wash performance

Specially coordinated wash materials:

 ${\tt POWERBRUSH+|SENSOFIL+|MICROMIX+}$

Available wash material colours:

| RAL 7021 black grey

RAL 7037 dusty grey

| RAL 650-M Christ standard

RAL 5015 sky blue

| RAL 5002 ultramarine blue

| RAL 6024 traffic green

| RAL 6018 yellow green

| RAL 3000 flame red



Optimum functional dimensions

Area	Values	Notes
Machine height	3040 mm	Vehicle height 2300 mm
Machine width	3500 mm	
Vehicle width	2550 mm	in the mirror zone
Vehicle height	2100 mm – 3100 mm	In 100 mm increments
Track width of wheel guiding tubes	2050 mm 2100 mm	travelling track width of 2500 mm travelling track width of 2800 mm with/without get out interruption
Track width of guide rails	2500 mm	track width
(Optional: Available in stainless steel)	2800 mm	track width

BLADE

VISUS display



The vehicle shown adapts to the required accent colour.

Accent colours

STRIPE and BLADE

STRIPE
RAL 7021 black grey
RAL 7037 dusty grey
RAL 9010 pure white
RAL 650-M Christ standard
RAL 5015 sky blue
RAL 5002 ultramarine blue
RAL 6024 traffic green
RAL 6018 yellow green
RAL 3000 flame red
RAL 2009 traffic orange
RAL 1023 traffic yellow

r	non-illumino	ited
ĺ	RAL 7021	black grey
ĺ	RAL 7037	dusty grey
	RAL 9010	pure white
	RAL 650-	M Christ standard
	RAL 5015	sky blue
	RAL 5002	ultramarine blue
i	RAL 6024	traffic green
i	RAL 6018	yellow green
	RAL 3000	flame red
	RAL 2009	traffic orange
	RAL 1023	traffic yellow

BLADE Standard

BLADE PREMIUM	BLADE PREMIUM+
illuminated	multicolour
RAL 9010 pure white	illuminatino,
RAL 650-M Christ standard	switchable between:
RAL 5015 sky blue	White
RAL 5002 ultramarine blue	Blue
RAL 6024 traffic green	Green
RAL 6018 yellow green	Red
RAL 3000 flame red	Cyan
RAL 2009 traffic orange	Yellow
RAL 1023 traffic yellow	Magenta

Everything from a single source

...from Christ Wash Systems


over 140 years of family tradition

over 20,000 active installations worldwide

Certificates:

Safety, quality, environment

69 distributors, including 8 subsidiaries



> 97 %* satisfied service customers > 97%* in-house service and > 98%* guaranteed plant installation technicians

engineering availability

> 95%* first-time fix rate

* Germany



