

# Specifications

## Material

- » Microsurfaced impact acrylic

## Finish

- » Matte non-glare

## Sheet Size

- » 24" x 48" + .062" (610mm x 1219mm)

## Thickness 3-ply

- » 1/16" (1.6mm)

## Engraving Method

- » Laser
- » Rotating carbide

## Usage

- » Interior Signage
- » Exterior Signage
- » Illuminated Wayfinding
- » Personal Identification
- » Equipment ID Tags
- » Safety Signage
- » Recreational Signage

## Engraving Depth

- » First Layer (Foil) - .003"-.004"
- » Second Layer (Cap) - .008"-.010"

## Fabrication

- » Saws
- » Drills
- » Shears
- » Laser Vector Cuts
- » Bevels
- » Heat Bendable
- » Screen Prints
- » Hot Stamps
- » Bonds
- » Permits Fine Engraving

Visit [rowmark.com](http://rowmark.com) for Rowmark's complete line of products for rotary engraving, laser engraving and sublimation.

Find answers to all your questions in the Technical Help section. Be sure to check out support tools under the Sales Tools and Downloads sections.

To request a sample or promotional literature, please call 1-877-ROWMARK (419-429-3160) or email [samples@rowmark.com](mailto:samples@rowmark.com). For technical assistance, call 1-877-ROWMARK (419-429-3160), visit [www.rowmark.com](http://www.rowmark.com) or email [inquiries@rowmark.com](mailto:inquiries@rowmark.com).

Can't find exactly what you're looking for? Contact us to learn more about our custom capabilities. Also, be sure to check out the Varsity Collection page at [www.rowmark.com](http://www.rowmark.com). Contact your authorized Rowmark distributor or speak with one of our customer service specialists at 1-800-243-3339 (419-425-2407).



## LaserMax® Tri-Layer Sign Kit

Fabricate the LaserMax® Tri-Layer Sign Kit by downloading the file found under the downloads section of our website at [www.rowmark.com](http://www.rowmark.com).



**Rowmark**

[rowmark.com](http://rowmark.com) / 1.877 ROWMARK / [samples@rowmark.com](mailto:samples@rowmark.com)



The Rowmark product and engineering teams developed this revolutionary tri-layer sheet to help customers increase fabrication speed by eliminating secondary processes such as paint filling or additional lamination.



**TL923-264**  
White/Red/  
Black

**TL923-764**  
Yellow/Red/  
Black

**TL923-274**  
White/Yellow/  
Black

**TL923-254**  
White/Blue/  
Black

**TL923-942**  
Green/Black/  
White