

The Miko Anchor Magnets form a series of powerful and robust underwater fixing points. With holding forces ranging from 90 kg to 2 000 kg, these magnets are used worldwide for a wide range of applications.

The magnetic component consists of neodymium which is coated with epoxy to improve its corrosion resistance in sea water.

MAM-00X is the strongest Miko Anchor Magnet with a holding force of 2 000 kg\*. Applications might include the temporary fastening of oil booms, large fenders or mooring lines to ship sides and other steel structures.

The magnet is equipped with a mooring lug and rotating lever for easy release and safe operation.



All Miko magnets are shipped in a double-skin steel box to isolate the magnetic field and to prepare them for air freight. MAM-005 is also shipped with a keeper disk for further shielding.

## CHARACTERISTICS

**Holding Force**      **Gross Weight (Box)**  
2 000 kg \*            31 kg

**Footprint**            **Quantity in Box**  
319 x 180 mm        1 pcs

**Net Weight**  
18 kg

## CONTACT

Miko Marine AS  
P.O. Box 1534 Vika  
N-0117 Oslo  
Norway

Website: [www.mikomarine.com](http://www.mikomarine.com)  
E-mail: [info@mikomarine.com](mailto:info@mikomarine.com)  
Telephone: +47 46 90 50 00

Read "IMPORTANT NOTES ABOUT MIKO MAGNETS" enclosed in each box before use.

\*Refers to the perpendicular holding force when applied directly onto a clean mild steel plate of minimum thickness 30 mm.



[www.mikomarine.com](http://www.mikomarine.com) | [info@mikomarine.com](mailto:info@mikomarine.com) | +47 46 90 50 00