

Superwool Plus Blanket

Høytemperatur isolering 1200°C



Superwool Plus på rull	
Temperatur °C	1200
Tetthet (kg/m ³)	128
Termisk ledningsevne (W/m.K)	0,03
Rull. Bredde x lengde x tykkelse	0,61m x 14,64m x 13mm



Seal Weld Pro AS

Nikkelveien 11,

4313 Sandnes

E-mail: firmapost@swp.no

Tlf: 51575340



SWP number: SPB-13-01
 Superwool 128kg/m³ 0,61mx14,64m/13mm

Description: Superwool plus blanket

Application:

Welding heat treatment thermal insulation blanket & valves, heat preservation and heat insulation pipe set- inner n

Characteristic	Unit	Data	
Temperature	C	1200	
Density	kg/m ³	≤2 (1100°C)	
Thermal conductivity	W/m.K	200°C	0.06
		400°C	0.10
		600°C	0.17
		800°C	0.26
		1000°C	0.38
Chemical Composition	%	SiO ₂	62-68
		CaO	26-32
		MgO	3-7
		Al ₂ O ₃	
		ZrO ₃	
		Cr ₂ O ₃	
		SiO ₂ +Al ₂ O ₃	
		ZrO ₂ +SiO ₂ +Al ₂ O ₃	
		Fe ₂ O ₃	
		Na ₂ O+K ₂ O	
		Other	<1
Measure roll		Length 14,64m Width 0,61m Height 13mm	



Seal Weld Pro AS

Nikkelveien 11,
 4313 Sandnes

E-mail: firmapost@swp.no

Tlf: 51575340