

Wall box for electric vehicles

JUICE CHARGER 2



JUICE CHARGER 2 is an intelligent wall charging station with up to 22 kW charging power.

Identification, activation, control and billing. With an integral RFID reader and JUICE extras, JUICE CHARGER 2 has every option covered.


juice
CHARGER 2

www.juice-technology.com

JUICE CHARGER 2 - The most attractive wall box in the world



Extremely simple to use
with an optional high-resolution touchscreen display.

Calibrated electricity meter

is the perfect solution for clean billing and use in the public domain.



Robust

The robust chrome steel housing is weather-resistant and provides optimum protection for the technology inside.

Integral residual current detection

DC and AC fault detection trips effectively at the specified value.

Residual current circuit breaker

Integral protection from DC and AC faults means you don't have to fit an expensive RCD Class B device at home. This can save you up to 1,000 Euros/Swiss francs in extra costs and labour.

With a cable length of over 3 m
it will still reach your car, even if your parking skills leave something to be desired.



No induction loop

And no tangled or trailing cables thanks to a clever cable attachment system.

Easy payment

with the option to use all standard payment methods, and all regular credit card - of course.



Plug store

to ensure that charging plugs stay dry and dust-free

Compatible

with all electric vehicles with a Type 2 or Type 1 connector.

Ultra-intelligent

A smart module for the smartJUICE charging and charge management system is already included in JUICE CHARGER 2.



More information about smartJUICE
www.juice-technology.co/solutions

Timeless design

JUICE CHARGER 2 adds a touch of elegance and class to any wall. Its appeal is primarily due to the simple, pared-down design. The high-quality chrome steel is robust and non-flammable, requiring no maintenance.

Good to know

JUICE CHARGER 2 comes in three different basic models.

Fix



Fix model

The classic model, installed in situ.

Flex model

so you can take the Integral JUICE BOOSTER with you on your travels.



Flex

Flat

Flat model

the housing for JUICE BOOSTER 2 if you already have this product.



JUICE CHARGER 2 – Incredibly good wall-mounted solution



Consistently successfully tested
Guaranteed compatibility: compatible with all existing and new electric vehicles on the market with a Type 2 or Type 1 connector.



Robust
Highly durable chrome steel housing, weatherproof (splash-proof and dust proof).



Lightning fast installation
A choice of standard fixings, integral levelling, robust quick connectors.



For more information and accessories, please see www.juice-technology.co/juice-charger

Technical specifications

Dimensions	Height 750 mm, width 230 mm, depth 150 mm, cable length 3 m
Weight	approx. 8 kg (depending on the model)
Input current	230 V 6–32 A (single phase) or 400 V 6–32 A (3-phase) AC
Power output	1.4 – 22.0 kW AC depending on input current

CE conformity	IEC 62752, 62196, 61851 – Mode 3, EMV, RoHS
Protection class – RCD – IP67 – RCD DC 6mA, AC/DC 30mA – protection	Protective earth conductor monitoring
Vehicle-end connector	Type 2 (EN 62196) , , also available with with a Type 1 or Type 2 socket, or both on request.
Material/colour	1.5 mm brushed chrome steel, silver Black cable