
Single Core Conductor BETAtherm® 155 UL/cUL (metric)

BETAtherm® 155 UL/cUL is a flexible low-voltage cable with UL recognition, consisting of a tinned copper stranded wire and insulated with coloured electron-beam crosslinked polyolefine copolymer.

Attributes

Due to its electron-beam cross-linked insulation, BETAtherm® 155 UL/cUL achieves a special thermal resistance required for Class F. This results in excellent thermal resistance. However, it cannot even be melted at elevated temperatures and has to be skinned during processing. Skinning is simple and also possible at machines.

BETAtherm® cables are resistant to common insulating varnishes. They are flame retardant.

Application

BETAtherm® 155 UL/cUL is suitable for the internal wiring of electric machines, lamps, heating appliances, as well as for application in apparatus, mechanical and plant engineering.

Due to the high thermal load capacity, it might be possible to reduce the conductor cross section and, therefore, save space and reduce the weight.

Standards

- Thermal class F (155 °C / UL-rating 150 °C)
- RoHS compliant according to 2011/65 EC
- UL AWM Style 3289, cUL CL 1503 (valid from 0.50 mm²)

Delivery forms

Metric dimensions

| mm ² | rings / m |
|-----------------|-----------|
| 4.0-10.0 | 100 |
| 16.0-25.0 | 50 |
| 35.0-95.0 | 25 |

Conductor

Tinned copper wire VDE 0295/ IEC 60228 class 5.

The dimensions specified in the technical datasheet are regarded as standard values. The actual cross sections may vary. The cables are manufactured according to European standards with a metric conductor cross section, AWG sizes

are approximate values and viceversa.

Always observe relevant standards valid for divergent operating conditions when laying for greater limit current loads.

Color

Green-yellow, black, light blue, red, yellow, green.

Brown, white, grey, violet, orange and 2-coloured on request.

| Dimension | Unit of measure | | | | | | |
|------------------------|-----------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| Nominal cross section | mm ² | 0.25 | 0.5 | 0.75 | 1.00 | 1.5 | 2.5 |
| Strands x diameter | mm | 14 x 0.15 | 16 x 0.20 | 24 x 0.20 | 32 x 0.20 | 27 x 0.25 | 45 x 0.25 |
| Cu Litz nom. diameter | mm | 0.65 | 0.90 | 1.15 | 1.25 | 1.55 | 2.05 |
| Wall thickness desired | mm | 0.85 | 0.85 | 0.85 | 0.85 | 0.85 | 0.85 |
| Wall thickness UL min | mm | 0.686 | 0.686 | 0.686 | 0.686 | 0.686 | 0.686 |
| Outer diameter | mm | 2.35 ± 0.10 | 2.60 ± 0.10 | 2.85 ± 0.10 | 2.95 ± 0.10 | 3.25 ± 0.20 | 3.75 ± 0.20 |
| Thermal load | kWh/m | 0.044 | 0.052 | 0.059 | 0.062 | 0.072 | 0.087 |

| Dimension | Unit of measure | | | | | | |
|-----------------------|-----------------|--------------|--------------|--------------|---------------|---------------|---------------|
| Nominal cross section | mm ² | 4 | 6 | 10 | 16 | 25 | 35 |
| Strands x diameter | mm | 52 x 0.30 | 78 x 0.30 | 74 x 0.40 | 119 x 0.40 | 181 x 0.40 | 257 x 0.40 |

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 05/24

BETAtherm® is a registered trademark of Leoni Studer AG.



Product datasheet

Single Core Conductor BETAtherm® 155
 UL/cUL (metric)
 Page 4

SynFlex Elektro GmbH
 Auf den Kreuzen 24
 D-32825 Blomberg Germany
 Telefon +49-5235-968-0
 E-Mail info@synflex.de



| Dimension | Unit of measure | | | | | | |
|------------------------|-----------------|-------------------|-------------------|-------------------|-------------------|-------------------|--------------------|
| Cu Litz nom. diameter | mm | 2.55 | 3.10 | 4.10 | 5.0 | 6.20 | 7.70 |
| Wall thickness desired | mm | 0.85 | 0.85 | 1.30 | 1.70 | 1.70 | 1.70 |
| Wall thickness UL min | mm | 0.686 | 0.686 | 1.041 | 1.372 | 1.372 | 1.372 |
| Outer diameter | mm | 4.25 ± 0.20 | 4.80 ± 0.20 | 6.70 ± 0.30 | 8.40 ± 0.30 | 9.60 ± 0.30 | 11.10 ± 0.40 |
| Thermal load | kWh/m | 0.103 | 0.120 | 0.247 | 0.398 | 0.469 | 0.579 |

| Dimension | Unit of measure | | | | |
|------------------------|-----------------|---------------|---------------|---------------|----------|
| Nominal cross section | mm ² | 50 | 70 | 95 | 120 |
| Strands x diameter | mm | 371 x 0.40 | 336 x 0.50 | 444 x 0.50 | 570x0.50 |
| Cu Litz nom. diameter | mm | 9.70 | 11.20 | 12.8 | 14.6 |
| Wall thickness desired | mm | 2.20 | 2.30 | 2.30 | 2.2 |
| Wall thickness UL min | mm | 1.829 | 1.829 | 1.829 | 1.829 |

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 05/24

BETAtherm® is a registered trademark of Leoni Studer AG.



Product datasheet

Single Core Conductor BETAtherm® 155
 UL/cUL (metric)
 Page 5

SynFlex Elektro GmbH
 Auf den Kreuzen 24
 D-32825 Blomberg Germany
 Telefon +49-5235-968-0
 E-Mail info@synflex.de



| Dimension | Unit of measure | | | | |
|----------------|-----------------|--------------|--------------|--------------|-------------|
| Outer diameter | mm | 14.10 ± 0.40 | 15.80 ± 0.40 | 17.40 ± 0.40 | 19.0 ± 0.40 |
| Thermal load | kWh/m | 0.961 | 1.146 | 1.269 | 1.358 |

| Mechanical | Values |
|----------------------|--------------------|
| Bend radius | 4 x outer diameter |
| Soldering resistance | very good |

| Thermal | Unit of measure | Conditions | Values | Test method |
|-------------------------------------|-----------------|-------------|-----------------|--------------------|
| Thermal class | | | F | |
| Temperature range fixed application | °C | | -55 bis +150 | UL 3289 / cUL 1503 |
| Temperature range short circuit | °C | max. 5 sec. | +280 | |
| Thermal resistance | | | 155 °C / 5000 h | IEC 60216-2 |

| Chemical | Values |
|------------|--|
| Insulation | Polyolefine copolymer electron beam cross-linked |

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 05/24

BETAtherm® is a registered trademark of Leoni Studer AG.



| Chemical | Values |
|--------------------|--------------------------------------|
| Resistance against | resistant against common impregnants |

| Electrical | Unit of measure | Conditions | Values |
|-----------------|-----------------|----------------|-------------------------------|
| Rated voltage | V | | U ₀ /U 600/1000 AC |
| Testing voltage | V | 50 Hz / 2 min. | 3500 |

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.
 Updated 05/24

BETAtherm® is a registered trademark of Leoni Studer AG.

