

Syrefast kamstål / Armeringsstål



Kamstål / Armeringsstål i syrefast utførelse for bruk i fundamenter, broer og som tekniske bolter i tunneler. Dette materialet bør anvendes til nybygg og renoveringsoppgaver i aggressivt miljø.

Lagerprogram:

Ø12x5850 vekt 5,32 kg

Ø16x5850 vekt 9,25 kg

Ø20x5850 vekt 14,45 kg

Ø25x5850 vekt 22,53 kg

Kappes, bøyes og gjenges etter behov.

Teknisk informasjon:

Bolt: Kamstål, mekaniske egenskaper i samsvar med B500NCR iht. NS 3576-5:2012

Material kval. 1.4404 (AISI 316L iht EN 10088-1:2005 og 10088-5:2005)

Dimensjon:	Spenningsareal mm ² , A _s	Flyt, ReH N/mm ² Min:	Brudd, Rm N/mm ² f _u	Duktilitet, Agt % min
Ø12	113	500	600-650	8
Ø16	201	500	600-650	8
Ø20	314	500	600-650	8
Ø25	491	500	600-650	8

Tilbehør:

Ved gysing: Fjær for sentrering og holding i borehull, anbefales.

Kan også leveres med påsatt blandefjær for montering med polyester i store borehull.

Stainless steel rebar



Stainless steel rebar for use in foundations, bridges and as a technical bolt in tunnels. This material should be used for new builds and renovations in aggressive environments.

Stock programme:

Ø12x5850 Weight 5,32 kg

Ø16x5850 Weight 9.25 kg

Ø20x5850 Weight 14.45 kg

Ø25x5850 Weight 22.53 kg

Cut, bent and threaded to meet requirements.

Technical information:

Bolt: Rebar, mechanical properties in accordance with B500NCR compliant with NS 3576-5:2012

Material quality: 1.4404 (AISI 316L compliant with EN 10088-1:2005 and 10088-5:2005)

Dimensions:	Tension area mm ² , A _s	Yield, ReH N/mm ² Min:	Tensile, Rm N/mm ² f _u	Ductility, AGT % min
Ø12	113	500	600-650	8
Ø16	201	500	600-650	8
Ø20	314	500	600-650	8
Ø25	491	500	600-650	8

Accessories:

With grouting: Spiral for centering and holding in the borehole recommended.

Can be supplied with mixing spiral fitted for insertion with polyester in large boreholes.