


**Ethernet Spanner**  
Master to master data exchange, NAT router, 16 digital PNP inputs  
**TBEN-L5-EN1**



- Two separate, electrically isolated Ethernet interfaces
- Bi-directional data exchange between two networks
- Protocol conversion between Ethernet/IP™, Modbus® TCP and Profinet®
- Profinet® is supported on P2 Ethernet port
- 1:1 NAT router
- Integrated Ethernet switch
- 10 Mbps/100 Mbps supported
- 2 × M12, 4-pin, D-coded, Ethernet-fieldbus connection
- Glass fiber reinforced housing
- Shock and vibration tested
- Fully potted module electronics
- Protection classes IP65, IP67, IP69K
- 7/8" connector for power supply, 5-pin
- Input diagnostics per port

<b>Type designation</b>	TBEN-L5-EN1
Ident no.	6814035
<b>Supply</b>	
Supply voltage	24 VDC
Admissible range	18...30 VDC
	Total current max. 9 A per voltage group V1
Voltage supply connection	5-pin male 7/8" connector X1
Sensor/Actuator supply V <sub>AUX1</sub>	supply of ports C0-C7 from V1
	short-circuit proof, 120 mA per port
Electrical isolation	galvanic isolation of the voltage groups V1 and V2, voltages up to 500 VAC
<b>System data</b>	
Fieldbus transmission rate	10 Mbps/100 Mbps
Fieldbus connection technology	2 × M12, 4-pin, reverse-keyed
Web server	default: 192.168.1.254
Service Interface	Ethernet via P1
<b>Modbus TCP</b>	
Addressing	Static IP, BOOTP, DHCP
Supported function codes	FC1, FC2, FC3, FC4, FC5, FC6, FC15, FC16, FC23
Number of TCP connections	8
<b>EtherNet/IP™</b>	
Addressing	acc. to EtherNet/IP™ specification
Number of CIP connections	3
<b>Digital inputs</b>	
Number of channels	16
Connectivity inputs	M12, 5-pin
Input type	PNP
Type of input diagnostics	group diagnostics
Switching threshold	EN 61131-2 Typ 3, PNP
Low level signal voltage	< 5 V
High level signal voltage	> 11 V
Low level signal current	< 1.5 mA
High level signal current	> 2 mA
Input delay	2.5 ms
Potential separation	galvanic isolation to P1/P2, voltages up to 500 VDC
<b>Standard/Directive conformity</b>	
Vibration test	acceleration to 20 g acc. to EN 60068-2-6
Shock test	acc. to EN 60068-2-27
Drop and topple	acc. to EN 60068-2-31/IEC 60068-2-32
Electro-magnetic compatibility	acc. to EN 61131-2
Approvals and certificates	CE

## Ethernet Spanner

Master to master data exchange, NAT router, 16 digital PNP inputs

### TBEN-L5-EN1

---

**General Information**


Dimensions (W x L x H)	60.4 x 230.4 x 39mm
Operating temperature	-40...+70 °C
Storage temperature	-40...+85 °C
Altitude	max.5000 m
Protection class	IP65 IP67 IP69K
MTTF	205 years
Housing material	PA6-GF30
Housing color	Black
Window material	Lexan
Material screw	303 stainless steel
Material label	Polycarbonate
Halogen-free	yes
Mounting	2 mounting holes □ 6.3 mm

---

**Note on the type designation:**




TBEN-L5-EN1 and TBEN-L1-EN1 are identical types of devices and have the same ID number!

**Ethernet Spanner**  
**Master to master data exchange, NAT router, 16 digital PNP inputs**  
**TBEN-L5-EN1**






**Note**  
 P1: External network  
 P2: Local network  
 Ethernet cable (example):  
 RSSD-RSSD-441-2M / S2174  
 ID number 6914218

M12 x 1 Ethernet




**Note**  
 Actuator and sensor cable/PUR cable (example):  
 RKC4.4T-2-RSC4.4T/TXL  
 ID number 6625608  
 Y extension cable for single occupancy  
 FSM4-2WAK3-1/1/P00  
 ID number 8009560

M12 x 1 Input



**Note**  
 Power supply cable (example):  
 RKM52-1-RSM52  
 ID number 6914149

7/8" Power Supply



**Ethernet Spanner**  
**Master to master data exchange, NAT router, 16 digital PNP inputs**  
**TBEN-L5-EN1**

**Module LED Status**

LED	Color	Status	Description
ETH1 / ETH2	Green	ON	Ethernet link (100 Mbps)
		flashing	Ethernet communication (100 Mbps)
	Yellow	ON	Ethernet link (10 Mbps)
		flashing	Ethernet communication (10 Mbps)
		OFF	No Ethernet link
BUS	Green	ON	Active connection to a master
		flashing	Ready
	Red	ON	Network error or Restore Mode or Modbus timeout
		flashing	Blink/Wink command active
		OFF	Power off
ERR	Green	ON	Diagnostics disabled
	Red	ON	Diagnostics enabled V <sub>2</sub> undervoltage diagnosis is parameter-dependent
PWR	Green	ON	Power supply V <sub>1</sub> OK
		OFF	V <sub>1</sub> power off or below defined tolerance of 18 V

**LED Status I/O**

LED	Color	Status	Description
LED 0 ... 15	Green	ON	Input active
		flashing	Power overload at the corresponding port. Both port LEDs are flashing.
		OFF	Input inactive

# Ethernet Spanner

## Master to master data exchange, NAT router, 16 digital PNP inputs

### TBEN-L5-EN1

#### Process Data Mapping of the Single Protocols

For more details on the corresponding protocols see manual.

#### Modbus TCP Register Mapping

The address ranges are valid for both networks.

	Reg	Bit 15	Bit 14	Bit 13	Bit 12	Bit 11	Bit 10	Bit 9	Bit 8	Bit 7	Bit 6	Bit 5	Bit 4	Bit 3	Bit 2	Bit 1	Bit 0	
Inputs (RO)	0x0000	DI15 C7P2	DI14 C7P4	DI13 C6P2	DI12 C6P4	DI11 C5P2	DI10 C5P4	DI9 C4P2	DI8 C4P4	DI7 C3P2	DI6 C3P4	DI5 C2P2	DI4 C2P4	DI3 C1P2	DI2 C1P4	DI1 C0P2	DI0 C0P4	
Status (RO)	0x0001	-	FCE	SPE1	SPE2	CFG	COM	V1	-	V2	-	-	-	-	-	-	Diag Warn	
Diag (RO)	0x0002	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	I/O Diag	
Spanner Input Data (RO)	0x3000 - 0x30FF	256 Bytes																
Spanner Output Data (WR)	0X3400 - 0x34ff	256 Bytes																
I/O Diag (RO)	0xA000										SCS7	SCS6	SCS5	SCS4	SCS3	SCS2	SCS1	SCS0

#### EtherNet/IP™ data mapping with activated scheduled diagnostics, default settings

The address ranges are valid for both networks.

	Word	Bit 15	Bit 14	Bit 13	Bit 12	Bit 11	Bit 10	Bit 9	Bit 8	Bit 7	Bit 6	Bit 5	Bit 4	Bit 3	Bit 2	Bit 1	Bit 0	
Input data (station -> scanner)																		
GW status	0	-	FCE	SPE1	SPE2	CFG	COM	V1	-	V2	-	-	-	-	-	-	Diag Warn	
Inputs	1	DI15 C7P2	DI14 C7P4	DI13 C6P2	DI12 C6P4	DI11 C5P2	DI10 C5P4	DI9 C4P2	DI8 C4P4	DI7 C3P2	DI6 C3P4	DI5 C2P2	DI4 C2P4	DI3 C1P2	DI2 C1P4	DI1 C0P2	DI0 C0P4	
Diag 1	2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	I/O Diag	
Diag 2	3										SCS7	SCS6	SCS5	SCS4	SCS3	SCS2	SCS1	SCS0
Spanner	4-132	256 bytes data exchange																
Output data (scanner -> station)																		
	0-3	reserved																
Spanner	4-132	256 bytes data exchange																

#### PROFINET process data

	Byte	Bit 7	Bit 6	Bit 5	Bit 4	Bit 3	Bit 2	Bit 1	Bit 0
Inputs	0	DI7 C3P2	DI6 C3P4	DI5 C2P2	DI4 C2P4	DI3 C1P2	DI2 C1P4	DI1 C0P2	DI0 C0P4
	1	DI15 C72	DI14 C7P4	DI13 C6P2	DI12 C6P4	DI10 C5P2	DI9 C5P4	DI8 C4P2	DI7 C4P4

Key:

DIx	Digital input channel x	CFG	I/O configuration error
DOx	Digital output channel x	FCE	I/O-ASSISTANT Force Mode active
Cx	Port x	I/ODiag	I/O diagnostics connected
Px	Pin x	SchedDiag	Manufacturer-specific diagnostics configured and active
DiagWarn	Diagnostic at least on 1 channel	SCSx	Short-circuit at port x
V1	Undervoltage V1	SCG1	Short-circuit supply ports C0-C3
V2	Undervoltage V2	SCG2	Short-circuit supply ports C4-C7
COM	Communication error on internal module bus	SCOx	Short-circuit output channel x
SPEx	Spanner port active		