



Variable throat widths and machining angles



Wide, rigid box ways on Z and Y-axes

- infinitely variable speeds
- head swivels $\pm 90^\circ$ to the right and to the left
- TV 1000 table feed in X and Y, infinitely variable with rapid feed
- coolant system
- chip tray
- central lubrication
- pneumatic tool clamping

Specifications

MF 5 VP

| Working Area | |
|--|---------------------------|
| Table size | mm 1.370x250 |
| Table load capacity (max.) | kg 350 |
| Travels | |
| X / Y / Z-axis travel | mm 800 x 390 x 380 |
| Vertical Milling Head | |
| Speed range, infinitely variable | rpm 70 - 3.600 |
| Spindle mount | ISO 40 |
| Quill stroke | mm 127 |
| Feed | |
| Quill feeds | mm/R (3) 0,04; 0,08; 0,15 |
| Drive Capacity | |
| Motor rating main drive | kW 3,75 |
| Supply voltage | V 400 |
| Measures and Weights | |
| Overall dimensions (length x width x height) | m 2,54x2,16x2,24 |
| Weight | kg 1.590 |
| Part No. | 301217 |

Standard Equipment

3-axis position indicator, table feed TV 1000 in X- and Y-axis, pneumatic tool clamping, chip tray, coolant system, central lubrication, horizontal guideway cover, operating tools, operator manual

Options

Part No.

| | |
|---------------------------------|--------|
| • Accessory-Set ISO 40 5-pc. | 104596 |
| • Divider ST 130 | 110960 |
| • Hydraulic Machine Vise HS 125 | 125024 |

For additional options for this machine, visit our website and search for MF 5 (Product Search)