PROFIBUS measuring and diagnostic tool PB-QONE



Indu-Sol GmbH - Specialist in Industrial Networks







ETHERNET













Indu-Sol GmbH Blumenstrasse 3 04626 Schmoelln

Telephone: +49 (0) 34491 5818-0 Telefax: +49 (0) 34491 5818-99

Email: info@indu-sol.com Homepage: www.indu-sol.com

PROFIBUS-tester PB-Q^{ONE}

Art. No.: 110010050

The PROFIBUS-tester PB-Q^{ONE} is a measuring and diagnostic tool that was developed especially for commissioning and factory acceptance tests, maintenance and service as well as troubleshooting in PROFIBUS networks. Its ease of use and clear evaluation of measuring results allow to reliably evaluate the state of the physical and logical transmission quality in the network.

With the PROFIBUS-tester PB-QONE measuring the transmission levels of the slaves in operation can be physically evaluated and displayed by a measurement bar chart as well taking into account the 7V-drivers of modern PROFIBUS-devices. The levels of the bars infer a measure of the physical transmission quality. Which includes an evaluation of the differential voltage, rising edges and the transient



response. As a result all capacitive, inductive and resistive effects become visible.

Highlights

- Ease of use, well-structured handling
- Simplified topology illustration with measuring site management
- Well-structured, editable report to process further in *.pdf or *.doc format
- Measuring results within seconds
- Simple evaluation through traffic light function

Application example topology plan

Diagnosis

	Measuring Points		
	Measured	1 of 1	
Overall Rating	Measurement at measuring point	Device (Address: 2) - Port 1	
	Date	07/04/2017	
	Timestamp	14:18:40	
	Duration	0:00:22.4699081	
Bus Physics	Quality values		
	Worst Quality Value	1500	
	Best Quality Value	1500	
	Critical Quality Value	2,500 1	
	Number of nodes below critical quality value	0	
	Number of unmeasured nodes (timeout)	0	
Bus Communication	Protocol Analysis		
	Baud Rate	3 Mbit/s	
	Bus Cycle Time (min/max)	0 ms / 0 ms	
	Number of received frames	31	
	Number of sent frames	31	

Quality values











