

# CONNECTORS OVERVIEW



REIMAGINING CONNECTIVITY  
TOGETHER

**fischer**<sup>®</sup>  
CONNECTORS

# CONNECTORS OVERVIEW



**BRASS**



ANY SIZE  
ANY CONFIGURATION  
ANY APPLICATION



**STAINLESS STEEL**



HIGH CORROSION RESISTANCE  
EASY DECONTAMINATION  
EASY HANDLING



**ALULITE**



ULTRALIGHT  
RUGGED  
HIGHLY CONFIGURABLE



**PLASTIC**



EASY TO USE  
DURABLE  
LIGHTWEIGHT



**DISPOSABLE**



COST-EFFECTIVE  
EASY TO USE  
MODULAR



**BROADCAST<sup>1)</sup>**



THE BEST OF TRIAX  
RUGGED  
FOR OUTDOOR USE



**ULTIMATE**



RUGGED  
COMPACT  
LIGHTWEIGHT



**FIBEROPTIC**



ROBUST  
OPTICAL PERFORMANCE  
EASY CLEANING



**MINIMAX**



HIGH-DENSITY MINIATURIZATION  
HIGH-SPEED DATA TRANSFER  
RELIABILITY



**FREEDOM**



EASY MATING  
EASY CLEANING  
EASY INTEGRATION

<b>Locking</b>	Push-pull / Quick-release / Friction	Push-pull	Push-pull Quick-release	Push-pull	Friction	Push-pull	Push-pull Quick-release	Push-pull	Push-pull Screw-locking Quick-release	Quick-release
<b>Shell material</b>	Brass	Stainless Steel 316L	Aluminum	PEI (405) PBT (4032)	ABS	Brass	Brass Aluminum	Brass	Brass	Brass/Plastic Stainless Steel 316L
<b>Plating</b>	Chrome over Nickel	-	Chrome over Nickel Anodized	-	-	Chrome over Nickel	Anthracite Nickel	Chrome over Nickel	Anthracite Nickel Chrome over Nickel	Anthracite Nickel
<b>Plug Ø [mm]</b>	9-34	12-34	9-18	14.5-18.5	15.8/17.8	25.5	12-29	13/24	9.9 - 12.9	20.4/25.4
<b>Number of contacts</b>	1 to 55	1 to 55	2 to 27	2 to 27	6 to 19	3	2 to 42	1 to 4 fibers / Hybrid 2+2	4 to 24	4/7
<b>AWG</b>	AWG9-32	AWG9-32	AWG9-32	AWG9-32	AWG20-30	-	AWG9-32	AWG17 (hybrid)	AWG18-30	AWG24-28 (cabled plugs)
<b>Contact type</b>	Low voltage / High voltage / Coax / Triax / Hybrid	Low voltage / High voltage / Coax / Triax	Low voltage	Low voltage Hybrid	Low voltage	High voltage	Low voltage	Fiber optic / High voltage	Low voltage	Low voltage
<b>Test voltage DC [kV]</b>	Up to 50	Up to 50	Up to 4.8	Up to 4	Up to 2.7	Up to 1.7	Up to 3.7	Up to 2.8	Up to 2.4	Up to 1.2
<b>Current rating [A]</b>	Up to 60	Up to 60	Up to 30	Up to 30	Up to 3.0	Up to 14	Up to 26	Up to 10	Up to 10	Up to 5.0
<b>Sealing level</b>	IP68/69/Hermetic	IP68/69/Hermetic	IP68/69/Hermetic	IP67/IP68	IP30 - IP40	IP68	IP68/69 Hermetic	IP67/IP68	IP68	Metal IP68 Plastic IP67
<b>Mating cycles</b>	10,000	5,000	10,000	5,000	10	5,000	10,000	1,000	5,000	Metal 10,000 Plastic 5,000

<sup>1)</sup> Technical specifications only available in PDF format on [fischerconnectors.com](https://www.fischerconnectors.com)



For more information visit  
[fischerconnectors.com](https://www.fischerconnectors.com)

© Fischer Connectors SA – All rights reserved - 550205 - version 2.0 - 08.2019 – Changes without prior notice

**fischer**  
CONNECTORS