
F/GS AC UL fibreglass sleeving with acrylic coating

F/GS AC UL is A fibreglass sleeving coated with an acrylate-based varnish.

Attributes

The F/GS AC UL sleeving is flexible, non-transparent and available in various colours. The fibreglass construction ensures very good mechanical properties at high temperatures up to class F (155 °C).

Application

The F/GS AC UL sleeving is used as additional mechanical protection for connecting cables and winding wires at high temperatures and at increased mechanical loads. It also provides additional insulation in electrical machines up to class F and transformers as well as in other applications in electrical engineering and electronics.

Standards

Thermal class F (155 °C) - short-term up to 190 °C

- UL-approved UZFT2.E468446
- UL-approved UZFT8.E468446 (temp. rating 155 °C, 600 V)
- UL 1441

Delivery forms

Standard colours are natural, black (up to ID 12), green, red and yellow (up to ID 6). Delivery format: rings.

Sleeving inner diameter Format length

0.5 - 4.0 mm	200 m rings
4.5 - 12.0 mm	100 m rings
≥ 13.0 mm	50 m rings

Further dimensions, formats and colours on request. All dimensions can be delivered in adapted lengths.

Dimension	Unit of measure						
Inner diameter (ID)	mm	0.5	0.8	1.0	1.5	2.0	2.5
Tolerance (ID)	mm	+0.18	+0.18	+0.23	+0.25	+0.27	+0.30
Wall thickness min.	mm	0.279	0.330	0.381	0.381	0.381	0.457

Dimension	Unit of measure						
Inner diameter (ID)	mm	3.0	3.5	4.0	4.5	5.0	6.0
Tolerance (ID)	mm	+0.30	+0.30	+0.40	+0.40	+0.50	+0.50
Wall thickness min.	mm	0.457	0.508	0.508	0.508	0.508	0.508

Dimension	Unit of measure						
Inner diameter (ID)	mm	7.0	8.0	9.0	10.0	12.0	14.0
Tolerance (ID)	mm	+0.50	+0.50	+0.60	+0.60	+0.60	+0.70

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 10/18



Dimension	Unit of measure						
Wall thickness min.	mm	0.508	0.635	0.635	0.635	0.635	0.635

Dimension	Unit of measure					
Inner diameter (ID)	mm	16.0	18.0	20.0	24.0	30.0
Tolerance (ID)	mm	+0.70	+0.90	+0.90	+0.90	+0.90
Wall thickness min.	mm	0.635	0.635	0.635	0.635	0.635

Thermal	Unit of measure	Values
Thermal class	°C	155)
Application range		-10 up to +155 °C

Electrical	Unit of measure	Values	Test method
Dielectric strength	kV	min. 7	UL 1441

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 10/18

