



# Cellulose Fiberglass & Mineral Fiber

## KRENDL



Fiber Moving  
Equipment

55 Years of American Ingenuity

## #575

The **575** all fiber machine provides the highest production in its class. Designed with the professional contractor in mind, the **575** will out perform and outlast the competition.

- Convertible fold down loading door
- Lightest machine in its class
- User friendly electric dashboard
- Clear acrylic safety guard allows for inspection
- Durable powder coat finish
- Double 14 amp / 2 stage blowers
- Semi pneumatic run flat treaded tires
- Built in tool holder



Backed by a manufacturer's  
**2-YEAR WARRANTY - Made in the U.S.A.**

## MATERIAL PRODUCTION RATE

MATERIAL	MACHINE w/double 2-Stage Blower *lbs/hr (kg/hr)
FIBERGLASS	800-1000 (363-454)
CELLULOSE	2600-2800 (1179-1270)
MINERAL FIBER	2500-2700 (1134-1225)

lbs/hr (kg/hr) rating with 150 ft. (45.8 m.) of 3" (7.6 cm.)  
Hose at 16 ft. (4.8 m.) elevation, product brand, product density  
and variable blowing conditions will affect production rate.

### • POWER REQUIREMENT •

Double input, 30/15 amps each/120 volt/60 hz

Single input, 30 amp 240 volt/60 hz

International - Double input, 230 volt/50 hz

CE/CSA/CUL/UL

### • HOPPER CAPACITY •

14 cu. ft. (.39 m<sup>3</sup>)

Loading made easy with built in  
convertible tray

### • WEIGHT/DIMENSIONS •

380 lbs / 40.5" W x 31.5" D x 62" H

172 kg. / 103cm x 80cm x 157cm

### • BLOWER/SIZE •

14 amp/2-stage (120 volt)

Double Blower System yields

140 CFM @ 4 1/2 PSI per blower

### • AIRLOCK •

14" x 10" diameter

(35.5 cm. x 25.4 cm. diameter)

3" (7.6 cm.) Outlet

## Electric Dashboard

- LED start & stop buttons • Digital hourmeter
- Digital voltmeter • Dual variable blower controls
- Recessed power supply



### Dual Agitators

Designed for Constant Flow



### Clear Acrylic Safety Guard

Allows for Inspection

**KRENDL**  
Fiber Moving  
Equipment

55 Years of American Ingenuity