

These compact and powerful Miko Permanent Magnets are used for a wide range of underwater applications. The material consists of Neodymium which is epoxy-coated for corrosion resistance in sea water. Each type comes in boxes of 10 pcs, packed in a double-skin container to isolate the magnetic field and prepare it for air freight.

## CHARACTERISTICS

<b>Holding Force</b> 60 kg*	<b>Gross Weight (Box)</b> 7 kg	<b>Footprint</b> 40 x 50 mm
<b>Net Weight</b> 0,3 kg	<b>Quantity in Box</b> 10 pcs	<b>Height</b> 20 mm



**MPM-001**



**MPM-002**

With 5 x 5 mm flange, compatible with MHT-002 Handling Tool



**MPM-001 CS**

With M8 x 30 mm countersunk screw

## CONTACT

Miko Marine AS  
P.O. Box 1534 Vika  
N-0117 Oslo  
Norway

Website: [www.miko.no](http://www.miko.no)  
E-mail: [info@miko.no](mailto:info@miko.no)  
Telephone: +47 46 90 50 00

Read "IMPORTANT NOTES ABOUT MIKO MAGNETS" enclosed in each box before use.

\*Refers to the perpendicular holding force when applied directly onto a clean mild steel plate of minimum thickness 30 mm