

# For extreme Cooling...



### The patented

## **Piranha-cooling line**

solves all cooling problems while editing on chip generating machines.

- fits on all standard tool holders
- is flexibly and variably applicable (1/2 to 1/4 inch)
- withstands pressures up to 80 bar
- versatile use (blowing out chucks, vacuum brazing, etc.)
- cost-effective acquisition
- long lifespan thanks to anodic coating
- light weight
- new design
- 100% Swiss made®



# 1⁄4 Inch

D-12.5/28	Spacer 28mm with ball and nut	
D-12.5/43	Spacer 43mm with ball and nut	
D-12.5/70	Spacer 70mm with ball and nut	
RD-12.5-3.5	Round nozzle Ø3.5mm Round nozzle Ø12.5 passage Ø3.5	
RD-12.5-4.5	Round nozzle Ø4.5mm Round nozzle Ø12.5 passage Ø4.5	
RD-12.5-5.5	Special nozzle Ø1.8mm / 90° short Special nozzle Ø12.5 / Ø5. 0 / 7xØ1. 8-90 ° passage Ø5.5	
<i>SDK-12.5/90°</i>	Special nozzle Ø1.8mm / 90° short Special nozzle Ø12.5 / Ø5. 0 / 7xØ1. 8-90 ° passage Ø5.5	
<i>SDL-12.5/90</i> °	Special nozzle Ø1.8mm / 90° long Special nozzle Ø12.5 / Ø5.0 / 7xØ1. 8-90 ° length 30 passage Ø5.5	
<i>SDK-12.5/60°</i>	Special nozzle Ø1.8mm / 60° short Special nozzle Ø12.5 / Ø5.0 / 7xØ1. 8-60 ° passage Ø5.5	
<i>SDL-12.5/60°</i>	Special nozzle Ø1.8mm / 60° long Special nozzle Ø12.5 / Ø5.0 / 7xØ1. 8-60 ° length 30 passage Ø5.5	
L-12.5	90 ° elbow with ball and nut	
Quatro-12.5	Quatro distribution block 90° with ball and nut	

T-12.5	T-distributor with ball and nut	
Y-12.5	Y-distributor with ball and nut	
H-12.5	Ball valve 1/4" with ball and nut	
M-SW16	Nut SW16 with ball socket SW16x7	
GA-M12x1	Threaded connector M12x1 single-sided with ball socket M12x1	
<b>GA-1/4</b> "	Threaded connector 1/4" cyl. single-sided with ball socket 1/4" cyl.	
GA-1/4" NPT	Threaded connector 1/4" NPT single-sided with ball socket 1/4" NPT	
GA-1/8" NPT	Threaded connector 1/8" NPT single-sided with ball socket 1/8" NPT	
<b>GA-1/8</b> "	Threaded connector 1/8" cyl. single-sided with ball socket 1/8"	
GA-M10x1	Threaded connector M10x1 single-sided with ball socket M10x1	
<i>Ring 12.5</i>	0-ring 1/4"	$\bigcirc$
S-11/16	Hexagon wrench SW11 / SW16	

# 1⁄2 Inch

D-22-46.5	Spacer 46.5 mm with ball and nut	
D-22-63	Spacer 63.5mm with ball and nut	
D-22-80	Spacer 80mm with ball and nut	
RD-22-6	Round nozzle Ø6mm Round nozzle Ø22.25 passage Ø6	
RD-22-8	Round nozzle Ø8mm Round nozzle Ø22.25 passage Ø8	
RD-22-10	Round nozzle Ø10mm Round nozzle Ø22.25 passage Ø10	
L-1/2"	90 ° elbow with ball and nut	
T-1/2"	T-distributor with ball and nut	
Y-1/2"	Y-distributor with ball and nut	
H-22	Ball valve 1/2" with ball and nut	
M-SW27	Nut SW27 with ball socket SW27x10.5	
GA-22-3/8" NPT	Threaded connector 3/8" NPT single-sided with ball socket 3/8" NPT	

GA-22-3/8"	Threaded connector 3/8" single-sided with ball socket 3/8"	
GA-22-1/2" NPT	Threaded connector 1/2" NPT single-sided with ball socket 1/2" NPT	
Ring 22	0-ring 1/2"	$\bigcirc$
S-21/27	Hexagon wrench SW21 / SW27	





Sumpfstrasse 32 · CH-6312 Steinhausen Phone: +41 41 743 07 30 info@piranha-clamp.com · www.piranha-clamp.com