


Special-Sensors for Automation



Inductive Sensors

Contents

Terminology for inductive measurement	3.03 - 3.05
Application notes	3.06
Extreme environment	
Metal face sensors Series IGV / IGVU...-C / IGVW	3.07 - 3.10
Mounting clamp for metal face sensors Series KBM	3.11
POLAR-Series climatic-proofed -60 °C Series IGMP / -80 °C Series IGMP	3.12 - 3.14
TROPICAL-Series climatic proofed 120 °C Series IGMF / IGMW	3.15 - 3.20
TROPICAL-Series resistant to cooling fluids 120 °C Series IGFW / INFW	3.21
TROPICAL-Series resistant to cooling fluids armoured cable Series IGMF / INFW	3.22 - 3.23
High temperature 120 °C Series IGMT / Series IDT	3.24 - 3.26
High temperature 160 °C Series IGMH	3.27 - 3.28
High temperature 250 °C Series IGH / IRH / IDH	3.29 - 3.30
High temperature 200 °C Series INT	3.31
Amplifiers for high temperature sensors Series IKM / IU	3.32 - 3.33
Demanding environment	
Metal sleeve M12 / M18 / M30 Series IGM	3.34 - 3.37
Long sensing range Ø 80 mm / Ø 105 mm / Ø 160 mm / Ø 200 mm Series ID	3.38 - 3.41
Analog sensors	
Metal sleeve M12 / M18 / Series IGA	3.42 - 3.43
Long sensing range Ø 80 mm Series IDA	3.43
High temperature 160 °C Series IGT	3.44
Standard switches	
Metal sleeve M12 / M18 / M30 Series IGM	3.45 - 3.46
Smooth-bodied switches Ø 20 mm / Ø 34 mm Series INK	3.47
Special functions	
Surface sensors Series IFE	3.48 - 3.49
Offshore Series IGMO / Series IGVO	3.50 - 3.51
Washing resistant Series IDKW	3.52
Factor 1 Series IGB / IDB	3.53
Speed sensor Series HGVH	3.54
Ex-Series	
Ex-Zone 20, compact model Series IGEX20	3.56
Ex-Zone 0/20, intrinsically safe Series IGEX	3.57 - 3.58
Ex-Zone 0/20, intrinsically safe Series IGEXH / Series IGEXP	3.59 - 3.60
Ex-Zone 22, compact model Series IGEX / IGVEX	3.61 - 3.63
Ex-Zone 20, compact model Series IDEX20	3.64
Ex-Zone 0/20, intrinsically safe Series IDEX	3.65
Ex-Zone 22, compact model Series IDEX	3.66
Ex-amplifiers Series IKM 122 Ex / IKM 123 Ex	3.67 - 3.68
Accessories	
M12 connector	3.69
PG plug system	3.70
Assembly parts	3.71

Technical alterations are reserved to us without prior announcement. The information provided in this catalogue is for reference only. Product installation information can be found in the instructions supplied with each product.

Terminology for inductive measurement

Operating Principal

An inductive proximity switch works with a high frequency oscillating circuit that creates an alternating electromagnetic field on the active sensor surface by means of a coil. When a metallic object nears this field a damping occurs in the oscillating circuit. If this damping exceeds a threshold value, a switching signal is generated.

Operating distance

The operating distance is the distance between an object and the active sensor surface at which a switching signal is generated. The operating distance depends on the diameter of the coil. Therefore larger sensors are required for longer operating distances. On some of the EGE sensors the operating distance is adjustable.

If a metal object dampens only a part of the alternating field, the operating distance decreases; a larger object increases it. The following approximate values are derived from a standard rectangular measurement plate made of steel ST 37 with an edge length that corresponds to the diameter of the sensor coil or three times the rated operating distance, whichever is greater.

Damping area in %						
150	100	75	50	25	12.5	
Operating distance in %						
110	100	93	86	73	55	

The operating distance is influenced by the material of the object: Constant dimensions for different materials against steel ST 37 yield a changed operating distance.

The following table lists approximate values for the material dependent reduction factors. In practical applications variations could occur due to different alloying, for example.

Material	Operating distance in %
steel ST37	100
stainless steel	70
brass (Br)	50
copper (Cu)	45
aluminium (Al)	40

Rated operating distance s_n

The rated operating distance is a device parameter that does not take into account sample variances and external influences such as temperature and supply voltages.

Effective operating distance s_r

The effective operating distance is the operating distance at nominal voltage and a nominal temperature of 23 °C. It is between 90% and 110% of the rated operating distance.

Usable operating distance s_u

The usable operating distance lies in the entire allowable temperature and voltage range between 90% and 110% of the effective operating distance.

Assured operating distance s_a

The assured operating distance takes into account all the external influences and sample variances and lies in the range from 0% to 80% of the usable operating distance. Within this range a guaranteed switching is ensured.

Switch point drift

The operating distances are given for an ambient temperature of 23 °C. In the permissible temperature range the operating distance varies by less than 15% from the value at 23 °C. The temperature of the measured object has no influence on the switch point.

Hysteresis H

The switching hysteresis describes the distance between the turn-on point while approaching an object and the turn-off point during the separation of it from the sensor. The hysteresis brings about a stable switching signal even when there are vibrations, temperature drift, or electrical variations. The hysteresis is defined in EN 60947-5-2 as a maximum 20% from the effective operating distance, and carries a value of typically 10% from the effective operating distance s_r for EGE sensors.

Repeating accuracy R

The repeating accuracy describes the maintenance of the switching point after the repeated approach of an object under specified circumstances. EGE sensors have typical tolerances of less than 3% of the effective operating distance.

Switching frequency

The maximum switching frequency of the sensor is determined at half rated operating distance s_n with standard measurement plates to EN 60947-5-2

Terminology for inductive measurement

Operating voltage

The operating voltage is the voltage range within EGE sensors function safely. For a constant voltage supply it is important to make sure that the limits are still observed when the residual ripple is included.

Switching current

This current gives the maximum long-term current for the switching output of the sensor at an ambient temperature of 25 °C and ohmic load. At an elevated ambient temperature, the current load capability decreases.

For analog outputs, the boundary values given in the appropriate technical data, and particularly the permissible values for resistance loads, must be observed.

Short circuit protection

The short circuit protection ensures the sensor against destruction through a short circuit on the output. After removal of the fault, the output is reactivated. Where a maximum overload current is listed, this should not be exceeded.

Excess-current release

This value indicates the median value of current at which the short circuit protection responds with a tolerance of $\pm 20\%$.

Reverse polarity protection

The reverse polarity protection prevents destruction of the sensor by a reversal of the polarity of the voltage supply.

Voltage drop U_d

The voltage drop arises at the internal resistance of semiconductor elements, which are in the current-path of the output. It is dependent of the load-current and is declared according to EN 60947-5-2 for a mean current of 50 mA.

Residual current I_r

The residual current flows in the load current circuit when the output is blocked. The residual current must be considered when switching sensors in parallel.

Minimum load current I_m

The minimum load current is necessary for flawless operation with two-wire devices.

Current consumption

The current consumption is the maximum value of the no-load current I_0 that the sensor can absorb without a load.

Ambient temperature

The ambient temperature indicates the maximum allowable temperature range for the sensor.

Electromagnetic compatibility EMC

The EMC class is a measure of the noise immunity of the sensor against external electrical and magnetic influences. The information is based on the standard EN 61000-6-2.

Switch-on impulse suppression

EGE sensors have a switch-on suppression that blocks the output during the switch-on phase, when the operational voltage is applied.

Protective system

The protective system indicates the protection of the sensors against penetration of foreign bodies and water to EN 60529.

LED display

EGE sensors with yellow light-emitting diodes indicate the switching status optically.

Housing material

The housing material determines the chemical resistance of the sensor against external influences. For special applications, other housing materials are available.


Connection

The connection of the sensors is accomplished through plug-in connections or cables. Different cable types and lengths are available upon request.

Instructions for mounting

Mounting

For flush mounting the sensor can be built into metal up to its active surface without changing its characteristics. For non-flush mounting a metal-free zone around the sensor must be allowed for. A free zone to the material opposite the sensor must be maintained for all sensors.



The indicated free zones are in accordance with the standard EN 60947-5-2.

Fixing nuts are part of delivery for all metal thread sensors. For mounting clamps see page 3.71.

Terminology for inductive measurement

Collocation

When collocating the sensors, a minimum separation must be kept between the devices. When in doubt, a test should be conducted under application conditions. For flush mounting the lateral separation between two sensors must correspond to at least the diameter of the sensor. For non flush mounting, the lateral separation from each other must correspond to at least twice the diameter of the sensor. For oppositely mounted sensors, a minimal separation of six times the rated operating distance should be allowed.

Torques

In order to prevent destruction of the threaded bushing during fitting, the following maximum torques must not be exceeded:

Design	Metal Housing	Plastic Housing
M12x1	10 Nm	1 Nm
M18x1	25 Nm	2 Nm
M30x1.5	40 Nm	5 Nm

PTFE sensors may only be tightened by hand.

Instructions for operation

Serial connection

For the serial connection of two wire or three wire sensors the individual voltage drops are added together. Therefore there is a lesser operational voltage at the disposal of the load. The addition of the switch-on delay times should be noted.

Parallel connection

The parallel connection of two wire sensors can only be conditionally recommended since the residual currents are added together and flow through the load. For the parallel connection of three wire sensors, the current consumption of the individual devices is added together. Since this current does not flow through the load, the maximum number of parallel connectable three wire sensors depends only on the power supply.

Approval for safety applications

Sensors for personal security must have a qualification approval according to EN 61508 and must be labeled accordingly. Sensors that are not labeled must not be used for applications of this kind.

Valid standards

EN 60947-5-2

Control units; low voltage control units, auxiliary switch, proximity switch

EN 61000-6-4

Electromagnetic compatibility (EMC)
Interference emissions in the industrial area

EN 61000-6-2

Electromagnetic compatibility (EMC)
Generic standards immunity for industrial environments

EN 61000-4-2 (ESD)

Electrostatic discharging immunity

EN 61000-4-3 (HF radiated)

Radiated radio-frequency electromagnetic field immunity test

EN 61000-4-4 (Burst)

Electrical fast transient/burst immunity test

EN 61000-4-5 (Surge)

Surge immunity test

EN 61000-4-6 (HF conducted)

Immunity to conducted disturbances, induced by radio-frequency fields

EN 60529 : 2013

Protective systems, IP-designation

EN 60079-0 : 2012 +A11:2013

Explosive atmospheres –
Part 0: Equipment – General requirements

EN 60079-7 : 2015

Explosive atmospheres –
Part 7: Equipment protection by increased safety „e“

EN 60079-11 : 2012

Explosive atmospheres –
Part 11: Equipment protection by intrinsic safety „i“

EN 60079-18 : 2015

Explosive atmospheres –
Part 18: Equipment protection by encapsulation „m“

EN 60079-26 : 2015

Explosive atmospheres –
Part 26: Equipment with Equipment Protection Level (EPL)Ga

EN 60079-31 : 2014

Explosive atmospheres –
Part 31: Equipment dust ignition protection by enclosure „t“

Authorisations

TÜV NORD CERT Zertifizierungsstelle - Deutschland
(technical monitoring certification agency - Germany)

Certification

TÜV-cert ISO 9001 : 2008

TÜV-cert Quality control production
Attachment IV of the EC-Guidelines 94/9/EG
DIN EN ISO / IEC 80079-34 : 2012

TÜV Nord Re-cancelling certificate according to EN 10204

Application notes

Metal face sensors

page 3.07 - 3.10

The inductive proximity switches series IGV are used in areas with heavy-duty mechanical loads at the sensor's face or where seals between face and housing cannot be used. Chips hitting the front or frequently changing coolants or lubricants do not diminish the function of these proximity switches. The variants with a PTFE coating are particularly well-suited for welding lines and similar environments where sensors are exposed to heavy soiling. Metal face switches are manufactured from stainless steel and are one solid piece. They detect iron and steel through the metal front face.

POLAR-Switches

page 3.12 - 3.14

The POLAR-switch is ideal for application in cold storage houses and in extreme climate conditions. It is waterproof, safe for cleaning and extremely chemical-resistant. Because of its stainless steel housing, it can withstand vibrations on vehicles. The POLAR-switch is very compact and robust, it can be used from $-60\text{ }^{\circ}\text{C}$ to $+60\text{ }^{\circ}\text{C}$. IGMF 030 S-80 sensors are suitable in cryogenic processes and for medical-technical applications; they can be used for temperatures up to $-80\text{ }^{\circ}\text{C}$.

TROPICAL-Switches

page 3.15 - 3.20

The TROPICAL switches series IGMF are anticipated for applications in corrosive environment. They are stable particularly at frequent temperature changes and simultaneously high humidity. The permanent work in carwashes is permissible. The high corrosion resisting at simultaneously high mechanical loading capacity is reached through the combination of PTFE and titan stabilized stainless steel. The PTFE-hoods are sealed through fluoroelastomers O-rings surely. The FEP-connecting cable is poured within the housing and freed over a double seal from the housing. Cable lengths up to 100 m are available. The installed LED's are shining through the cable side cap and don't break out the case. IGMW series sensors are suitable for hydro steam environments with pressures of up to 4 bars. For higher pressures in hydro steam environments, IGWW series sensors made of full stainless steel are recommended.

120 °C-High temperature switches

page 3.21 - 3.26

The inductive PTFE switches series IGFW and INFW are made entirely of PTFE. The housing cover is securely sealed with a fluoroelastomer O-Ring. These sensors are designed for particularly difficult and aggressive environmental conditions. They can be used in damp and aggressive environments as well as under water (oil). IGMT- and IDT-series proximity switches are designed for use in temperatures up to $120\text{ }^{\circ}\text{C}$.

160 °C-High temperature switches

page 3.27 - 3.28

Inductive compact devices for ambient temperatures up to $160\text{ }^{\circ}\text{C}$ are available flush and non-flush in the standard designs M12, M18 and M30 with switching distances from

2 mm to 15 mm. The material used is the rugged stainless steel housing combined with high temperature resistant PEEK plastic.

250 °C-High temperatures sensors

page 3.29 - 3.30

The inductive proximity switches series IGH/IDH/IRH are used for ambient temperatures up to $250\text{ }^{\circ}\text{C}$. The units feature optional a plug connection which withstands high temperatures, allowing users to quickly and easily install a replacement sensor head in case of damage without having to replace the sensor cable. The sensors are particularly suited for operation in extreme heat, e. g. in drying ovens or brick kilns. Manufactured from aluminum / stainless steel and PEEK, the robust sensors can be used in rugged industrial environments. Their electronics are housed separately in a pluggable cable amplifier. The units are connected via a metal armored cable.

Amplifiers

page 3.32 - 3.33

Switching amplifiers are designed for induction sensors for which it is necessary to separate the sensor coil from the amplifier, e. g. for operating temperatures above $160\text{ }^{\circ}\text{C}$ or for sensor coils which must be exchanged due to frequent damage.

The switching amplifiers work statically, that is, if the sensor coil is permanently damped, the switching output also remains activated. Switching interval and hysteresis (IKM 120 GPP, IU 130...) can be set on the amplifier. The sensor cable may have a length of up to 20 m.

Demanding environment

Seite 3.34 - 3.41

The "Demanding environment" series is especially designed for harsh environments in which sensors are subjected to high electrical, electromagnetic or mechanical stress. For sensors used in critical applications, EGE has developed special inspection and test methods which place particular emphasis on the disturbances that occur in various production environments. The sensors are designed to be very resistant to the interference spectra produced by, e. g., frequency inverters, wireless communication systems and switching power supplies.

Surface sensors IFE...

page 3.48 - 3.49

The switches are build as flat sensors. They are used particularly to detect moving sheet metal or steel rods on conveyor belts. The complete sensor is covered, which make the sensor moisture resistant.

Reduced overall height affects the operating distance (sn). The IFE switches are self-contained with integral amplifier.

Dust- and Gas-Ex sensors

page 3.56 - 3.66

IGEX and IDEX are sensors for detecting metals in the Ex area zone 0/20 and zone 22 according to ATEX. Devices can be delivered in the standard configurations M12, M18 and M30. For large switching distances there are configurations with diameters of 80 mm to 160 mm.

Metal face sensors • Plug connection

Series IGUV - Proximity switches




M12 / M18 / M30

One piece stainless steel housing

DC 10...30 V

**Shock resistant
Impact proof**



Design	DC PNP M12 • M18 • M30			DC 2-Wire M12 • M18 • M30		
Dimensions						
						
Operating distance sn [mm]	2	5	10	2	5	10
ID-No.	P31193	P31194	P31195	P31225	P31226	P31227
Type	IGVU 02 GSP	IGVU 05 GSP	IGVU 10 GSP	IGVU 02 GS	IGVU 05 GS	IGVU 10 GS
Supply voltage [V]	10...30 DC			8...30 DC		
Switching current [mA]	250			150		
Short circuit proof	•			•		
Reverse protection	•			•		
Voltage drop max. [V]	1.5			3.5		
Current consumption [mA]	5			1.5		
Switching frequency [Hz]	180	180	150	180	180	150
Ambient temperature [°C]	-25...+80			-25...+80		
EMC-class	A			A		
Protection [EN 60529]	IP 68 + IP 69K			IP 68 + IP 69K		
LED display	•			•		
Housing material	AISI 316 L			AISI 316 L		
Connection	M12 connector			M12 connector		
The specified operating distance (sn) applies to ferromagnetic objects (ST37).						
	Accessories					
connecting cable type SLG 3-2 (Z01076), page 3.69						

Metal face sensors • Cable connection





Series IGV - Proximity switches

M12 / M18 / M30
One piece stainless
steel housing

DC 10...30 V

Shock resistant
Impact proof



Design	DC PNP • M12x1	DC PNP • M18x1	DC PNP • M30x1.5
Dimensions			
Operating distance sn [mm]	2	5	10
Switching output PNP			
ID-No.	P31228	P31229	P31230
Type	IGV 02 GSP	IGV 05 GSP	IGV 10 GSP
Supply voltage [V]	10...30 DC		
Switching current [mA]	250		
Short circuit proof	•		
Reverse protection	•		
Voltage drop max. [V]	1.5		
Current consumption [mA]	max. 5		
Switching frequency [Hz]	180	180	150
Ambient temperature [°C]	-25...+80		
EMC-class	A		
Protection [EN 60529]	IP 67		
LED display	•		
Housing material	AISI 316 L		
Connection	2 m PVC-cable 3x0.34 mm ²		
The specified operating distance (sn) applies to ferromagnetic objects (ST37).			

Metal face sensors • PTFE-coated

Series IGUVU - Proximity switches





M12 / M18 / M30

One piece stainless steel housing

DC 10...30 V

Shock resistant
Impact proof



Design	DC PNP • M12x1	DC PNP • M18x1	DC PNP • M30x1.5
Dimensions			
Operating distance sn [mm]	2	5	10
Switching output PNP			
ID-No.	P31234	P31235	P31236
Type	IGVU 02 GSP-C	IGVU 05 GSP-C	IGVU 10 GSP-C
Supply voltage [V]	10...30 DC		
Switching current [mA]	250		
Short circuit proof	•		
Reverse protection	•		
Voltage drop max. [V]	1.5		
Current consumption [mA]	5		
Switching frequency [Hz]	180	180	150
Ambient temperature [°C]	-25...+80		
EMC-class	A		
Protection [EN 60529]	IP 68 + IP 69K		
LED display	•		
Housing material	AISI 316 L, PTFE-coated		
Connection	M12 connector		
The specified operating distance (sn) applies to ferromagnetic objects (ST37).	Design with fixed cable on request		
			
Accessories	connecting cable SLG 3-2 (Z01076), page 3.69		

Metal face sensors • Climatic-proofed





Series IGW - Proximity switches

M12 / M18 / M30
One piece stainless
steel housing

DC 10...30 V

Shock resistant
Impact proof



Design	DC PNP • M12x1	DC PNP • M18x1	DC PNP • M30x1.5
Dimensions			
Operating distance sn [mm]	2	5	10
Switching output PNP			
ID-No.	P31237	P31238	P31239
Type	IGW 02 GSP	IGW 05 GSP	IGW 10 GSP
Supply voltage [V]	10...30 DC		
Switching current [mA]	250		
Short circuit proof	•		
Reverse protection	•		
Voltage drop max. [V]	1.5		
Current consumption [mA]	5		
Switching frequency [Hz]	180	180	150
Ambient temperature [°C]	-10...+110		
EMC-class	A		
Protection [EN 60529]	IP 68 + IP 69K		
Housing material	AISI 316 L		
Connection	2 m FEP-cable 3x0.34 mm ²		
The specified operating distance (sn) applies to ferromagnetic objects (ST37).			

Mounting clamp • For metal face sensors




Series KBM 012 / KBM 018 / KBM 030

**Impact- and shock resistant,
protected installation**

**Simple adjustment
via slotted holes**

**Mount and replace sensor
quickly and precisely**



Design		KBM 012 • KBM 018 • KBM 030					
Dimensions							
ID-No.		Z01209	Z01210	Z01211	Z01212	Z01213	Z01214
Type		KBM 012 A-ST52	KBM 018 A-ST52	KBM 030 A-ST52	KBM 012 B-A2	KBM 018 B-A2	KBM 030 B-A2
For sensor design		M12	M18	M30	M12	M18	M30
Dimensions							
L1 x L2 x L3	[mm]	34 x 24 x 40	40 x 30 x 40	55 x 40 x 40	34 x 24 x 40	40 x 30 x 40	55 x 40 x 40
Hole spacing e	[mm]	20	26	40	20	26	40
Sensor installation		flushed relative to the set back surface			set back		
Housing material		ST52, hardened			AISI 303		
Note:							
Mounting clamps are fastened to their metal surface using M6 hexagon socket screws. Make sure that the provided stainless steel washers have been placed in-between.							
The typical torque is 6 Nm.							
							
		flushed relative to the set back surface			set back		

POLAR-Series DC • Climatic-proofed –60 °C

Series IGMP - Proximity switches

M12 / M18 / M30






Stainless steel sleeve

DC 10...30 V

IP 68 Water-proofed

IP 69K Resistant to
high pressure cleaning



Design	DC PNP • M12x1		DC PNP • M18x1		DC PNP • M30x1.5	
Dimensions						
Installation flush (f) non flush (nf)						
Operating distance sn [mm]	2 f	4 nf	5 f	7 nf	10 f	15 nf
Switching output PNP						
ID-No.	P31145	P31146	P31147	P31148	P31219	P31220
Type	IGMP 02 GSP	IGMP 04 GSP	IGMP 05 GSP	IGMP 08 GSP	IGMP 010 GSP	IGMP 015 GSP
Supply voltage [V]	10...30 DC					
Switching current [mA]	200					
Short circuit proof	•					
Overcurrent release [mA]	230					
Reverse protection	•					
Voltage drop max. [V]	2					
Load current [mA]	–					
Current consumption [mA]	4					
Switching frequency [Hz]	1000					
Ambient temperature [°C]	–55...+60					
Temperature min. [°C]	–60					
Temperature gradient [K/min]	5					
EMC-class	A					
Protection [EN 60529]	IP 68 + IP 69K					
LED display	•					
Housing material	PTFE / AISI 316 Ti					
Connection	2 m FEP-cable 3x0.34 mm ²					
Switching current						
						

POLAR-Series AC • Climatic-proofed –60 °C

Series IGMP - Proximity switches

M18




Stainless steel sleeve

AC 20...250 V

IP 68 Water-proofed

**IP 69K Resistant to
high pressure cleaning**



Design	AC • M18x1	
Dimensions	 	
Installation flush (f) non flush (nf)	 	
Operating distance sn [mm]	5 f	7 nf
ID-No.	P31149	P31150
Type	IGMP 005 WS	IGMP 008 WS
Supply voltage [V]	20...250 AC	
Switching current [mA]	300	
Short circuit proof	-	
Overcurrent release [mA]	-	
Reverse protection	-	
Voltage drop max. [V]	4.5	
Load current [mA]	5	
Current consumption [mA]	2.5	
Switching frequency [Hz]	25	
Ambient temperature [°C]	-55...+60	
Temperature min. [°C]	-60	
Temperature gradient[K/min]	5	
EMC-class	A	
Protection [EN 60529]	IP 68 + IP 69K	
LED display	•	
Housing material	PTFE / AISI 316 Ti	
Connection	2 m FEP-cable 3x0.75 mm ²	
		

POLAR-Series • Climatic-proofed –80 °C

Series IGMP - Proximity switches



M30

Stainless steel sleeve

IP 68 Water-proofed

–80 °C permanent temperature



Design	M30x1.5
Dimensions Installation flush (f) non flush (nf)	
Operating distance sn [mm]	3 nf
ID-No.	P31337
Type	IGMP 030 S-80
Supply voltage [V]	–
Switching current [mA]	–
Hysteresis max. [%]	10
Short circuit proof	–
Reverse protection	–
Current consumption [mA]	–
Switching frequency [Hz]	–
Ambient temperature [°C]	–80...+50
EMC-class	A
Protection [EN 60529]	IP 68
LED display	–
Housing material	PTFE / AISI 316 Ti
Connection	2 m FEP-cable 3x0.75 mm², shielded
Sensor for the connection to amplifier IKM 120..., see page 3.32	

TROPICAL-Series DC • Climatic-proofed 120 °C





Series IGMF - Proximity switches



M12 / M18-short form
Stainless steel sleeve

DC 10...30 V

IP 68 Water-proofed
IP 69K Resistant to
high pressure cleaning



Design	DC PNP • M12x1		DC PNP • M18x1	
Dimensions				
Installation flush (f) non flush (nf)				
Operating distance sn [mm]	2 f	4 nf	5 f	7 nf
GSP  ID-No.	P31132	P31133	P30701	P30703
Type	IGMF 02 GSP	IGMF 04 GSP	IGMF 05 GSP	IGMF 08 GSP
GOP  ID-No.			P30702	P30704
Type			IGMF 05 GOP	IGMF 08 GOP
Supply voltage [V]	10...30 DC			
Switching current [mA]	200			
Overcurrent release [mA]	230			
Current consumption [mA]	4			
Residual current [μA]	1			
Voltage drop max. [V]	2			
Switching frequency [Hz]	1000			
Ambient temperature [°C]	-25...+120			
Compressive strength [bar]	10			
Residual ripple max. [%]	10			
EMC-class	A			
Protection [EN 60529]	IP 68 + IP 69K			
Housing material	PTFE / AISI 316 Ti (A4)			
Connection	2 m FEP-cable 3x0.34 mm ²			
Switching current				



TROPICAL-Series DC • Climatic-proofed 120 °C

Series IGMF - Proximity switches

M18 / M30






Stainless steel sleeve

DC 10...55 V

IP 68 Water-proofed

IP 69K Resistant to
high pressure cleaning



Design	DC PNP • M18x1		DC PNP • M30x1,5	
Dimensions				
Installation flush (f) non flush (nf)				
Operating distance sn [mm]	5 f	7 nf	10 f	15 nf
GSP				
ID-No.	P30705	P30708	P30711	P30714
Type	IGMF 005 GSP	IGMF 008 GSP	IGMF 010 GSP	IGMF 015 GSP
GOP				
ID-No.	P30706	P30709	P30712	P30715
Type	IGMF 005 GOP	IGMF 008 GOP	IGMF 010 GOP	IGMF 015 GOP
GSOP				
ID-No.	P30707	P30710	P30713	P30716
Type	IGMF 005 GSOP	IGMF 008 GSOP	IGMF 010 GSOP	IGMF 015 GSOP
Supply voltage [V]	...GSP, ...GOP 10...55 DC / ...GSOP 10...30 DC			
Switching current [mA]	...GSP, ...GOP 400 / ...GSOP 200			
Overcurrent release [mA]	...GSP, ...GOP 430 / ...GSOP 230			
Current consumption [mA]	4			
Residual current [µA]	1			
Voltage drop max. [V]	2			
Switching frequency [Hz]	...GSP, ...GOP 150 / ...GSOP 1000			
Ambient temperature [°C]	-25...+120			
Compressive strenght [bar]	10			
EMC-class	A			
Protection [EN 60529]	IP 68 + IP 69K			
Housing material	PTFE / AISI 316 Ti (A4)			
Connection	2 m FEP-cable 3x0.34 mm ² / 2 m FEP-cable 4x0.25 mm ²			
Switching current				
	GSP/GOP 		GSOP 	

TROPICAL-Series AC • Climatic-proofed 120 °C

Series IGMF - Proximity switches

M18 / M30





Stainless steel sleeve



AC 20...250 V

IP 68 Water-proofed

**IP 69K Resistant to
high pressure cleaning**



Design	AC • M18x1		AC • M30x1.5	
Dimensions				
Installation flush (f) non flush (nf)				
Operating distance sn [mm]	5 f	7 nf	10 f	15 nf
WS  ID-No.	P31071	P31073	P31075	P31077
Type	IGMF 005 WS	IGMF 008 WS	IGMF 010 WS	IGMF 015 WS
WO  ID-No.	P31070	P31072	P31074	P31076
Type	IGMF 005 WO	IGMF 008 WO	IGMF 010 WO	IGMF 015 WO
Supply voltage	20...250 AC			
WS/WO [V]				
Switching current	< 400			
WS/WO [mA]				
Current consumption [mA]	< 2.5			
Voltage drop max. [V]	< 5 eff.			
Switching frequency [Hz]	25			
Ambient temperature [°C]	-25...+120			
Compressive strength [bar]	10			
Minimum load current [mA]	5.0			
EMC-class	A			
Protection [EN 60529]	IP 68 + IP 69K			
Housing material	PTFE / AISI 316 Ti (A4)			
Connection	2 m FEP-cable 3x0.75 mm ²			
Switching current				



TROPICAL-Series DC • Climatic-proofed 120 °C

Series IGMW - Proximity switches

M12 / M18-short form





Stainless steel sleeve



DC 10...30 V

IP 68 Water-proofed

IP 69K Resistant to
high pressure cleaning
Steam proof



Design	DC PNP • M12x1		DC PNP • M18x1	
Dimensions				
Installation flush (f) non flush (nf)				
Operating distance sn [mm]	2 f	4 nf	5 f	7 nf
GSP  ID-No. Type	P31338 IGMW 02 GSP	P31339 IGMW 04 GSP	P31340 IGMW 05 GSP	P31341 IGMW 08 GSP
GOP  ID-No. Type			P31342 IGMW 05 GOP	P31343 IGMW 08 GOP
Supply voltage [V]	10...30 DC			
Switching current [mA]	200			
Overcurrent release [mA]	230			
Current consumption [mA]	4			
Residual current [µA]	1			
Voltage drop max. [V]	2			
Switching frequency [Hz]	1000			
Ambient temperature [°C]	-25...+120			
Compressive strength [bar]	4			
Residual ripple max. [%]	10			
EMC-class	A			
Protection [EN 60529]	IP 68 + IP 69K			
Housing material	PTFE / AISI 316 Ti (A4)			
Connection	2 m FEP-cable 3x0.34 mm²			
Switching current				



TROPICAL-Series DC • Climatic-proofed 120 °C

Series IGMW - Proximity switches

M18 / M30

Stainless steel sleeve

DC 10...55 V









IP 68 Water-proofed

IP 69K Resistant to

high pressure cleaning

Steam proof



Design	DC PNP • M18x1		DC PNP • M30x1,5	
Dimensions				
Installation flush (f) non flush (nf)	 LED		 LED	
Operating distance sn [mm]	5 f	7 nf	10 f	15 nf
GSP	 ID-No. P31344 Type IGMW 005 GSP	 ID-No. P31345 Type IGMW 008 GSP	 ID-No. P31346 Type IGMW 010 GSP	 ID-No. P31347 Type IGMW 015 GSP
GOP	 ID-No. P31348 Type IGMW 005 GOP	 ID-No. P31349 Type IGMW 008 GOP	 ID-No. P31350 Type IGMW 010 GOP	 ID-No. P31351 Type IGMW 015 GOP
GSOP	 ID-No. P31352 Type IGMW 005 GSOP	 ID-No. P31353 Type IGMW 008 GSOP	 ID-No. P31354 Type IGMW 010 GSOP	 ID-No. P31355 Type IGMW 015 GSOP
Supply voltage [V]	...GSP, ...GOP 10...55 DC / ...GSOP 10...30 DC			
Switching current [mA]	...GSP, ...GOP 400 / ...GSOP 200			
Overcurrent release [mA]	...GSP, ...GOP 430 / ...GSOP 230			
Current consumption [mA]	4			
Residual current [µA]	1			
Voltage drop max. [V]	2			
Switching frequency [Hz]	...GSP, ...GOP 150 / ...GSOP 1000			
Ambient temperature [°C]	-25...+120			
Compressive strenght [bar]	4			
EMC-class	A			
Protection [EN 60529]	IP 68 + IP 69K			
Housing material	PTFE / AISI 316 Ti (A4)			
Connection	2 m FEP-cable 3x0.34 mm² / 2 m FEP-cable 4x0.25 mm²			
Switching current				
	GSP/GOP 		GSOP 	

TROPICAL-Series AC • Climatic-proofed 120 °C

Series IGMW - Proximity switches

M18 / M30



Stainless steel sleeve



AC 20...250 V

IP 68 Water-proofed

IP 69K Resistant to
high pressure cleaning
Steam proof



Design	AC • M18x1		AC • M30x1.5	
Dimensions				
Installation flush (f) non flush (nf)				
Operating distance sn [mm]	5 f		10 f	
WS  ID-No.	P31356		P31358	
Type	IGMW 005 WS		IGMW 010 WS	
WO  ID-No.	P31360		P31362	
Type	IGMW 005 WO		IGMW 010 WO	
Supply voltage	WS/WO [V]		20...250 AC	
Switching current	WS/WO [mA]		<400	
Current consumption	[mA]		<2.5	
Voltage drop max.	[V]		<5 eff.	
Switching frequency	[Hz]		25	
Ambient temperature	[°C]		-25...+120	
Compressive strength	[bar]		4	
Minimum load current	[mA]		5.0	
EMC-class			A	
Protection [EN 60529]			IP 68 + IP 69K	
Housing material			PTFE / AISI 316 Ti (A4)	
Connection			2 m FEP-cable 3x0.75 mm²	
Switching current				



TROPICAL-Series • Resistant to rolling oil

Series IGFW / INFW - Proximity switches

PTFE housing

DC 10...55 V








AC 20...250 V

IP 68 Water-proofed

IP 69K Resistant to

high pressure cleaning



Design	DC PNP • M30x1.5		DC • Ø 35	AC • M30x1.5		AC • Ø 35
Dimensions						
Installation flush (f) non flush (nf)	LED		LED	LED		LED
Operating distance sn [mm]	10 f		14 nf	10 f		19 nf
Switching output (DC PNP)						
ID-No.	P30628		P30640	P30626		P30650
Type	IGFW 010 GSP		INFW 020 GSP	IGFW 010 WS		INFW 020 WS
Supply voltage [V]	10...55 DC			20...250 AC		
Switching current [mA]	< 400			< 400		
Surge current [mA]	short circuit protection			< 3000 / 10 ms		
Current consumption [mA]	4			2.5		
Inverse current max. [µA]	1			2500		
Voltage drop [V]	2			5 eff.		
Ambient temperature [°C]	-25...+120					
Temperature deviation [%]	10 (-25...+70 °C), 20 (-25...+120 °C)					
Overcurrent release approx. [mA]	430			-		
Reverse Protection	•			-		
Minimum load current [mA]	-			4.5		
EMC-class			A			
Switching frequency [Hz]	100			20		
Protection [EN 60529]			IP 68 + IP 69K			
Housing material			PTFE			
Connection	2 m FEP-cable 3x0.34 mm ²			2 m Silicone-cable 0.75 mm ²		
Switching current						

Accessories nut M30x1.5 (Z00120), clamp Ø 35 (Z00125), page 3.71

TROPICAL-Series • Resistant to rolling oil






Series IGMF / INFW - Proximity switches

DC 10...55 V

Climatic-proofed
Resistant to acid

Armoured cable
with IP 68-plug



Design	DC PNP • M30x1.5	DC PNP • Ø35
Dimensions Installation flush (f) non flush (nf)		
Operating distance sn [mm]	10 f	20 nf
Switching output PNP		
ID-No.	P31215	P31216
Type	IGMF 010 GSP-PZ	INFW 020 GSP-PZ
Supply voltage [V]	10...55 DC	10...55 DC
Switching current max. [mA]	400	400
Current consumption [mA]	4	4
Switching frequency [Hz]	150	100
Ambient temperature [°C]	-25...+120	-25...+120
Compressive strength [bar]	10	-
Protection [EN 60529]	IP 68 + IP 69K	IP 68 + IP 69K
Function indicator	LED	LED
Housing material	PTFE, AISI 316 Ti	PTFE
Connection	5 m FEP-cable 3x0.34mm ² armoured cable	5 m FEP-cable 3x0.34mm ² armoured cable
Plug, Lemo series K, 3-pol   Sensors without plug on request		
Accessories	junction box GS..., page 3.23	




Junction box • Resistant to rolling oil

Series GS 125 / GS 175 / GS 250



Connection of sensors with
armoured cable

IP 68-plug



Design	GS 125	GS 175	GS 250
Dimensions			
ID-No.	P31212	P31217	P31218
Type	GS 125	GS 175	GS 250
Connectable sensors	2	3	4
Supply voltage [V]	10...55 DC	10...55 DC	10...55 DC
Ambient temperature [°C]	-20...+75	-20...+75	-20...+75
Protection [EN 60529]	IP 68	IP 68	IP 68
Housing material	Aluminium	Aluminium	Aluminium
Connection	10 m TPE-numbered cable 7x0.5mm ²	10 m TPE-numbered cable 7x0.5mm ²	10 m TPE-numbered cable 7x0.5mm ²

Plug, Lemo series K, 3-pol



Notice

for sensors IGMF 010 GSP-PZ / INFW 020 GSP-PZ, page 3.22

High temperature 120 °C

Series IGMT - Proximity switches




M12 / M18 / M30



Metal sleeve

DC 10...48 V

Extended
temperature range
-25 °C...+120 °C



Design	DC PNP • M12x1		DC PNP • M18x1		DC PNP • M30x1.5	
Dimensions						
Installation flush (f) non flush (nf)						
Operating distance sn [mm]	2 f	4 nf	5 f	8 nf	10 f	15 nf
Switching output PNP						
ID-No.	P31282	P31283	P31290	P31291	P31292	P31293
Type	IGMT 02 GSP	IGMT 04 GSP	IGMT 005 GSP	IGMT 008 GSP	IGMT 010 GSP	IGMT 015 GSP
Supply voltage [V]	10...48 DC					
Switching current [mA]	200					
Short circuit proof	•					
Reverse protection	•					
Voltage drop max. [V]	2					
Current consumption [mA]	4					
Switching frequency [Hz]	500					
Ambient temperature [°C]	-25...+120					
EMC-class	A					
Protection [EN 60529]	IP 67					
LED display	•					
Housing material	Br-Ni / PBT					
Connection	2 m Silicone-cable 3x0.34 mm ²					
Switching current						
Notes	design with M12 connector on request					



High temperature 120 °C

Series IGMT - Proximity switches

M18 / M30






Metal sleeve


AC 20...250 V

Extended
temperature range

-25 °C...+120 °C



Design	AC • M18x1		AC • M30x1.5	
Dimensions				
Installation flush (f) non flush (nf)				
Operating distance sn [mm]	5 f	8 nf	10 f	15 nf
Switching output				
ID-No.	P31118	P31119	P31120	P31121
Type	IGMT 005 WS	IGMT 008 WS	IGMT 010 WS	IGMT 015 WS
Supply voltage [V]	20...250 AC			
Switching current [mA]	200			
Short circuit proof	-			
Reverse protection	-			
Voltage drop max. [V]	5 eff.			
Minimum load current [mA]	5			
Current consumption [mA]	2.5			
Switching frequency [Hz]	25			
Ambient temperature [°C]	-25...+120			
EMC-class	A			
Protection [EN 60529]	IP 67			
LED display	•			
Housing material	Br-Ni / PBT			
Connection	2 m Silicone-cable 3x0.75 mm ²			
Switching current				



High temperature 120 °C







Series IDT - Proximity switches

DC 10...55 V

AC 20...250 V

Extended
sensing range



Design	Ø80 mm		Ø105 mm		Ø160 mm	
Dimensions						
Installation non flush (nf)						
Operating distance sn [mm]	50 nf	45 nf	80 nf	60 nf	110 nf	100 nf
Switching output (DC PNP)						
ID-No.	P31276	P31279	P31277	P31280	P31278	P31281
Type	IDT 080 GSP	IDT 080 WS	IDT 105 GSP	IDT 105 WS	IDT 160 GSP	IDT 160 WS
Supply voltage [V]	10...55 DC	20...250 AC	10...55 DC	20...250 AC	10...55 DC	20...250 AC
Switching current [mA]	400	400	400	400	400	400
Short circuit proof	•	–	•	–	•	–
Reverse protection	•	–	•	–	•	–
Voltage drop max. [V]	2	5 eff.	2	5 eff.	2	5 eff.
Minimum load current [mA]	–	5	–	5	–	5
Current consumption [mA]	4	2.5	4	2.5	4	2.5
Switching frequency [Hz]	20	10	20	10	20	10
Ambient temperature [°C]	–25...+120					
EMC-class	A					
Protection [EN 60529]	IP 67					
Housing material	PBT / Aluminium					
Connection	2 m Silicone-cable 3x0.34 mm ²	2 m Silicone-cable 2x0.75 mm ²	2 m Silicone-cable 3x0.34 mm ²	2 m Silicone-cable 2x0.75 mm ²	2 m Silicone-cable 3x0.34 mm ²	2 m Silicone-cable 2x0.75 mm ²
Switching current	  					

High temperature 160 °C

Series IGMH - Proximity switches

M12 / M18 / M30







Stainless steel sleeve


DC 10...30 V

IP 68 Water-proofed

IP 69K Resistant to
high pressure cleaning



Design	DC PNP • M12x1		DC PNP • M18x1		DC PNP • M30x1.5	
Dimensions						
Installation flush (f) non flush (nf)						
Operating distance sn [mm]	2 f	4 nf	5 f	8 nf	10 f	15 nf
Switching output PNP						
ID-No.	P31288	P31289	P31161	P31162	P31163	P31164
Type	IGMH 02 GSP	IGMH 04 GSP	IGMH 005 GSP	IGMH 008 GSP	IGMH 010 GSP	IGMH 015 GSP
Supply voltage [V]	10...30 DC					
Switching current [mA]	200					
Short circuit proof	•					
Reverse protection	•					
Voltage drop max. [V]	2					
Residual current max. [mA]	0.02					
Current consumption (not actuated) [mA]	7					
Switching frequency [Hz]	200					
Temperature deviation [%]	15					
Ambient temperature [°C]	-25...+150		-25...+160			
EMC-class	A					
Protection [EN 60529]	IP 68 + IP 69K					
LED display	-					
Housing material	AISI 316 Ti / PEEK					
Connection	2 m FEP-cable 3x0.34 mm²					
Switching current						



Notes

temperature depending parameters are described in the technical manual

High temperature 160 °C

Series IGMH - Proximity switches

M12 / M18 / M30




Stainless steel sleeve



DC 10...30 V

Moisture resistant

Silicone-cable



Design	DC PNP • M12x1		DC PNP • M18x1		DC PNP • M30x1.5	
Dimensions						
Installation flush (f) non flush (nf)						
Operating distance sn [mm]	2 f	4 nf	5 f	8 nf	10 f	15 nf
Switching output PNP						
ID-No.	P31299	P31300	P31301	P31302	P31303	P31304
Type	IGMH 02 GSP-K	IGMH 04 GSP-K	IGMH 005 GSP-K	IGMH 008 GSP-K	IGMH 010 GSP-K	IGMH 015 GSP-K
Supply voltage [V]	10...30 DC					
Switching current [mA]	200					
Short circuit proof	•					
Reverse protection	•					
Voltage drop max. [V]	2					
Residual current max. [mA]	0.02					
Current consumption (not actuated) [mA]	7					
Switching frequency [Hz]	200					
Temperature deviation [%]	15					
Ambient temperature [°C]	-25...+150		-25...+160			
EMC-class	A					
Protection [EN 60529]	IP 67					
LED display	-					
Housing material	AISI 316 Ti / PEEK					
Connection	2 m Silicone-cable 3x0.34 mm ²					
Switching current						



Notes

temperature depending parameters are described in the technical manual






High temperature 250 °C

Series IRH / IDH - Proximity sensor

Armoured cable

With connector for cable amplifier




Design	Cuboid 40 mm	Ø80 mm	DC PNP • M30x1.5
Dimensions Installation non flush (nf)			
Operating distance sn [mm] Switching output PNP	20 nf, adjustable	40 nf, adjustable	amplifier 
ID-No.	P31294	P31295	P31204
Type	IRH 040 S250	IDH 080 S250	IK 030 GSP
Supply voltage [V]	—	—	10...30
Switching current [mA]	—	—	200
Current consumption [mA]	—	—	15
Voltage drop max. [V]	—	—	1.5
Ambient temperature [°C]	0...+250	—	0...+70
Short circuit proof	—	—	•
Reverse protection	—	—	•
EMC-class	A	—	A
Switching frequency [Hz]	30	—	30
Protection [EN 60529]	IP 60	—	IP 67
Function indicator	—	—	LED yellow
Stand-by indicator	—	—	LED green
Housing material	Aluminium / PEEK	—	AISI 316 Ti
Connection cable	5 m FEP-cable, Ø 8 mm armoured cable	—	—
Connection	M12 connector	—	M12 connector
			
Accessories	connecting cable SLG 3-2 (Z01076), page 3.69		






High temperature 250 °C

Series IGHS / IRHS / IDHS - Proximity sensor

Armoured cable

With connector for cable amplifier and sensor



Design	M30x1.5	Cuboid 40 mm	Ø 80 mm
Dimensions			
Installation non flush (nf)			
Operating distance sn [mm]	15 nf, adjustable	20 nf, adjustable	40 nf, adjustable
ID-No.	P31298	P31296	P31297
Type	IGHS 030 S250	IRHS 040 S250	IDHS 080 S250
Supply voltage [V]	-		
Switching current [mA]	-		
Current consumption [mA]	-		
Voltage drop [V]	-		
Ambient temperature [°C]	0...+250		
Short circuit proof	-		
Reverse protection	-		
EMC-class	A		
Switching frequency [Hz]	30		
Protection [EN 60529]	IP 60		
Housing material	AISI 316 Ti / PEEK	Aluminium / PEEK	
Connection	M12 connector		
Connection cable (Accessories)	5 m FEP-cable, Ø 8 mm armoured cable (KAP 08-DS5, Z01190)		
			
			
Accessories	connecting cable SLG 3-2 (Z01076), page 3.69		

Accessories connecting cable SLG 3-2 (Z01076), page 3.69





High temperature 200 °C

Series INT - Proximity sensor

PTFE housing

No cooling



Design	INT020-S200		INT100-S180	
Dimensions				
Installation non flush (nf)				
Operating distance sn [mm]	15 nf		50 nf	
Adjustable range [mm]	5...20		10...80	
ID-No.	P31101	P30411	P31103	P30427
Type	INT020-S200 K	INT020-S200 GC	INT100-S180 K	INT100-S180 GC
Limiting temperature [°C]	250		200	
Nominal temperature [°C]	200		180	
Temperature deviation [mm/°C] (not linear)	0.05		0.06	
EMC-class	B			
Protection [EN 60529]	IP 40			
Housing material	PTFE			
Mounting	Aluminium plate			
Sensing material [ST 37]	40x40x1		100x100x1	
Connecting cable	5 m PTFE shielded			
Connection and required Amplifier	clamp connection IKM 120 GPP	plug C 16 IU 130...	clamp connection IKM 120 GPP	plug C 16 IU 130...
Special notes	If the ambient temperature exceeds 230 °C, there might be failed reactions from the sensor, but it will nor be destroyed by this. The inductive high temperature proximity switches must be used with an amplifier. The connection cable can be up to 10 m long. We can supply the cable with a flexible aluminium tube on request.			
Connection diagram	Sensor-Connection sensors INT...K to IKM 120 GPP		Plug C 16: connection for Sensors INT...to IU 130...	
Amplifiers see page 3.32 - 3.33				
Temperature depending parameters are described in the technical manual				
Accessories			plug C 16	



Amplifier

Series IKM

**For the connection of
separate sensors for
extreme temperatures**

LED display



Design		IKM 120 GSOP	
Dimensions			
ID-No.		P31334	
Type		IKM 120 GSOP	
Switching output		 PNP	
Supply voltage	[V]	24 V DC ±20%	
Switching current	[mA]	400	
Short circuit proof		•	
Current consumption	[mA]	max. 18	
Operating distance		adjustable	
Hysteresis max.	[%]	10	
Switching frequency	[Hz]	100	
Ambient temperature	[°C]	−25...+75	
EMC-class		A	
Protection	[EN 60529]	terminal: IP 20 / housing: IP 40	
Function indicator		LED yellow	
Stand-by indicator		LED green	
Housing material		PA	
Connection sensor		terminal screws	
Connection Amplifier		terminal screws	
			




Amplifiers

Series IU

For the connection of
separate sensors

LED display



Design	IU 130...	
Dimensions		
ID-No.	P30438	P30439
Type	IU 130 WP	IU 130 GPP
Supply voltage [V]	230 AC $\pm 10\%$	24 DC $\pm 10\%$
Switching current [mA]	400	
Short circuit proof	-	
Current consumption [mA]	15	
Operating distance	adjustable	
Hysteresis max. [%]	adjustable	
Output	programmable	
Switching frequency [Hz]	5	15
Ambient temperature [°C]	-20...+70	
EMC-class	A	
Protection [EN 60529]	IP 67	
Function indicator	LED yellow	
Stand-by indicator	LED green	
Housing material	PBT	
Connection sensor	C 16 plug connection	
Connection amplifier	2 m PVC-cable 4x0.75 mm ²	2 m PVC-cable 3x0.50 mm ²
	connection amplifier 	connection amplifier 
Accessories	external plug C 16 (Z00039)	

Demanding environment

Series IGM - Proximity switches

M12 / M18 / M30




Metal sleeve



DC 10...48 V

Short form

Increased EMC



Design	DC PNP • M12x1		DC PNP • M18x1		DC PNP • M30x1.5	
Dimensions						
Installation flush (f) non flush (nf)						
Operating distance sn [mm]	2 f	4 nf	5 f	8 nf	10 f	15 nf
GSP						
ID-No.	P31246	P31247	P31305	P31306	P31307	P31308
Type	IGMU 02 GSP	IGMU 04 GSP	IGMU 05 GSP	IGMU 08 GSP	IGMU 10 GSP	IGMU 15 GSP
GSOP						
ID-No.	-	-	P31250	P31251	P31254	P31255
Type	-	-	IGMU 05 GSOP	IGMU 08 GSOP	IGMU 10 GSOP	IGMU 15 GSOP
Supply voltage [V]	10...48 DC					
Switching current [mA]	200					
Short circuit proof	•					
Reverse protection	•					
Voltage drop max. [V]	2					
Current consumption [mA]	2.5					
Switching frequency [Hz]	500					
Ambient temperature [°C]	-25...+75					
EMC-class	A					
Protection [EN 60529]	IP 67					
LED display	•					
Housing material	Br-Ni / PBT					
Connection	M12 connector					



Accessories connecting cable SLG 3-2 (GSP) / SLG 4-2 (GSOP), page 3.69

Demanding environment

Series IGM - Proximity switches

M12 / M18 / M30






Metal sleeve

DC 10...48 V

Short form

Increased EMC



Design	DC PNP • M12x1		DC PNP • M18x1		DC PNP • M30x1.5	
Dimensions						
Installation flush (f) non flush (nf)						
Operating distance sn [mm]	2 f	4 nf	5 f	8 nf	10 f	15 nf
GSP  ID-No.	P31244	P31245	P31309	P31310	P31311	P31312
Type	IGM 02 GSP	IGM 04 GSP	IGM 05 GSP	IGM 08 GSP	IGM 10 GSP	IGM 15 GSP
GSOP  ID-No.	-	-	P31248	P31249	P31252	P31253
Type	-	-	IGM 05 GSOP	IGM 08 GSOP	IGM 10 GSOP	IGM 15 GSOP
Supply voltage [V]	10...48 DC					
Switching current [mA]	200					
Short circuit proof	•					
Reverse protection	•					
Voltage drop max. [V]	2					
Current consumption [mA]	2.5					
Switching frequency [Hz]	500					
Ambient temperature [°C]	-25...+75					
EMC-class	A					
Protection [EN 60529]	IP 67					
LED display	•					
Housing material	Br-Ni / PBT					
Connection	GSP: 2 m PVC-cable 3x0.34 mm ²			GSOP: 2 m PVC-cable 4x0.34 mm ²		
						

Demanding environment

Series IGM - Proximity switches

M18 / M30

Metal sleeve











DC 10...48 V

AC 20...250 V

Long form

Increased EMC



Design	DC PNP • M18x1		DC PNP • M30x1.5		AC • M30x1.5 programmable	
Dimensions						
Installation flush (f) non flush (nf)						
Operating distance sn [mm]	5 f	8 nf	10 f	15 nf	10 f	15 nf
GSP 	ID-No. P31313 IGMU 005 GSP	ID-No. P31314 IGMU 008 GSP	ID-No. P31315 IGMU 010 GSP	ID-No. P31316 IGMU 015 GSP	-	-
GSOP 	ID-No. P31258 IGMU 005 GSOP	ID-No. P31259 IGMU 008 GSOP	ID-No. P31262 IGMU 010 GSOP	ID-No. P31263 IGMU 015 GSOP	-	-
WP 	ID-No. -	ID-No. -	ID-No. -	ID-No. -	P30015 IGMS 010 WP	P30019 IGMS 015 WP
Supply voltage [V]	10...48 DC				20...250 AC	
Switching current [mA]	200				400	
Short circuit proof	•				3000 mA/10 ms	
Reverse protection	•				-	
Voltage drop max. [V]	2				6	
Minimum load current [mA]	-				5	
Current consumption [mA]	2.5				2.5	
Switching frequency [Hz]	500				25	
Ambient temperature [°C]	-25...+75				-25...+75	
EMC-class	A				A	
Protection [EN 60529]	IP 67				IP 67	
LED display	•				•	
Housing material	Br-Ni / PBT				Br-Ni / PBT	
Connection	M12 connector				PG-plug connection 2 m PVC-cable 3x0.5 mm²	
Accessories	connecting cable SLG 3-2 (GSP) / SLG 4-2 (GSOP), page 3.69					
						

Demanding environment

Series IGM - Proximity switches

M18 / M30

Metal sleeve










DC 10...48 V

AC 20...250 V

Long form

Increased EMC



Design	DC PNP • M18x1		DC PNP • M30x1.5		AC • M30x1.5	
Dimensions						
Installation flush (f) non flush (nf)						
Operating distance sn [mm]	5 f	8 nf	10 f	15 nf	10 f	15 nf
GSP		ID-No. P31317 Type IGM 005 GSP	ID-No. P31318 Type IGM 008 GSP	ID-No. P31319 Type IGM 010 GSP	ID-No. P31320 Type IGM 015 GSP	-
GSOP		ID-No. P31256 Type IGM 005 GSOP	ID-No. P31257 Type IGM 008 GSOP	ID-No. P31260 Type IGM 010 GSOP	ID-No. P31261 Type IGM 015 GSOP	-
WS		ID-No. - Type -	-	-	-	ID-No. P30016 Type IGM 010 WS ID-No. P30020 Type IGM 015 WS
Supply voltage [V]	10...48 DC				20...250 AC	
Switching current [mA]	200				400	
Short circuit proof	•				3000 mA/10 ms	
Reverse protection	•				-	
Voltage drop max. [V]	2				6	
Minimum load current [mA]	-				5	
Current consumption [mA]	2.5				2.5	
Switching frequency [Hz]	500				25	
Ambient temperature [°C]	-25...+75				-25...+75	
EMC-class	A				A	
Protection [EN 60529]	IP 67				IP 67	
LED display	•				•	
Housing material	Br-Ni / PBT				Br-Ni / PBT	
Connection	GSP: 2 m PVC-cable, 3x0.34 mm ² GSOP: 2 m PVC-cable, 4x0.34 mm ²				2 m PVC-cable 3x0.5 mm ²	
						

Demanding environment

Series ID - Proximity switches

Ø80 mm




DC 10...55 V

AC 20...250 V

Sensing range adjustable

Increased EMC



Design	DC PNP • Ø80 mm	DC PNP • Ø80 mm	AC • Ø80 mm programmable
Dimensions Installation non flush (nf)			
Operating distance sn [mm] (Adjustable range)	55 nf (25...80)	55 nf (25...80)	55 nf (25...80)
GSP  ID-No. Type	P31321 IDU 080 GSP	P31322 ID 080 GSP	-
GSOP  ID-No. Type	P31264 IDU 080 GSOP	P31265 ID 080 GSOP	-
WP  ID-No. Type	-	-	P31266 IDS 080 WP
Supply voltage [V]	10...55 DC	10...55 DC	20...250 AC
Switching current [mA]	400	400	400
Short circuit proof	•	•	3000 mA/10 ms
Reverse protection	•	•	-
Voltage drop max. [V]	2	2	6 eff.
Minimum load current [mA]	-	-	8
Current consumption [mA]	4	4	2.5
Switching frequency [Hz]	20	20	10
Ambient temperature [°C]	-25...+75	-25...+75	-25...+75
EMC-class	A	A	A
Protection [EN 60529]	IP 67	IP 67	IP 67
LED display	•	•	•
Housing material	PBT	PBT	PBT
Connection	M12 connector	GSP: 2 m PVC-cable, 3x0.5 mm ² GSOP: 2 m PVC-cable, 4x0.5 mm ²	PG-plug connection 2 m, 2x0.75 mm ² , PVC
			

Accessories

connecting cable SLG 3-2 (GSP) / SLG 4-2 (GSOP), page 3.69

Demanding environment

Series ID - Proximity switches


Ø 105 mm






DC 10...55 V

AC 20...250 V

Sensing range adjustable

Increased EMC



Design	DC PNP • Ø 105 mm	DC PNP • Ø 105 mm	AC • Ø 105 mm programmable
Dimensions Installation non flush (nf)			
Operating distance sn [mm] (Adjustable range)	100 nf (20...110)	100 nf (20...110)	70 nf (20...110)
GSP  ID-No. Type	P31323 IDU 105 GSP	P31324 ID 105 GSP	–
GSOP  ID-No. Type	P31267 IDU 105 GSOP	P31268 ID 105 GSOP	–
WP  ID-No. Type	–	–	P31269 IDS 105 WP
Supply voltage [V]	10...55 DC	10...55 DC	20...250 AC
Switching current [mA]	400	400	400
Short circuit proof	•	•	3000 mA/10 ms
Reverse protection	•	•	–
Voltage drop max. [V]	2	2	6 eff.
Minimum load current [mA]	–	–	8
Current consumption [mA]	4	4	2.5
Switching frequency [Hz]	20	20	10
Ambient temperature [°C]	–25...+75	–25...+75	–25...+75
EMC-class	A	A	A
Protection [EN 60529]	IP 67	IP 67	IP 67
LED display	•	•	•
Housing material	PBT	PBT	PBT
Connection	M12 connector	GSP: 2 m PVC-cable, 3x0.5 mm ² GSOP: 2 m PVC-cable, 4x0.5 mm ²	PG-plug connection 2 m, 2x0.75 mm ² , PVC
	GSP  GSOP  WP 		

Accessories

connecting cable SLG 3-2 (GSP) / SLG 4-2 (GSOP), page 3.69

Demanding environment

Series ID - Proximity switches

Ø 160 mm






DC 10...55 V

AC 20...250 V

Sensing range adjustable

Increased EMC



Design	DC PNP • Ø 160 mm	DC PNP • Ø 160 mm	AC • Ø 160 mm programmable
Dimensions Installation non flush (nf)			
Operating distance sn [mm] (Adjustable range)	120 nf (20...150)	120 nf (20...150)	120 nf (20...150)
GSP  ID-No. Type	P31325 IDU 160 GSP	P31326 ID 160 GSP	–
GSOP  ID-No. Type	P31270 IDU 160 GSOP	P31271 ID 160 GSOP	–
WP  ID-No. Type	–	–	P31272 IDS 160 WP
Supply voltage [V]	10...55 DC	10...55 DC	20...250 AC
Switching current [mA]	400	400	400
Short circuit proof	•	•	3000 mA/10 ms
Reverse protection	•	•	–
Voltage drop max. [V]	2	2	6 eff.
Minimum load current [mA]	–	–	8
Current consumption [mA]	4	4	2.5
Switching frequency [Hz]	20	20	10
Ambient temperature [°C]	–25...+75	–25...+75	–25...+75
EMC-class	A	A	A
Protection [EN 60529]	IP 67	IP 67	IP 67
LED display	•	•	•
Housing material	PBT / Aluminium	PBT / Aluminium	PBT / Aluminium
Connection	M12 connector	GSP: 2 m PVC-cable, 3x0.5 mm ² GSOP: 2 m PVC-cable, 4x0.5 mm ²	PG-plug connection 2 m, 2x0.75 mm ² , PVC
 1: BN 2: WH 3: BU 4: BK	GSP 	GSOP 	WP 

Accessories connecting cable SLG 3-2 (GSP) / SLG 4-2 (GSOP), page 3.69

Demanding environment

Series ID - Proximity switches


Ø 200 mm






DC 10...55 V

AC 20...250 V

Sensing range adjustable

Increased EMC



Design	DC PNP • Ø200 mm		AC • Ø200 mm programmable
Dimensions Installation non flush (nf)			
Operating distance sn [mm] (Adjustable range)	140 nf (40...170)	140 nf (40...170)	140 nf (40...170)
GSP  ID-No. Type	P31327 IDU 200 GSP	P31328 ID 200 GSP	–
GSOP  ID-No. Type	P31273 IDU 200 GSOP	P31274 ID 200 GSOP	–
WP  ID-No. Type	–	–	P31275 IDS 200 WP
Supply voltage [V]	10...55 DC	10...55 DC	20...250 AC
Switching current [mA]	400	400	400
Short circuit proof	•	•	3000 mA/10 ms
Reverse protection	•	•	–
Voltage drop max. [V]	2	2	6 eff.
Minimum load current [mA]	–	–	8
Current consumption [mA]	4	4	2.5
Switching frequency [Hz]	20	20	10
Ambient temperature [°C]	–25...+75	–25...+75	–25...+75
EMC-class	A	A	A
Protection [EN 60529]	IP 67	IP 67	IP 67
LED display	•	•	•
Housing material	PBT / Aluminium	PBT / Aluminium	PBT / Aluminium
Connection	M12 connector	GSP: 2 m PVC-cable, 3x0.5 mm ² GSOP: 2 m PVC-cable, 4x0.5 mm ²	PG-plug connection 2 m, 2x0.75 mm ² , PVC
	GSP 	GSOP 	WP 
Accessories	connecting cable SLG 3-2 (GSP) / SLG 4-2 (GSOP), page 3.69		

Analog output

Series IGA - Proximity sensors






M12 / M18

Metal sleeve

0...10 V

4...20 mA



Design	M12x1	M18x1	M18x1
Dimensions			
Installation non flush (nf)			
Analog range [mm]	0...4 nf	0...5 nf	0...5 nf
Output			
ID-No.	4...20 mA P31128	0...10 V P31040	4...20 mA P31129
Type	IGA 104 GI	IGA 005 GU	IGA 005 GI
Supply voltage [V]	18...27 DC	18...27 DC	18...27 DC
Current consumption max. [mA]	40	25	40
Voltage output max. [V]	–	11	–
Output current max. [mA]	23	–	23
Linearity deviation [%]	10	5	5
Load resistance R _L [kΩ]	<0.4	>2	<0.4
Ambient temperature [°C]	–25...+70		
Temperature deviation [%]	10		
Protection [EN 60529]	IP 67		
Housing material	Br-Ni / PBT		
Connecting	2 m PVC-cable 3x0.34 mm ²	2 m PVC-cable 3x0.5 mm ²	
Output signal with approaching iron plate ST37			
Connection diagram			






Analog output

Series IGA / IDA - Proximity sensors

M30
Ø 80 mm

0...10 V
4...20 mA



Design	M30x1.5		Ø 80 mm	
Dimensions				
Installation non flush (nf)				
Analog range [mm]	0...10 nf	0...10 nf	0...30 nf	0...30 nf
Output				
ID-No.	0...10 V P31041	4...20 mA P31130	0...10 V P31043	4...20 mA P31131
Type	IGA 010 GU	IGA 010 GI	IDA 030 GU	IDA 030 GI
Supply voltage [V]	18...27 DC	18...27 DC	18...27 DC	18...27 DC
Current consumption max. [mA]	25	40	25	40
Voltage output max. [V]	11	–	11	–
Output current max. [mA]	–	23	–	23
Linearity deviation [%]	5			
Load resistance R _L [kΩ]	>2	<0.4	>2	<0.4
Ambient temperature [°C]	–25...+70			
Temperature deviation [%]	10			
Protection [EN 60529]	IP 67			
Housing material	Br-Ni / PBT		PBT	
Connection	2 m PVC-cable 3x0.5 mm ²			
Output signal with approaching iron plate ST37				
Connection diagram				

Analog • High temperature 160 °C


Series IGT - Proximity sensors







M18

4...20 mA

**For the connection to
amplifier IKM 120 GA**

Permanent temperature 160 °C



Design	IGT 005	IKM 120 GA
Dimensions		
Installation non flush (nf)		
Analog range [mm]	0...5 nf	—
ID-No.	P31143	P31144
Type	IGT 005	IKM 120 GA
Supply voltage [V]	—	24 DC ±20%
Current consumption [mA]	—	30
Current output [mA]	—	4...20 mA
Linearity [%]	6	0.5
Load R_L [Ω]	—	50...500
Ambient temperature [°C]	-25...+160	-20...+60
Temperature deviation [%]	10	2
Protection [EN 60529]	IP 67	IP 40
Housing material	AISI 316 Ti / PKS	PC
Connection	2 m PTFE 3x0.75 mm ²	terminal screws
Output signal with approaching iron plate ST37	 	
Connection diagramm		

Standard switches

Series IGM - Proximity switches








M8 / M12

Metal sleeve

DC 10...30 V

Euronorm



Design	M8x1	DC PNP • M12x1		DC PNP • M12x1	
Dimensions					
Installation flush (f) non flush (nf)					
Operating distance sn [mm]	1.5 f	2 f	4 nf	2 f	4 nf
Switching output PNP					
ID-No.	P31013	P31104	P31105	P31106	P31107
Type	IGM 1 GSP	IGM 102 GSP	IGM 104 GSP	IGMU 102 GSP	IGMU 104 GSP
Supply voltage [V]	10...30 DC	10...30 DC	10...30 DC	10...30 DC	10...30 DC
Switching current [mA]	200	200	200	200	200
Short circuit proof	•	•	•	•	•
Overcurrent release [mA]	250	250	250	250	250
Reverse protection	•	•	•	•	•
Voltage drop max. [V]	2	2	2	2	2
Residual current [mA]	–	–	–	–	–
Current consumption (not actuated) [mA]	<11	<5	<5	<5	<5
Switching frequency [Hz]	1000	800	400	800	400
Ambient temperature [°C]	–25...+70	–25...+70	–25...+70	–25...+70	–25...+70
EMC-class	A	A	A	A	A
Protection [EN 60529]	IP 67	IP 67	IP 67	IP 67	IP 67
LED display	•	•	•	•	•
Housing material	Stainless steel / PA	Br-Ni / PPO	Br-Ni / PPO	Br-Ni / PPO	Br-Ni / PPO
Connection	2 m PVC-cable 3x0.14 mm ²	2 m PVC-cable 3x0.14 mm ²	2 m PVC-cable 3x0.14 mm ²	M12 connector	M12 connector
Accessories					

connecting cable SLG 3-2, page 3.69

Standard switches

Serie IGM - Proximity switches







M18

Metal sleeve

DC 10...30 V

Euronorm



Design	DC PNP • M18x1		DC PNP • M18x1	
Dimensions				
Installation flush (f) non flush (nf)				
Operating distance sn [mm]	5 f	8 nf	5 f	8 nf
Switching output PNP				
ID-No.	P31110	P31111	P31112	P31113
Type	IGM 105 GSP	IGM 108 GSP	IGMU 105 GSP	IGMU 108 GSP
Supply voltage [V]	10...30 DC	10...30 DC	10...30 DC	10...30 DC
Switching current [mA]	200	200	200	200
Short circuit proof	•	•	•	•
Overcurrent release [mA]	250	250	250	250
Reverse protection	•	•	•	•
Voltage drop max. [V]	1.5	1.5	1.5	1.5
Residual current [mA]	–	–	–	–
Current consumption (not actuated) [mA]	1	1	1	1
Switching frequency [Hz]	500	200	500	200
Ambient temperature [°C]	–25...+70	–25...+70	–25...+70	–25...+70
EMC-class	A	A	A	A
Protection [EN 60529]	IP 67	IP 67	IP 67	IP 67
LED display	•	•	•	•
Housing material	Br-Ni / PPO	Br-Ni / PPO	Br-Ni / PPO	Br-Ni / PPO
Connection	2 m PVC-cable 3x0.5 mm ²	2 m PVC-cable 3x0.5 mm ²	M12 connector	M12 connector
Accessories				

connecting cable SLG 3-2, page 3.69

Standard switches

Series INK - Proximity switches





Smooth-bodied switch

Ø 20 mm / Ø 34 mm

DC 10...55 V

Sensors for AC voltage are available on request



Design	DC PNP		DC PNP	
	Ø 20 mm	Ø 34 mm	Ø 20 mm programmable	Ø 34 mm
Dimensions				
Installation non flush (nf)	LED	LED	LED	LED
Operating distance sn [mm]	10 nf	20 nf	10 nf	20 nf
Switching output PNP				
ID-No.	P30159	P30166	P30158	P30165
Type	INK 010 GSP	INK 020 GSP	INKS 010 GPP	INKS 020 GPP
Supply voltage [V]	10...55 DC	10...55 DC	10...55 DC	10...55 DC
Switching current [mA]	400	400	400	400
Short circuit proof	•	•	•	•
Overcurrent release [mA]	450	450	450	450
Reverse protection	•	•	•	•
Voltage drop max. [V]	2	2	2	2
Residual current [mA]	–	–	–	–
Current consumption (not actuated) [mA]	2.5	2.5	2.5	2.5
Switching frequency [Hz]	1500	500	1500	500
Ambient temperature [°C]	–25...+75	–25...+75	–25...+75	–25...+75
EMC-class	A	A	A	A
Protection [EN 60529]	IP 67	IP 67	IP 67	IP 67
LED display	•	•	•	•
Housing material	PBT	PBT	PBT	PBT
Connection	2 m PVC-cable 3x0.5 mm ²	2 m PVC-cable 3x0.5 mm ²	2 m PVC-cable 3x0.5 mm ² (PG-plug connection)	2 m PVC-cable 3x0.5 mm ² (PG-plug connection)
PG-plug connection	DC 1: BN 2: BU 3: BK  Schalter / switch Disconnect power supply before pulling off plug connector. Spannungsversorgung abschalten bevor Steckverbindung gezogen wird. 			

Disconnect power supply before pulling off plug connector.
Spannungsversorgung abschalten bevor Steckverbindung gezogen wird.

Accessories

mounting clamps Ø 20 mm (Z00100), Ø 34 mm (Z00102) are part of delivery

Special functions • Surface sensor

Series IFE - Proximity switches

Wide detection range



DC 10...55 V

Sensitivity adjustable

Moisture-resistant

PG-plug IP 68



Design		DC PNP				
Dimensions	Installation non flush (nf)					
Operating distance sn [mm]		100 nf	100 nf	130 nf	150 nf	180 nf
Adjustable range max.		120	150	170	200	250
Switching output PNP						
ID-No.		P31016	P31018	P31020	P31022	P31024
Type		IFE 200/100 GSP	IFE 400/100 GSP	IFE 400/150 GSP	IFE 700/150 GSP	IFE 900/150 GSP
Dimensions	L	200	400	400	700	900
	B	100	100	150	150	150
	Si	108	280	230	190	182
Supply voltage [V]		10...55 DC				
Switching current [mA]		<400				
Short circuit protection		•				
Overcurrent release approx. [mA]		430				
Reverse protection		•				
Current consumption approx. [mA]		4				
Inverse current max. [μA]		1				
Residual ripple max. [%]		15				
Voltage drop max. [V]		2				
Switching frequency [Hz]		10				
Hysteresis [%]		10				
Ambient temperature [°C]		-25...+75				
Correction factors		St 37: 1	AL: 0.4	VA 4: 0.65	Cu: 0.45	ZN: 0.5 MS: 0.6
EMC-class		A				
Protection [EN 60529]		IP 68				
Housing material		PVC / Aluminium				
Connection		PG-plug connection, 2 m PVC-cable 3x0.5 mm ²				
						
Notes		see page 3.06				

Special functions • Surface sensor

Series IFE - Proximity switches

Wide detection range




AC 20...250 V

Sensitivity adjustable

Moisture-resistant

PG-plug IP 68



Design		AC				
Dimensions						
	Installation non flush (nf)					
Operating distance sn [mm]		100 nf	100 nf	130 nf	150 nf	180 nf
Adjustable range max.		120	150	170	200	250
Switching output						
ID-No.		P31015	P31017	P31019	P31021	P31023
Type		IFE 200/100 WS	IFE 400/100 WS	IFE 400/150 WS	IFE 700/150 WS	IFE 900/150 WS
Dimensions	L	200	400	400	700	900
	B	100	100	150	150	150
	Si	108	280	230	190	182
Supply voltage [V]		20...250 AC				
Switching current [mA]		< 400				
Surge current [mA]		< 3000 / 10 ms				
Overcurrent release approx. [mA]		-				
Current consumption approx. [mA]		2.5				
Inverse current approx. [mA]		2.5				
Minimum load current approx. [mA]		6				
Voltage drop max. [V]		6 eff.				
Switching frequency [Hz]		10				
Hysteresis [%]		10				
Ambient temperature [°C]		-25...+75				
Correktion factors		St 37: 1	AL: 0.4	VA 4: 0.65	Cu: 0.45	ZN: 0.5 MS: 0.6
EMC-class		A				
Protection [EN 60529]		IP 68				
Housing material		PVC				
Connection		PG-plug connection, 2 m PVC-cable 2x0.75 mm²				
						
Notes		see page 3.06				

Special functions • Offshore

Series IGMO - Proximity switches

M12 / M18

Stainless steel sleeve




DC 10...30 V

High compressive strength

Longitudinal water blocked cable

Sea water proofed



Design	DC PNP • M12x1	DC PNP • M18x1
Dimensions		
Installation flush (f)		
Operating distance sn [mm]	2 f	5 f
Switching output PNP		
ID-No.	P31223	P31224
Type	IGMO 02 GSP	IGMO 05 GSP
Supply voltage [V]	10...30 DC	
Switching current [mA]	200	
Short circuit proof	•	
Reverse protection	•	
Current consumption [mA]	4	
Switching frequency [Hz]	200	
Ambient temperature [°C]	-25...+70	
Compressive strength [bar]	30	
Protection [EN 60529]	IP 68	
Housing material	PTFE / AISI 316 Ti	
Sealing material	FKM	
Connection	1 m longitudinal water blocked cable	
		

Special functions • Offshore

Series IGVO - Proximity switches




M18 / M30

One piece stainless steel housing

DC 10...30 V

**High compressive strength
Longitudinal water blocked cab
Sea water proofed**



Design	DC PNP • M18x1	DC PNP • M30x1.5
Dimensions		
Installation flush (f)		
Operating distance sn [mm]	5 b	10 b
Switching output PNP		
ID-No.	P31365	P31366
Type	IGVO 05 GSP	IGVO 10 GSP
Supply voltage [V]	10...30 DC	
Switching current [mA]	250	
Short circuit proof	•	
Reverse protection	•	
Current consumption max. [mA]	5	
Switching frequency [Hz]	180	150
Ambient temperature [°C]	-25...+70	
Compressive strength [bar]	30	
Protection [EN 60529]	IP 68 + IP 69K	
EMC-class	A	
Housing material	AISI 316 L	
Sealing material	FKM	
Connection	1 m longitudinal water blocked cable PLWDC-cable 3x0.5 mm ²	
		

Special functions • Washing resistant

Series IDKW - Proximity switches

DC 10...30 V





110 °C Permanent temperature

Resistant to hot steam

Resistant to detergents

IP 68 + IP 69K



Design	DC PNP • Ø 80 mm	DC PNP • Ø 120 mm
Dimensions		
Installation non flush (nf)		
Operating distance sn [mm]	55 nf	90 nf
Switching output PNP		
ID-No.	P31214	P31177
Type	IDKW 080 GSP	IDKW 120 GSP
Supply voltage [V]	10...30 DC	
Switching current [mA]	300	
Hysteresis	<0.1 Sn	
Voltage drop max. [V]	2	
Current consumption [mA]	10	
Switching frequency [Hz]	30	
Ambient temperature [°C]	-20...+110	
Limiting temperature [°C]	120	
Temperature deviation [%]	≤10	
EMC-class	A	
Protection [EN 60529]	IP 68 + IP 69K	
Housing material	PP / AISI 316 Ti	
Sealing material	EPDM	
Connection	5 m FEP-cable 3x0.75 mm², shielded	
Switching current		
		

Special functions • Factor 1

Series IGB / IDB - Proximity switches

M30

Ø 80 mm / Ø 160 mm

DC 10...30 V

**Correction factor 1
for all metals**



Design	M30x1.5	M30x1.5	Ø 80 mm	Ø 160 mm
Dimensions				
Installation flush (f) non flush (nf) adjustable (a)				
Operating distance sn [mm]	10 f	20 nf	70 nf-a	150 nf-a
Switching output PNP				
ID-No.	P31135	P31136	P31141	P31142
Type	IGBS 010 GSP	IGBS 020 GSP	IDBS 080 GPP	IDBS 160 GPP
Supply voltage [V]	10...30 DC			
Switching current [mA]	200			
Short circuit proof	•			
Current consumption [mA]	25			
Reverse protection	•			
Voltage drop max. [V]	2			
Switching frequency [Hz]	300		20	
Ambient temperature [°C]	-25...+75			
EMC-class	A			
Protection [EN 60529]	IP 67			
Housing material	Br-Ni / PBT		PBT / Aluminium	
Connection	M12 connector		PG-plug connection 2 m, 3x0.5 mm² PVC	
PG-plug-system				
AC 1: BN 2: BU 3: BK				
DC 1: BN 2: BU 3: BK				
Schalter / switch				
Disconnect power supply before pulling off plug connector. Spannungsversorgung abschalten bevor Steckverbindung gezogen wird.				

AC 1: BN 2: BU 3: BK
DC 1: BN 2: BU 3: BK

 Schalter / switch
 Disconnect power supply before pulling off plug connector.
 Spannungsversorgung abschalten bevor Steckverbindung gezogen wird.

Metal face sensors • Speed sensor • $-40...+150\text{ }^{\circ}\text{C}$

Series HGVH


Detection of ferromagnetic targets



One piece stainless steel housing


$-40...+150\text{ }^{\circ}\text{C}$

IP 68 Water-proofed

IP 69K Resistant to high pressure cleaning



Design	DC PNP • M18x1
Dimensions	
Operating distance sn [mm]	3
Switching output PNP	
ID-No.	P31364
Type	HGVH 03 GSP
Supply voltage [V]	10...30 DC
Switching current max. [mA]	100
Short circuit proof	•
Reverse protection	•
Voltage drop max. [V]	1.5
Current consumption max. [mA]	20
Switching frequency [Hz]	6000
Ambient temperature [$^{\circ}\text{C}$]	$-40...+150$
EMC-class	A
Protection [EN 60529]	IP 68 + IP 69K
Housing material	AISI 316 L
Connection	2 m FEP-cable 3x0.34 mm ²
	



Probes
Compact models
Amplifiers

Dust - Compact model • Zone 20






Series IGEX20 - Proximity switches

Category 1

Dust Zone 20

Direct connection to DC 24 V
PNP switching output



Design	DC PNP • M18x1		DC PNP • M30x1.5	
Dimensions				
Installation flush (f) non flush (nf)				
Operating distance [mm]	5 f	8 nf	10 f	15 nf
Switching output PNP				
ID-No.	P31178	P31179	P31180	P31181
Type	IGEX20 05 GSP	IGEX20 08 GSP	IGEX20 10 GSP	IGEX20 15 GSP
Ex marking	II 1D T80 °C IP 67			
Certificate No.	ÜV 05 ATEX 2845 X			
Supply voltage [V]	10...30 DC			
Switching current [mA]	100			
Short circuit proof	•			
Reverse protection	•			
Voltage drop max. [V]	2			
Residual current [mA]	-			
Current consumption [mA]	7			
Switching frequency [Hz]	200			
Ambient temperature [°C]	-20...+70			
EMC-class	A			
Protection [EN 60529]	IP 67			
LED display	•			
Housing material	Br-Ni / PA			
Connection	2 m PVC-cable 3x0.5 mm ²			
				
Accessories	housing for screw terminals series GK...			

Series IGEXU - Proximity switches

Gas-Ex Category 1

 II 1G Ex ia IIC T6 Ga

Dust-Ex Category 1

 II 1D Ex ia IIIC T80 °C Da



Design	M12x1		M18x1		M30x1.5	
Dimensions						
Installation flush (f) non flush (nf)						
Operating distance [mm]	2 f	4 nf	5 f	8 nf	10 f	15 nf
ID-No.	P31196	P31197	P31198	P31199	P31200	P31201
Type	IGEXU 02	IGEXU 04	IGEXU 05	IGEXU 08	IGEXU 10	IGEXU 15
Ex area of use	Gas: Zone 0/1 / Dust: Zone 20/21					
Certificate No.	TÜV 15 ATEX 163839 X					
Ex marking	Gas: II 1G Ex ia IIC T6 Ga Dust: II 1D Ex ia IIIC T80 °C Da					
Ambient temperature [°C] and medium temperature	Gas Zone 0: T6: -20 ≤ Ta ≤ +60 T5: -20 ≤ Ta ≤ +60 T4: -20 ≤ Ta ≤ +60 T3: -20 ≤ Ta ≤ +60 Dust Zone 20: -25 ≤ Ta ≤ +75		Gas Zone 1: T6: -25 ≤ Ta ≤ +75 T5: -25 ≤ Ta ≤ +75 T4: -25 ≤ Ta ≤ +75 T3: -25 ≤ Ta ≤ +75 Dust Zone 21: -25 ≤ Ta ≤ +75			
Maximum values	Ui = 12.6 V / li = 15.9 mA / Pi = 50 mW / Ci = 22 nF / Li = 3 mH					
Housing material	Br-Ni / PA					
Protection [EN 60529]	IP 67					
Connection	M12 connector					
For the connection to amplifiers IKM 122 Ex..., see page 3.67	Explosionsgefährdeter Bereich Hazardous Area Sicherer Bereich Safe Area					
Accessories	plug-lock type PL-M12 (Z01182), page 3.69					

Series IGEX - Proximity switches








Gas-Ex Category 1

 II 1G Ex ia IIC T6 Ga

Dust-Ex Category 1

 II 1D Ex ia IIIC T80 °C Da



Design	M12x1		M18x1		M30x1.5	
Dimensions						
Installation flush (f) non flush (nb)						
Operating distance [mm]	2 f	4 nf	5 f	8 nf	10 f	15 nf
ID-No.	P31151	P31152	P31153	P31154	P31155	P31156
Type	IGEX 02	IGEX 04	IGEX 05	IGEX 08	IGEX 10	IGEX 15
Ex area of use	Gas: Zone 0/1 / Dust: Zone 20/21					
Certificate No.	TÜV 15 ATEX 163839 X					
Ex marking	Gas:  II 1G Ex ia IIC T6 Ga Dust:  II 1D Ex ia IIIC T80 °C Da					
Ambient temperature [°C] and medium temperature	Gas Zone 0: T6: $-20 \leq T_a \leq +60$ T5: $-20 \leq T_a \leq +60$ T4: $-20 \leq T_a \leq +60$ T3: $-20 \leq T_a \leq +60$ Dust Zone 20: $-25 \leq T_a \leq +75$		Gas Zone 1: T6: $-25 \leq T_a \leq +75$ T5: $-25 \leq T_a \leq +75$ T4: $-25 \leq T_a \leq +75$ T3: $-25 \leq T_a \leq +75$ Dust Zone 21: $-25 \leq T_a \leq +75$			
Maximum values	$U_i = 12.6 \text{ V}$ / $I_i = 15.9 \text{ mA}$ / $P_i = 50 \text{ mW}$ / $C_i = 22 \text{ nF}$ / $L_i = 3 \text{ mH}$					
Housing material	Br-Ni / PA					
Protection [EN 60529]	IP 67					
Connection	2 m PVC-cable 2x0.5 mm ²					
For the connection to amplifiers IKM 122 Ex..., see page 3.67	Explosionsgefährdeter Bereich Hazardous Area  Sicherer Bereich Safe Area					
Note	proximity switches with cable length >2 m are available on request					

Series IGEXH - Proximity switches

Gas-Ex Category 1





 II 1G Ex ia IIC T6 Ga

Dust-Ex Category 1

 II 1D Ex ia IIIC T145 °C Da

High temperature sensors +140 °C



Design	M12x1		M18x1		M30x1.5	
Dimensions						
Installation flush (f) non flush (nf)						
Operating distance [mm]	2 f	4 nf	5 f	8 nf	10 f	15 nf
ID-No.	P31367	P31368	P31369	P31370	P31371	P31372
Type	IGEXH 02	IGEXH 04	IGEXH 05	IGEXH 08	IGEXH 10	IGEXH 15
Ex area of use	Gas: Zone 0/1 / Dust: Zone 20/21					
Certificate No.	TÜV 15 ATEX 163839 X					
Ex marking	Gas:  II 1G Ex ia IIC T6 Ga Dust:  II 1D Ex ia IIIC T145 °C Da					
Ambient temperature [°C] and medium temperature	Gas Zone 0: T6: $-20 \leq T_a \leq +60$ T5: $-20 \leq T_a \leq +60$ T4: $-20 \leq T_a \leq +60$ T3: $-20 \leq T_a \leq +60$ Dust Zone 20: $-25 \leq T_a \leq +140$		Gas Zone 1: T6: $-25 \leq T_a \leq +75$ T5: $-25 \leq T_a \leq +90$ T4: $-25 \leq T_a \leq +125$ T3: $-25 \leq T_a \leq +140$ Dust Zone 21: $-25 \leq T_a \leq +140$			
Maximum values	$U_i = 12.6 \text{ V}$ / $I_i = 15.9 \text{ mA}$ / $P_i = 50 \text{ mW}$ / $C_i = 22 \text{ nF}$ / $L_i = 3 \text{ mH}$					
Housing material	AISI 316 Ti / PEEK					
Protection [EN 60529]	IP 68					
Connection	2 m FEP-cable 2x0.34 mm ²					
For the connection to amplifiers IKM 122 Ex..., see page 3.67	Explosionsgefährdeter Bereich Hazardous Area Sicherer Bereich Safe Area 					
Note	proximity switches with cable length > 2 m are available on request					

Series IGEXP - Proximity switches

Gas-Ex Category 1








 II 1G Ex ia IIC T6 Ga

Dust-Ex Category 1

 II 1D Ex ia IIIC T65 °C Da

POLAR-Sensors –60 °C



Design	M12x1		M18x1		M30x1.5	
Dimensions						
Installation flush (f) non flush (nf)						
Operating distance [mm]	2 f	4 nf	5 f	8 nf	10 f	15 nf
ID-No.	P31373	P31374	P31375	P31376	P31377	P31378
Type	IGEXP 02	IGEXP 04	IGEXP 05	IGEXP 08	IGEXP 10	IGEXP 15
Ex area of use	Gas: Zone 0/1 / Dust: Zone 20/21					
Certificate No.	TÜV 15 ATEX 163839 X					
Ex marking	Gas:  II 1G Ex ia IIC T6 Ga Dust:  II 1D Ex ia IIIC T65 °C Da					
Ambient temperature [°C] and medium temperature	Gas Zone 0: T6: $-20 \leq T_a \leq +60$ T5: $-20 \leq T_a \leq +60$ T4: $-20 \leq T_a \leq +60$ T3: $-20 \leq T_a \leq +60$ Dust Zone 20: $-60 \leq T_a \leq +60$		Gas Zone 1: T6: $-60 \leq T_a \leq +60$ T5: $-60 \leq T_a \leq +60$ T4: $-60 \leq T_a \leq +60$ T3: $-60 \leq T_a \leq +60$ Dust Zone 21: $-60 \leq T_a \leq +60$			
Maximum values	$U_i = 12.6 \text{ V}$ / $I_i = 15.9 \text{ mA}$ / $P_i = 50 \text{ mW}$ / $C_i = 22 \text{ nF}$ / $L_i = 3 \text{ mH}$					
Housing material	AISI 316 Ti / PTFE					
Protection [EN 60529]	IP 68					
Connection	2 m FEP-cable 2x0.34 mm ²					
For the connection to amplifiers IKM 122 Ex..., see page 3.67	Explosionsgefährdeter Bereich Hazardous Area  Sicherer Bereich Safe Area Auswertegerät Amplifier Betriebsspannung / Supply voltage Relais Ausgang / Relay output					
Note	proximity switches with cable length > 2 m are available on request					

Dust - Compact model • Zone 22

Series IGEX22 - Proximity switches








Category 3

Dust  Zone 22

DC 24 V

PNP switching output



Design	DC PNP • M12x1		DC PNP • M18x1		DC PNP • M30x1.5	
Dimensions						
Installation flush (f) non flush (nf)						
Operating distance [mm]	2 f	4 nf	5 f	8 nf	10 f	15 nf
Switching output PNP						
ID-No.	P31187	P31188	P31189	P31190	P31191	P31192
Type	IGEX22 02 GSPU	IGEX22 04 GSPU	IGEX22 05 GSPU	IGEX22 08 GSPU	IGEX22 10 GSPU	IGEX22 15 GSPU
Ex marking	 II 3D Ex mc IIIC T 80 °C Dc IP 67 X					
Supply voltage [V]	10...30 DC					
Switching current [mA]	200					
Short circuit proof	•					
Overcurrent release [mA]	250					
Reverse protection	•					
Voltage drop max. [V]	2					
Residual current [mA]	-					
Current consumption [mA]	7					
Switching frequency [Hz]	500					
Ambient temperature [°C]	-25...+70					
EMC-class	A					
Protection [EN 60529]	IP 67					
LED display	•					
Housing material	Br-Ni / PBT					
Connection	M12 connector					
						
Accessories	connection cable SLG 3-2 (Z01076), plug-lock type PL-M12 (Z01182), page 3.69					

Dust - Compact model • Zone 22

Series IGEX22 - Proximity switches





Category 3

Dust Zone 22

DC 24 V

PNP switching output



Design	DC PNP • M12x1		DC PNP • M18x1		DC PNP • M30x1.5	
Dimensions						
Installation flush (f) non flush (nf)						
Operating distance [mm]	2 f	4 nf	5 f	8 nf	10 f	15 nf
Output PNP						
ID-No.	P31165	P31166	P31167	P31168	P31169	P31170
Type	IGEX22 02 GSP	IGEX22 04 GSP	IGEX22 05 GSP	IGEX22 08 GSP	IGEX22 10 GSP	IGEX22 15 GSP
Ex marking	Ⓔ II 3D Ex mc IIIC T 80 °C Dc IP 67 X					
Supply voltage [V]	10...30 DC					
Switching current [mA]	200					
Short circuit proof	•					
Overcurrent release [mA]	250					
Reverse protection	•					
Voltage drop max. [V]	2					
Residual current [mA]	–					
Current consumption [mA]	7					
Switching frequency [Hz]	500					
Ambient temperature [°C]	–25...+70					
EMC-class	A					
Protection [EN 60529]	IP 67					
LED display	•					
Housing material	Br-Ni / PBT					
Connection	2 m PVC-cable 3x0.34 mm²					
						

Dust - Compact model • Zone 22

Series IGVE22 - Proximity switches

Stainless steel




Category 3


Dust  Zone 22

DC 24 V

PNP switching output



Design	DC PNP • M12x1	DC PNP • M18x1	DC PNP • M30x1,5
Dimensions			
Operating distance [mm]	2	5	10
Switching output PNP			
ID-No.	P31285	P31286	P31287
Type	IGVE22 02 GSPU	IGVE22 05 GSPU	IGVE22 10 GSPU
Ex marking	 II 3D Ex mc IIIC T 95 °C Dc IP 67 X		
Supply voltage [V]	10...30 DC		
Switching current [mA]	200		
Short circuit proof	•		
Reverse protection	•		
Voltage drop max. [V]	1,5		
Current consumption [mA]	12		
Switching frequency [Hz]	180		
Ambient temperature [°C]	-25...+70		
EMC class	A		
Protection [EN 60529]	IP 67		
LED display	•		
Housing material	AISI 316 L		
Connection	M12 connector		



Accessories connection cable SLG 3-2 (Z01076), plug-lock type PL-M12 (Z01182), page 3.69





Series IDEX - Proximity switches

Category 1

Dust  Zone 20

Gas  Zone 0



Design	Ø80 mm	Ø100 mm	Ø160 mm
Dimensions Installation non flush (nf)			
Operating distance [mm] (Adjustable range)	55 nf (10...70)	70 nf (10...100)	120 nf (20...150)
ID-No.	P31157	P31158	P31159
Type	IDEX 080	IDEX 100	IDEX 160
Ambient temperature [°C]	-25...+75		
Ex marking	Ex II 1G Ex ia IIC T6 / Ex II 1D T100 °C		
Certificate No.	TÜV 03 ATEX 2037		
Ambient temperatures for temperature classes [°C]	T6 : 75 T5 : 90		
Maximum values	Ci = 120 nF Li = negligibly small Ii = 80 mA Ui = 12.6 V Pi = 252 mW		
Only for the connection to certified intrinsically safe circuits with the following maximum values:			
Housing material	PA / Aluminium		
Protection [EN 60529]	IP 67		
Connection	2 m PVC-cable 3x0.5 mm ²		
For the connection to amplifiers IKM 123 Ex..., see page 3.68			

Dust - Compact model • Zone 22


Series IDEX22 - Proximity switches








Category 3

Dust Zone 22

DC 24 V

PNP switching output



Design	DC PNP • Ø80 mm	DC PNP • Ø105 mm	DC PNP • Ø160 mm
Dimensions			
Installation non flush (nf)			
Operating distance [mm] (Adjustable range)	55 nf (10...80)	100 nf (10...110)	120 nf (20...150)
Switching output PNP			
ID-No.	P31329	P31330	P31331
Type	IDEX22 080 GSPU	IDEX22 105 GSPU	IDEX22 160 GSPU
Ex marking	 II 3D Ex mc IIIC T 80 °C Dc IP 67 X		
Supply voltage [V]	10...30 DC		
Switching current [mA]	200		
Short circuit proof	•		
Overcurrent release [mA]	450		
Reverse protection	•		
Voltage drop max. [V]	2		
Residual current [mA]	-		
Current consumption [mA]	7		
Switching frequency [Hz]	20		
Ambient temperature [°C]	-20...+70		
EMC-class	A		
Protection [EN 60529]	IP 67		
LED display	•		
Housing material	PBT	PBT	PBT / Aluminium
Connection	M12 connector	M12 connector	M12 connector
Accessories			
	connection cable SLG 3-2 (Z01076), page 3.69		

- Amplifiers

Series IKM 122 Ex

Dust 



Gas 

**Cable break and
short circuit monitoring**

**Connection to intrinsically safe
2-lead sensors**

Output function programmable



Design	IKM 122 Ex...	
Dimensions		
ID-No.	P31332	P31333
Type	IKM 122 Ex-230	IKM 122 Ex-24
Output	 relay / change over	
Ex area of use	outside of the hazardous areas (gas or dust)	
Certificate No.	TÜV 11 ATEX 556280	
Ex marking	Gas:  II (1) G [Ex ia Ga] IIC Dust:  II (1) D [Ex ia Da] IIIC	
Ambient temperature	[°C] -20 ≤ Ta ≤ +60	
Maximum values	Uo = 9.6 V / Io = 10.1 mA / Po = 24.2 mW / Co = 0.84 µF / Lo = 5.00 mH	
Supply voltage	[V] 230 AC ±10%	24 DC ±10%
Switching voltage max	[V] 250 AC / 60 DC / 24 DC	
Switching current max.	[A] 4 AC / 0.8 DC / 4 DC	
Switching power	cos φ >0.7 / L/R ≤200 ms / L/R ≤200 ms	
Protection	[EN 60529] IP 40	
Connection	terminal screws	
	Explosionsgefährdeter Bereich Hazardous Area  Sicherer Bereich Safe Area  L1 / + Betriebsspannung N / - Supply voltage Relais Ausgang / Relay output	

- Amplifiers

Series IKM 123 Ex

Dust 




Gas 

Cable break and
short circuit monitoring

Connection to intrinsically safe
3-lead sensors

Output function programmable



Design	IKM 122 Ex...	
Dimensions		
ID-No.	P31335	P31336
Type	IKM 123 Ex-230	IKM 123 Ex-24
Output	 relay / change over	
Ex area of use	outside of the hazardous areas (gas or dust)	
Certificate No.	TÜV 11 ATEX 556280	
Ex marking	Gas:  II (1) G [Ex ia Ga] IIC Dust:  II (1) D [Ex ia Da] IIIC	
Ambient temperature [°C]	-20 ≤ Ta ≤ +60	
Maximum values	U ₀ = 9.6 V / I ₀ = 50.5 mA / P ₀ = 121.3 mW / C ₀ = 0.68 µF / L ₀ = 5.00 mH	
Supply voltage [V]	230 AC ±10%	24 DC ±10%
Switching voltage max [V]	250 AC / 60 DC / 24 DC	
Switching current max. [A]	4 AC / 0.8 DC / 4 DC	
Switching power	cos φ > 0.7 / L/R ≤ 200 ms / L/R ≤ 200 ms	
Protection [EN 60529]	IP 40	
Connection	terminal screws	
	Explosionsgefährdeter Bereich Hazardous Area  Sicherer Bereich Safe Area  15 L1 / + Betriebsspannung 16 N / - Supply voltage 10 Relais Ausgang / 9 Relay output 12	


Accessories • M12 connector

System SL


Finished cable plug housing

Self locking screw plug

Protection IP 67




Cable plug housing



SLG...


SLW...

Pin-assignment



DC

Plug-lock



PL-M12

TYPE	ID-NO.	DESIGN
SLG 3-2	Z01076	Cable plug housing straight, 2 m cable 3x0.34 mm ² max. 250 V / 4 A
SLG 3-5	Z01077	Cable plug housing straight, 5 m cable 3x0.34 mm ² max. 250 V / 4 A
SLW 3-2	Z01078	Cable plug housing angular, 2 m cable 3x0.34 mm ² max. 250 V / 4 A
SLW 3-5	Z01079	Cable plug housing angular, 5 m cable 3x0.34 mm ² max. 250 V / 4 A
SLW 3-2-LED	Z00052	Cable plug housing angular, 2 m cable 3x0.34 mm ² max. 250 V / 4 A PNP with LED
SLG 4-2	Z00445	Cable plug housing straight, 2 m cable 4x0.25 mm ² max. 250 V / 4 A
SLG 4-5	Z00449	Cable plug housing straight, 5 m cable 4x0.25 mm ² max. 250 V / 4 A
SLW 4-2	Z00446	Cable plug housing angular, 2 m cable 4x0.25 mm ² max. 250 V / 4 A
SLW 4-5	Z00450	Cable plug housing angular, 5 m cable 4x0.25 mm ² max. 250 V / 4 A
SLW 4-2-LED	Z01157	Cable plug housing angular, 2 m cable 4x0.25 mm ² max. 250 V / 4 A PNP with LED
SLG 5-2	Z01150	Cable plug housing straight, 2 m cable 5x0.34 mm ² max. 60 V / 2 A
SLW 5-2	Z01151	Cable plug housing angular, 2 m cable 5x0.34 mm ² max. 60 V / 2 A
SLG 6-2	Z01197	Cable plug housing straight, 2 m cable 6x0.25 mm ² max. 36 V / 2 A
SLW 6-2	Z01198	Cable plug housing angular, 2 m cable 6x0.25 mm ² max. 36 V / 2 A
PL-M12	Z01182	Plug-lock for sensors in Ex areas

DATA

Thread	M12x1	Contact resistance	≤ 5 mΩ
Material	PVC	Insulation resistance	>10 ⁹
Protection	IP 67	Testing voltage	2.0 KV eff. / 5 and 6 pol. 1.5 KV eff.
Temperature range	-25...+80 °C		

Note


Sensors with NC output are connected to 4 pole cable plug housings. In this case, the break output is connected to the white lead (connection 2).

Accessories • PG plug system

PG plug system

PG plug type connection with PVC-cable Protection IP 68

PG-plug connection



Mounting of PG plug system

Connect the cable to the EGE-plug (2) and put it into the plug-housing (1) until it is at the stop. Make sure that the "nose" of the plug fits exactly into the housing. If this is done in the right way, the plug is hidden in the plug-housing.

Screw part (3) into the plug-housing (1) and fix it rightly with a spanner. After about 2 hours righten it again with the spanner.

Now fit the nut (4) by hand and afterwards with a spanner. Do not apply too much force. For a good sealing there should be stet 2 mm between nut (4) and part (3).

TYPE	ID-NO.	DESIGN
PG 2-2	Z00025	PG-plug connection, 2 m PVC-cable 2x0.75 mm ² AC
PG 2-3	Z00026	PG-plug connection, 3 m PVC-cable 2x0.75 mm ² AC
PG 2-5	Z00027	PG-plug connection, 5 m PVC-cable 2x0.75 mm ² AC
PG 2-10	Z00028	PG-plug connection, 10 m PVC-cable 2x0.75 mm ² AC
PG 2-20	Z00029	PG-plug connection, 20 m PVC-cable 2x0.75 mm ² AC
PG 3-2	Z00020	PG-plug connection, 2 m PVC-cable 3x0.5 mm ² DC
PG 3-3	Z00021	PG-plug connection, 3 m PVC-cable 3x0.5 mm ² DC
PG 3-5	Z00022	PG-plug connection, 5 m PVC-cable 3x0.5 mm ² DC
PG 3-10	Z00023	PG-plug connection, 10 m PVC-cable 3x0.5 mm ² DC
PG 3-20	Z00024	PG-plug connection, 20 m PVC-cable 3x0.5 mm ² DC

Note

The power supply must be disconnected before the plug will be installed or removed.

Code: BK = black BN = brown BU = blue GN = green YE = yellow GY = grey PK = pink WH = white

Accessories • Assembly parts

Lock nuts, brass-nickel - plated

ID-NO.	Z00106	Z00107	Z00114	Z00109	Z00110
Nut thickness [mm]	4	4	4	5	5
Thread	M12x1	M18x1	M22x1	M30x1.5	M38x1.5
Spanner size	17	24	27	36	50

Lock nuts, special steel

ID-NO.	Z01098	Z00112	Z00113	Z00115
Nut thickness [mm]	4	4	4	5
Thread	M8x1	M12x1	M18x1	M30x1.5
Spanner size	13	17	24	36

Lock nuts, plastics

ID-NO.	Z00180	Z00120	Z00117	Z00118	Z00119	Z01092	Z01052
Nut thickness [mm]	6	8	4	5	5,5	8	8
Thread	M14x1	M30x1.5	M12x1	M18x1	M30x1.5	G 3/4	G 1
Spanner size	22	41	17	24	36	41	50
Material	PTFE	PTFE	PPE	PPE	PPE	PTFE	PTFE

Central screw, polyamide

Z00104	M12, length 70 mm, hexagon socket 10 mm, material PA
Z00105	M16, length 90 mm, hexagon socket 14 mm, material PA

MOUNTING CLAMPS

TYPE	ID-NO.	DIMENSIONS	DESIGN																		
KLS 20 KLS 34	Ø 20 Ø 34	Z00100 Z00102	Clamps of PA, for smooth-bodied switches																		
			<table><tr><td>F</td><td>Ø 20</td><td>Ø 34</td></tr><tr><td>A</td><td>47</td><td>61</td></tr><tr><td>B</td><td>30</td><td>47</td></tr><tr><td>C</td><td>17</td><td>15</td></tr><tr><td>D</td><td>32</td><td>45</td></tr><tr><td>E</td><td>M5x30</td><td>M5x50</td></tr></table>	F	Ø 20	Ø 34	A	47	61	B	30	47	C	17	15	D	32	45	E	M5x30	M5x50
F	Ø 20	Ø 34																			
A	47	61																			
B	30	47																			
C	17	15																			
D	32	45																			
E	M5x30	M5x50																			
KLB 35	Ø 35	Z00125	Clamp of PTFE (Teflon), for smooth-bodied switches hexagon socket screw M5x40																		
KBM 025 KBM 030 KBM 035	Ø 25 Ø 30 Ø 35	Z01189 Z01188 Z01187	Mounting clamp of Aluminium																		
			<table><tr><td>Type</td><td>D</td></tr><tr><td>KBM 025</td><td>Ø 25</td></tr><tr><td>KBM 030</td><td>Ø 30</td></tr><tr><td>KBM 035</td><td>Ø 35</td></tr></table>	Type	D	KBM 025	Ø 25	KBM 030	Ø 30	KBM 035	Ø 35										
Type	D																				
KBM 025	Ø 25																				
KBM 030	Ø 30																				
KBM 035	Ø 35																				



Headquarters
EGE-Elektronik
Spezial-Sensoren GmbH

Ravensberg 34
D-24214 Gettorf
Tel. +49 (0) 4346 / 41580
Fax +49 (0) 4346 / 5658

Internet: www.ege-elektronik.com



EGE-Elektronik ApS
Forstallé 79
DK-6200 Aabenraa
Tel. +45 70207271
Fax +45 70207272



EGE-Specialsensorer AB
Stationsgatan 4
S-51250 Svenljunga
Tel. +46 32512060
Fax +46 32512064



Stork AS
Brynsveien 100
N-1352 Kolsås
Tel. +47 67176400
Fax +47 67176401



Vision Systems OY
PL353
FI-40101 Jyväskylä
Tel. +358 (0)10 322 7100
Fax +358 (0)10 322 7119



Molex France
18 Parc Burospace
F-91571 Bièvres Cedex
Tel. +33 2 32 96 04 28
Fax +33 2 32 96 04 21



Cematic-Electric B.V.
Spinel 200
NL-3316 LG Dordrecht
Telefon +31 74 2433422
Telefax +31 74 2913333



ICM Ital Control Meters Srl
Via della Valle 67
I-20048 Carate Brianza (Mi)
Tel. +39 0362 8052 00
Fax +39 0362 8052 01



Bibus Spain, S. L.
Rua do Arroncal, Vial C – Nave 4A
ES-36350 Nigran
Tel. +34 986 247286
Fax +34 986 209247



Powelectrics Limited
Unit 12 Ninian Park
Ninian Way
Tamworth
GB-Staffordshire B77 5ES
Tel. +44 1827 310666
Fax +44 1827 310999



Bachofen AG
Ackerstraße 42
CH-8610 Uster
Tel. +41 449441111
Fax +41 449441233



VWR International GmbH
Graumannsgasse 7
A-1150 Wien
Tel. +43 1 97 002 - 0
Fax +43 1 97 002 - 600



Countapulse Controls (PTY) LTD.
P.O.B. 40393
ZA-2022 Cleveland
Tel. +27 116157556
Fax +27 116157513



HITECH Ltd.
1-35-2 Simouma, Setagaya,
JPN-Tokyo 154-0002
Tel. +81 35430 2301
Fax +81 35430 2302



Micromax S&A P/L
Unit 2 106-110 Beaconsfield Street
AUS-Silverwater NSW 2128
Tel. +61 1300 362626
Fax +61 1300 017100



**PROTEK TEKNİK ELEKTRİK
TİC.SAN.LTD.ŞTİ.**
Okçumusa Cad. Kismet Han
No: 36/2 P.K.
TR-34420 Karaköy-Istanbul
Tel. +90 212 237 20 00
Fax +90 212 235 46 09



IAC & Associates
2180 Fasan Drive
Oldcastle
CDN-Ontario N0R 1L0
Tel. +1 519 7370311
Fax +1 519 7370314
TF +1 800 711 1900



Yuden-Tech Co., Ltd.
5F., No. 121, Lide St.,
Zhonghe City, Taipei County 235,
Taiwan (R.O.C.)
Tel. +886 2 8221 2958
Fax +886 2 8221 2492



**Shanghai Beishidietian
Business Trade Co., Ltd.**
4F, No. 88-1, Lane 7039,
Zhongchun Rd., Minhang Area
Shanghai City
Tel. +86 21 54887307
Fax +86 21 54887305



CSE-W. Arthur Fischer Ltd.
15 Polaris Place, Greenmount
NZ-East Tamaki, Auckland
Tel. +64 9271 3810
Fax +64 9265 1362



KOLEKTOR SISTEH d.o.o.
Šlandrova ulica 10
SI-1231 Ljubljana - Črnuče
Slovenija
Tel. +386 1 5636 300
Fax +386 1 7227 930



Introl Sp. z o.o.
ul. Kościuszki 112
40-519 Katowice
Tel. +48 32 789 00 00
Fax +48 32 205 33 77



Bibus Portugal, LDA
Centro Empresarial AAA
Rua Ponte da Pedra, 240 - C4
4470-108 Gueifães - Maia
Porto
Tel. +351 22 906 50 50
Fax +351 22 906 50 53



Futron Electronics PTE Ltd.
1004 Toa Payoh North
#04-08/09/10
Singapore 318995
Tel. +65 6250 2456
Fax +65 6250 6592



Useong Electrade Co.,
D-1006, Technopark
No. 1345, Soha-dong, Gwangmyeong-si
Gyeonggi-do,
Korea
Tel. +82 (0) 2 2686 7314
Fax +82 (0) 2 2686 7316