

ALLM. KONSTRUKTIONS- OCH MASKINSTÅL

Runt							
Dim. mm	kg/m	S355J2	S355J2+M Ovako	S355J2 Hydax15 Ovako	C45E (SS 1672)	Centerlesslipad axel ISO h6/h8	
		kr/kg	kr/kg	kr/kg	kr/kg	20MnV6 (2142) ISO h6	C45E (1672) ISO h8
8	0,39						
10	0,62					26:70	26:30
12	0,89					25:30	25:30
14	1,21						24:30
15	1,39					26:–	24:30
16	1,58		16:70			25:30	24:30
18	2,00						24:30
19	2,23		16:70				
20	2,47		16:70			23:70	22:40
24	3,55		16:70				
25	3,85		16:70			23:70	22:40
30	5,55		16:70	17:90		23:70	22:40
32	6,31		16:70				
35	7,55		16:70	17:90		23:70	22:40
38	8,90		16:70				
40	9,86	15:–	16:70	17:90	16:95	23:70	22:40
42,0 SK	10,90		16:70				
45	12,50		16:70	17:90	16:95	23:70	22:40
50	15,40	15:–	16:70	17:90	16:95	23:70	22:40
55	18,70		16:70	17:90	16:95	23:70	22:40
60	22,20	15:–	16:70	17:90	16:95	23:70	22:40
65	26,10		16:70	17:90	16:95	23:70	
70	30,20	15:–	16:70	17:90	16:95	23:70	22:40
75	34,70		16:70	17:90	16:95	23:70	22:40
80	39,50	15:–	16:70	17:90	16:95	23:70	22:40
85	44,50		16:70	17:90	16:95		23:20
90	49,90	15:–	16:70	17:90	16:95	23:90	23:20
95	55,60		18:10		17:45		
100	61,70	15:–	18:10	18:20	17:45	23:90	23:20
105	68,00		18:10		17:45		
110	74,60	15:–	18:10	18:20	17:45	26:10	
115	81,50		18:10		17:45		
120	88,80	16:50	18:10	18:20	17:45	26:10	24:30
125	96,30		18:10			26:10	
130	104,20	16:50	18:10	18:20	17:45		
135	112,00		18:10				
140	121,00	16:50	18:10		17:45		
145	130,00		18:10				
150	139,00	16:50	18:10		17:45		
160	158,00	16:50	18:10		17:55		
170	178,00	16:50	18:10		17:55		
180	200,00	16:50	18:10		17:55		
190	223,00	16:50	18:10		15:95		
200	247,00	16:50	18:10		15:95		
210	272,00	16:50			15:95		
220 SK	298,00	17:50			16:65		
230 SK	326,00	17:50			16:65		
240 SK	355,00	17:50					
250 SK	385,00	17:50			16:65		
260 SK	417,00	17:50			16:65		
270 SK	449,00	17:50					
280 SK	483,00				16:65		
290 SK	519,00	18:80					
300 GS	566,00	18:80			18:60		
305 GS	574,00	18:80			18:60		
320 GS	643,00	18:80			18:60		
335 GS	692,00	18:80			18:60		
350 GS	768,00	18:80			18:60		
355 GS	777,00	18:80			18:60		
380 GS	904,00	18:80			18:60		
385 GS	914,00	18:80			18:60		
400 GS	1001,00	18:80			18:60		
405 GS	1011,00	18:80			18:60		

Lagerlängder för varmvalsad resp. skalsvarvad stång generellt 5900 +200/–0 mm.
Centerlesslipad axel dim 8–10 mm längder ca 3000 mm. Övriga 5900 +200/–0 mm