Datasheet

Туре:	NS17
Itemnr.:	1622300101

Product describtion

NS17 is an exclusive linear LED lamp to install in ceilings. It is developed with a special lens-system, enabling you to very precisely control the light. NS17 can either be delivered with an ordinary fixed frame, a frame with a flexible lens and movable light column or with a frame developed to being built into a wall, which gives you a sleek and integrated look. The three product variations have an amazing quality of light in common, and can be delivered with fixed tilted lenses at 10, 15 or 30 degrees. NS17 is dimmable with most traditional dimmers available on the market, DALI and 0-10V. Both frame and reflectors can be delivered in a RAL colour of choice, but are delivered with a white frame and black reflector as standard. The exclusivity and options within NS17 does not neglect any of the usual LED benefits, as it is of genuinely high quality, meaning incredible energy efficiency and longevity.





Normasym Intl. Phone +4571995825 hello@normasym.com www.normasym.com

Technical Data

Lumen	Module 205lm
Beam Angle	10, 15, 30
Colors Avaliable	Warm white or Neutral white
Color Temperature	3000К, 4000К
Color Rendering	CRI80 (option CRI90+)
MacAdam	Step 3 (option Step 2)
Color Bin	V6
Consumption	Module 2.2W
Voltage Range	220 ~ 240VAC 50/60Hz
Efficiency	93 LPW
Equal To	NS17 2.2W = Halogenbulb QT 10W
Lifetime LEDs	50K hours at Ta = 25°C (L70) B10
Lifetime driver	50K hours at Ta = 25°C (MTBF) B10
Dimmable	DALI, 0-10V, Triac/Leading edge
IP Code	IP20
Class	2, Double Insulated
Working temp	-20 to 50 degree Celsius
Size	Pending on item - See our website
Hole size	Pending on item - See our website
Installation	Recessed
Weight	From 0,94 Kg to 2.91 KG
IES File	Yes
Certificates	CE, ROHS, TM21, LM80, IES
Warranty	5 years*
Housing	White, black or optional



Shipping

The products are to be delivered in package of 12 pcs.

Energy savings up to 70%

Halogen bulb QT 10W

NS17 2.2W

Normasym is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. The right is reserved to change specifications without prior notification or public announcement. *For more information on warranty see: normasym.com/terms/