

Your success counts



Field mount Indicators

for safe and hazardous areas































The F-Series is your first and safest choice for field mount indicators in safe and hazardous area applications. Especially in harsh weather conditions like rain, snow, salty atmospheres and temperatures between -40°C up to +80°C (-40°F up to 176°F).

Advantages

- Robust aluminum or stainless steel 316L field enclosure (IP67
 / NEMA Type4X). It is so rugged, a truck can even stand on it!
- Intrinsically Safe available ATEX, IECEx, FM and CSA approval for gas and dust applications.
- Intuitive "Know one, know them all!" configuration menu, saving time, cost and aggravation.
- Very diverse mounting possibilities: walls, pipes, panels or directly onto outdoor sensors!

Features

- Easy configuration with clear alphanumerical display.
- Displays flow rate, totals, level, temperature, pressure percentage and alarm values with engineering units.
- Clear 17mm(0.7") numeric and 8mm(0.3") alphanumeric digits.
- LED backlight, can be set to be red flashing in case of an alarm.
- Piegraph indication and 5½ extra large 26mm (1") digits.
- Auto backup of settings and running totals.
- Ability to process all types of signals: Sine wave (coil), NAMUR,
 NPN/PNP pulse, Reed-switch, Active pulse signals, (0)4-20mA.
- Modbus or HART communication.
- Configurable pulse, alarm or control outputs.
- Analog (0)4 20mA output.
- Power requirements: long life lithium battery, 8 24V AC/DC,
 110 230V AC or input / output loop powered.
- Sensor supply: 1.2 / 3 / 8.2 / 12 / 24V DC.







Feature overview









All info at a glance



to install



to program



Know one know them all!





User-friendly