

# Recommended application tool



ANZA X6 PA NoLoss



X6 PA NoLoss is an endless polyamide roller range available in following dimensions:

- Dimensions: 10 cm mini, 15 cm mini, 18 cm – and 25 cm maxi stick system. Requires standard mini handles in 6 mm dimension and maxi handles in 8 mm dimension (on the steel thread)
- Pile height 13 mm. Specially processed in finish line for high pick-up and release capacity, and high spreading rate without holidays
- **Typical achieved WFT in high build coatings (mastic): 150-300 microns**
- **Typical achieved WFT in PFP (passive fire protection): 500-800 microns**

*Tested and recommended by Jotun for Jotamastic Smart Pack HB.*

---

**Note! All Brushes inn the Anza I&C series will work perfectly in all paints, but for stipe coating purposes round brush is recommended!**

**Recommended in following paints:**

<b>Jotacoat F 60:</b>	<b>Roller X6 if wanted WFT exceeds 150 microns. Brush X2 or X2T after own choice</b>
<b>Jotacoat N 10:</b>	<b>Roller X6 if wanted WFT exceeds 150 microns. Brush X2 or X2T after own choice</b>
<b>Jotacoat Universal:</b>	<b>Roller X6 if wanted WFT exceeds 150 microns. Brush X2 or X2T after own choice</b>
<b>Jotamastic 90:</b>	<b>Roller X6 if wanted WFT exceeds 150 microns. Brush X2 or X2T after own choice</b>
<b>Safeguard universal ES:</b>	<b>Roller X6 if wanted WFT exceeds 150 microns. Brush X2 or X2T after own choice</b>
<b>Seaquantum Ultra:</b>	<b>Roller X6 if wanted WFT exceeds 150 microns. Brush X2 or X2T after own choice</b>
<b>SeaMate:</b>	<b>Roller X6 if wanted WFT exceeds 150 microns. Brush X2 or X2T after own choice</b>
<b>Muki Z 3000</b>	<b>Brush X2 or X2T after own choice</b>
<b>Marathon IQ</b>	<b>Roller X6. Brush X2 or X2T after own choice</b>

# Recommended application tool



## ANZA X3 Superior HiCap Felt



X3 Superior HiCap Felt is a polyester roller range available in following dimensions:

- Dimensions: 10 cm mini, 10 cm MIDI, 15 cm mini, 18 cm - and 25 cm maxi stick system. Requires mini handles in standard 6 mm dimension and maxi handles in 8 mm dimension (on the steel thread)
- Designed for low viscosity primers, topcoat and antifouling. Pile height 6-7 mm. Specially processed in finish line for high pick-up and release capacity, and high spreading rate. Provides a smooth surface with even coverage without holidays and no fibre loss
- **Typical achieved WFT in primers and topcoat: 100-125 microns**

**Tested and recommended by Jotun for Barrier Smart Pack and Hardtop One.**

**Note! All Brushes inn the Anza I&C series will work perfectly in all paints, but for stripe coating purposes round brush is recommended!**

**Recommended in following paints:**

<b>Jotun Penguard primer:</b>	<b>Roller X3. Brush X2 or X2T after own choice</b>
<b>Jotacoat F 60:</b>	<b>Roller X3 up to app. 125 microns. Brush X2 or X2T after own choice</b>
<b>Jotacoat N10:</b>	<b>Roller X3 up to app. 125 microns. Brush X2 or X2T after own choice</b>
<b>Safeguard universal ES:</b>	<b>Roller X3 up to app. 125 microns. Brush X2 or X2T after own choice</b>
<b>Jotun Pilot 2:</b>	<b>Roller X3 up to app. 125 microns. Brush X2 or X2T after own choice</b>